

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

Approved by Menominee County
Land Survey Remonumentation
Peer Group Under Act 345 Of

P.A. of 1990 Op 12/16, 1996

For corners in

MBENOMINEE
(County)

Located In:

Corner Code #

1. Public Land Survey

T 37N R 27W _____ H-7

T _____ R _____ _____

T _____ R _____ _____

T _____ R _____ _____

2. Property Controlling
in Section

S _____ T _____ R _____ _____

S _____ T _____ R _____ _____

3. Miscellaneous
Property in Sec.

S _____ T _____ R _____ _____

S _____ T _____ R _____ _____

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

I, William Lenca, in a field survey on Oct 14, 1996, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

Approved by Menominee County
Land Survey Remonumentation
Peer Group Under Act 345 Of

P.A. of 1990 Op 12/16, 1996

Mike Davis RLS
Chairman

RECEIVED FOR RECORD
6 DEC 20 AM 9:33
379 BR4
MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS
REGISTER OF DEEDS
LANSING, MICHIGAN 48906-1616

Register of Deeds Stamp & File Number

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6		5		4		3		2		1	
3												
4	7		8		9		10		11		12	
5												
6	18		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												

A. Description of original monument and accessories for subsequent restoration:

1852: Original Survey by Francis Coleman - B.T.'s - Hemlock, 12" - N45°E - 03 lks; Elm, 14" - S44°W - 07 lks. All original evidence for this corner has been destroyed by clearing and farming activities.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

We located the single proportional position for this corner and searched this area. The position falls in a large farm field with no original or occupational evidence available. The distance from this position West to the Little Cedar River fits reasonably well with GLO measurements. We set the corner based on our single proportion, and accepted this location as a careful and faithful reestablishment of the position of the original corner

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 5/8" x 24" Iron Rod/3-1/4" dia. Alum. cap stamped for corner location 14" below ground surface:

7" dia. Tamarack	N22°W	129.71 feet	Scr. NBT
16" dia. Cedar	S85°W	178.65 feet	Scr. NBT
Metal Survey Sign Post	N54°W	50.6 feet	
Falls in Large farm field - Nothing else nearby			

NOTE: All bearings are magnetic bearings. All distances are measured with steel tape. Distances to trees are to nail in side of tree.

Signed by William Lenca
Surveyor's Michigan License No. 26461

Date Oct. 31, 1996