

C.M.P.

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Menominee (County) Located In: Corner Code #
1. Public Land Survey T R
2. Property Controlling in Section S 10 T 37N R 28W 1, 15, 16, 2.
3. Miscellaneous Property in Sec. S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

Grid table with columns A-M and rows 2-13. Contains numbers 1-36 in a 6x6 pattern.

I, David B. Babbitt, in a field survey on 3/15, 1988, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefor as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

- A. Description of original monument and accessories and/or subsequent restoration:
1. West 1/16 corner on the north section line of Section 10. No previous record.
5. West 1/16 corner on the S. section line of Section 10. No previous record.
6. East 1/16 corner on the S. section line of Section 10. No previous record.
7. E 1/16 corner between Sections 3 and 10. No previous record.

- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
1. Set MPOL between the N 1/4 corner and the NW section corner of Section 10.
2. Set MPOL between the South 1/4 corner and the SW section corner of Section 10.
3. Set MPOL between the S 1/4 corner and the SE section corner of Section 10.
4. Set MPOL between the NE section corner and the N 1/4 corner of Section 10.

- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
DNR Monument 15. DNR Monument 16. DNR Monument 2. DNR Monument
4" aspen, S23W, 8.9' 4" tamarack, S10E, 12.6' 4" balsam, N20E, 45.3' 5" spru. N32W 23.2
3" aspen, N71W, 8.9' 5" tamarack, S43W, 5.9' 10" cedar, N31W, 41.1' 8" aspen S73E 33.3
3" cherry, N38E, 17.65' 5" tamarack, N81E, 4.1' tw13" cedars, N60W, 28.9'
4" balsam, N85E, 36.8' 4" cedar, N25W, 7.7' 6" balsam, S32W, 10.8' 4" r.maple S26E, 45.1'
5" balsam N74W, 59.6'

Signed by David B. Babbitt Date 9-29-88
Surveyor's Michigan License No. 21558