Approved by	Menomina	County
Land Survey		
	Under Act	

					Paer Group Under Act 345 Of	2,
	•			TO ATE	PA 01 1990 On 12/20 1992	
			RDATION CERT		CC Chairman	<u>-</u> -
_	Filing Re	equirement of	Act 74, Mich. P.	.A. 1970	系型 30 円	
For corners in MENOMINEE		0	Cado :-tt		NECEIVED 35 DEC 2 NGC #-3 ARBARA REGISTE METICINI	
(County)	Located In:	Corr	ner Code =##			
		26W	M-4			
 Public Land Survey 	<u>T</u> <u>B</u>					
	T R					
	T R T R					
2. Property Controlling	STR_				* * *	
in Section	ST_R_					
3. Miscellaneous	S T R			Regis	ter of Deeds Stamp & File Numbe	er.
Property in Sec.	S T R					
					A B C O F F G H I J K	, , ,
4. Lot No, ,	Recorded Plat				A B C D E F G H I J K	
5. Private Claims		***			2 - 6 - 5 - 4 - 4 - 5 - 2 -	<u> </u>
(SAMES AS A-4 T37	N-R25W)				3 	
XXVIII's self-self-		July 31		95	4 - 7 - 1 - 8 9 - 1 - 10 - 1 - 1 - 1	12-(
William Lenca	in a field survey on	-	19	•	5	╂╼┼┈
and the second section of the close co.	autroments of P A 74 Michiga	an P.A. 01 1970. to	e corner points menti	ioned*	6 18 17 16 15 14-	—-{a
· the the I observe weeks to	n conformance with regulation	ons and rules in	fittinis as redaince i		7 <u> </u>	╌┼╌
current manual of survey instr Management or by a decree of	a Court of Law and/or that the	e corner bouns in	らいけいいこつ いいいかっつい ユ	4114 0	8 19 20 21 22 23	-24-
	ik the culoc of the Michigae b	toard of Land Jul	146401201049999		9	╁╼┼╾
Court of Law; established,	re-established, monumente	d. re-monument	ed, recovered, lour	iu as	03029262726	<u>2</u> 5
expressed below:		wen and sance	may be recorded	1	1	
NOTE: Not more than 4 on this certificate	corners, all in the same to	JWII aliu lange,	may be recorded	1	2 31 32 33 34 35	36-
					3	
A. Description of original	monument and accessori	es and/or subs	equent restoration	η;		
10.19. Original Sur	nor by James H. Mullett -	R T 's - Hemloc	k. 5" - N30 ⁰ W - 8	1 lks: Heml	lock, 4" - \$38 ⁰ W - 24 lks. All	
	la a a a fana dan dan mayad ba	e county road it	nnrovemenis			
1900 Survey by A	thert Hass County Surveyo	or, shows subdi	vision of Section 7,	T37N-R25	W. His record states that the origin	nal
	Lineal Associate Augentin	an Na nourma	nument or witness	es are descri	nea.	
1982: Plat of Surve	w by William Lenca, RLS	No. 26461, sho	rws this corner as n	t relates to o	ther corners in Section 7, T37N-R3	25W.
The corner i	monument is described as a	a 3/4" x 18" iro	n pipe with identifi	cation cap.		
		والممالية والمسالة	rootoring or rees	tablishing c	, orner:	
 B. Description of corner 	evidence found and/or me	etnog applied ii	I teathing or rees	(aphoming o	•	
		-				
In a 1995 Survey in S	Section 12, T37N-R26W, v	ve found a 3/4"	x 18" iron pipe on	line betwee	n the NE Corner and the Southeast	
Comes of said Castin	n 10 and in line with an a	ncient fence lin	ie running West. T	ine corner p	OSITION THIS IN THE CERTELLINE OF A	
tt mina	North & South There is s	> 1/16th fence 1	/4 mile south of th	is location v	MICH HIS CHOSELY WITH THIS COLLECT	
position. This corne	r has been used by local su	irveyors for at I	east 13 years, and	is accepted a	is the best available evidence of the	•
position of the origin	al corner.		•			
			•			
					- common	2022
C. Description of monum Set 2" dia, Aluminur			ad to perpetuate t	ocating the	position of the corner of MI	CALCO
C. Description of monum	ent for corner and access	ones establish	co to perpetuate i		ALL ST.	<u>:</u> :
Set 2" dia, Aluminur	n Pipe/3-1/4" dia. Alum ca	th seambed for (COLINCI IOCANOII.		WEMA!	
10" dia. Cedar	N44°E	38,55 feet	Scr. NBT		LAND	-
7" dia, Cedar	\$38°E	48.06 feet	Scr. NBT		# SURVEY	. .
8" dia. Cedar	S54°W	41.43 feet	Scr. NBT		₹ 2661	
5" dia. Balsam	N37°W	55.45 feet	Scr. NBT			CUR
				.	PED LAN	MELLIN
NOTE: All bearings	s are magnetic bearings. A	All distances are	e measured with a s	steel tape. L	Distances to trees are to nail libride	401
tree.						i
. 1/2	n,			Nov	r. 17, 1995	
Signed by	in tous		Date			
_	26461			-	D BY MICHGAN STATE BOARD OF LAND SURVEYORS, J	AN. 28. 11
Surveyor's Michigan Licer	ise No			FORM APPROVI	KEA12ED W	SME 14, 61
	•		•		REVISE	D JAN., 1!