LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN -:	CORNER CODE NUMBER	1	
1. PUBLIC LAND SURVEY	т. 24 %, к. 7 ж.	L-11; M-11; M-13		
2. PROPERTY CONTROLL- 21 ING IN SECTION	5. ,T. 24 N. R. 7 W.	7		
3. MISCELLANEOUS PROPERTY IN SECTION	,T S., R E.			
4. LOT NO, REC				
5, PRIVATE CLAIMS			REGISTER OF DEEDS	
the corner points mentioned in re-established, monumented, re and rules therefore as required Bureau of Land Management of and 5 above were, in a field surv	lines 1 and 2 above were, in a monumented, recovered or rain the current manual of surverby a decree of a court of law ey on	rertify that under requirements of field survey on <u>March</u> estored as expressed below and rey instructions of the United Str. Furthermore, that the corner, 19, found, recovered, rest Michigan State Board of Registr	13, 19 80 in conformance wit tates Department of points mentioned incomed, established or a	, established, h regulations the Interior, n lines 3, 4 re-established
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX			909) conc. mon.	1/4 mile N
C. Continued: M-1 Fd. 1/2" x 18" rod re	3	Set 5/8" x 36" re	7	
rerod w/RLS cap. *26" Beech N	30°W 44.53	w/loc tag. 5" Maple	\$08°E	28.5
6" Maple S	50°W 53.68 22°F 61.40	4" Maple	S45°W	12.4
28" Maple Set ced. post w/loc t Cor. falls in cr E-W g	ag N45°E 47.	4" Maple	N50°W	9.4
Trail rd. S is E. B. Description of corner evider	raveira.			
L-11 Fd. 2" pipe in conc.				C 26 P
1977 Jerry Wilcox Ce M-11 Fd. & accepted 1/2" 30 & 31 (24-6). Corn	rt. Sur. of S-25. L x 18" rerod for corne er was set by Larry (. Cavanagh found this per common to Sec.'s 25 Cavanagh in Cert. Sur.	oipe. & 36 (24-7) an for S-36 (24-7	d Sec.'s) in 1972
and subsequently use	d by Matt McClung in ur. of Sec. 25 (24-7)	Cert. Sur. of Sec. 31	(24-6) in 1975	and by J.
M-13 Fd. & accepted 1/2"	x 18" rod for cor. co	ommon to T23 & 24N-R6 8	7W per RLS, L	arry Cava-
L. Wilcox in Cert. S M-13 Fd. & accepted 1/2" nagh Cert. Sur. in S 1909 J. G. Cavanagh 7 Est pestipusion menument	ec. 36, Liber S-1, Po Wit; 6" beech, N35 1) of NW1/4-NW1/4 of Se reormer and accessores estate	js. 24-27; Larry appare 72W,45.9'. Rigica 30 Te24N-R6W)enwidis	entlyset corner tant & one line	from one bet. J.L.
1	3.7			
Fd. 2" pipe in conc. 8	added ced. post	Fd. 1/2" x 18" re	rod w/pc. of s	teel fn
w/loc tag. 8" Maple N	44°W 83	post beside	€22°F	35.8
6" Maple twin S	46°W 13.3	6" W. Pine	N46°E	29.80
6" Maple twin S	52°E 20.31	7" W. Pine	S38°W	33.18
w/loc tag. 8" Maple N 6" Maple twin S 6" Maple twin S 10" Maple N Cor. falls on N edge E-W	trail	Set ced. post w/l	oc tag S45°W	47.9 33'
	_		min	· · · · · · · · · · · · · · · · · · ·
SIGNED BY Carl 7.	Roser 5	-13-81 DATE	CARL	10/4/19
			CARL	7
SURVEYOR'S MICHIGAN RE	GISTRATION NO. TEOE		LAND	OR
FOR STATE AND UNITED S	FATES AGENCIES:		No. 12028	10
SIGNED BY	CHIEF OF SURVEY PARTY	DATE	PED LANG	SURVIER
FOR STATE AND UNITED S SIGNED BY APPROVED AND SIGNED BY	MICHIGAN REGISTERED LA	DATE	***************************************	
r.			(SEAL)	
		LION	EEK IOMNOUTE	
SURVEYOR'S MICHIGAN RE	GISTRATION NO	MISS	AUKEE COUNTY	

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28. 1971 REVISED MAY 14. 1975