LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

	FOR CORNERS OF -:	LOCATED IN	I - :	CORNER CODE NUMBER		
2. XXMENTATION COLLEGE PLAT 5. PRIVATE CLAIMS 1. Carl F. Roser 1. Decarption of corner carlos Roser Roser Roser Roser Roser Roser Roser 1. Carl Roser 1. Carl F. Roser 1	I. PUBLIC LAND SURVEY	1. 24 N.	, R 7 w .	G-8; L-9		
2. AMMONINGENERAL 24 . 24 . 15 . 15 4. LOT NO. RECORDED PLAT 5. PRIVATE CLAIMS 1. Carl F. Roser	2. PROPERTY CONTROLL- ING IN SECTION—	22 ,T. 24 N.	R7 W.			
1. Carl F. Roser	_		İ			
1	4. LOT NO, RI	CORDED PLAT				
the currier points mentioned in lines 1 and 2 above were, in a field survey on May 15. 19.80. established re-established, monumented, re-monamented, recovered or restored as expressed below and in conformance with regulators and mules therefore as required in the current namen of survey instructions of the Chited States Department of the Interior Bineau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in these 3 and 3 above were, in a field survey on 19. [tound, recovered, restored, established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by: Decree of a Court of law: ***EXXXXMYKKMXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	5. PRIVATE CLAIMS				j .	
the contact points mentioned in lines 1 and 2 above were, in a field survey on May 15, 19.80. established menumental, resonation or restored as expressed below and in conformance with regulation and rules therefore as required in the current manual of survey instructions of the United States. Department of the Interior Bureau of Land Management or by a decree of a court of law. Furthermore, that the comer points mentioned in lines 3, and 3 above were, in a field survey on. 19. 19. 19. 19. 19. 19. 19. 19. 19. 19					FILING NUM	BEK
Drove 5/8" x 36" rerod w/RLS cap Prove 5/8" x 36" rerod w/RLS cap	the corner points mentioned in re-established, monumented, a and rules therefore as required Bureau of Land Management and 5 above were, in a field su as expressed below and in con	a lines 1 and 2 above-monumented, red in the current more by a decree of a rvey on	we were, in a fice covered or restorantial of survey a court of law.	Id survey on May 15, ored as expressed below and instructions of the United Surthermore, that the corner b, found, recovered, rest	in conformance wit tates Department of points mentioned i ored, established or i	established, h regulations the Interior, n lines 3, 4 re-established
Drove 5/8" x 36" rerod w/RLS cap Drove 5/8" x 36" rerod w/RLS cap 12" Maple	МИХИКУЛКИКИ ВИКИКИ ВИТИКИ	M KONTHANCH KINCH KAN	Dexection	химихихихиихи		
Drove 5/8" x 36" rerod w/RLS cap 12" Maple S44°W 18" Maple S46°E 54.5 8" Maple N80°E 8.44 4" Maple N52°E 43.3 10" Maple S10°E 48.04 Set cedar post w/loc tag W 33' 8" Maple S57°W 46.16 B. Description of corner evidence found and/or method applied in restoring or re-establishing corner: -8 Restored 1/4 cor. in line with old fn. to east at 50.0' west ofold cor. post per hwy. R.O.W. sheet. Corner is on approx. line of M-66 B. top tangent to North and is midway between Sec. cor.'s to N & S. A comp. straight line between Sec. cor. to N & S. Would be 4.7' West. Corner falls at east edge of M-66 B. top in curve and is in line with gravel road to Nest. -9 Fd. 1/8 cor. as set by RLS J. Wilcox in 1977 Certificate Survey. Estab. N1/8 cor. on E line S-22 per std. B.L.M. instructions. 5 Fd. 1/8 cor. as set by RLS J. Wilcox in 1977 Certificate Survey. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: G-8 Drove 5/8" x 36" rerod w/RLS cap P. Pole S15°E 73.85 8" R. Pine N65°E 63.55 *10" Cherry N80°W 32.46 Ctr. of b. top in curve W 11't *4" Cherry N80°W 32.46 (fn. N & E) *7" Maple twin S16°E 47.52 (fn. N & E) *10" Beech twin S35°W 21.46 *Replaced old cor. post w/new ced. post & *= Wits from RLS J. Wilcox In 1908 SURVEYOR'S MICHIGAN REGISTRATION NO. 12028 PLOATE SURVEYOR'S MICHIGAN REGISTRATION NO. 12028 SURVEYOR'S MICHIGAN REGISTRATION NO. 12028 SURVEYOR'S MICHIGAN REGISTRATION NO. 12028 PLOATE SURVEYOR'S MICHIGAN REGISTRATION NO. 12028 SURVEYOR'S MICHIGAN REGISTRATION NO. 12028 PLOATE SURVEYOR'S MICHIGAN REGISTRATION NO	. Continued:				15	
18" Maple S40-1: 54.5 8" Maple S10"E 48.04 4" Maple N52"E 43.3 10" Maple S10"E 48.04 B. Description of corner evidence found and/or method applied in restoring or re-establishing corner: -8 Restored 1/4 cor. in line with old fn. to east at 50.0' west of old cor. post per hwy. R.O.W. sheet. Corner is on approx. line of M-66 B. top tangent to North and is midway between Sec. cor.'s to N & S. A comp. straight line between Sec. cor. to N & S would be 4.7' West. Corner falls at east edge of M-66 B. top in curve and is in line with gravel road to West. -9 Fd. J. G. Cavanagh 1909 mon. for S1/4 S-24, cor. also used by RLS J. Wilcox in 1977 Cer Survey. Estab. N1/8 cor. on E line S-22 per std. B.L.M. instructions. Fd. 1/8 cor. as set by RLS J. Wilcox in 1977 Certificate Survey. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: G-8 Drove 5/8" x 36" rerod w/RLS cap Fd. 1" pipe in conc. added ced. post w/1 P. Pole S15°E 73.85 tag. 8" R. Pine N65°E 73.85 tag. 8" R. Pine N65°E 63.55 *10" Cherry N80°W 32.46 Ctr. of b. top in curve W 11'2 * 4" Cherry N80°E 19.83 **Old cor. fn. post Due E 50.0' * 7" Maple twin S16°E 47.55 (fn. N & E) **Replaced old cor. post w/new ced. post & * = Wits from RLS J. Wilcox Note of Michigan Registration No. 12028 SIGNED BY SURVEYOR MICHIGAN REGISTRATION NO. 12028 **SURVEYOR'S MICHIGAN REGISTRATION NO. 12028 PLOATE SURVEYOR MICHIGAN REGISTRATION NO. 12028 **SURVEYOR'S MICHIGAN REGISTRATION NO. 12028 **PAPROVED AND SIGNED BY DATE **CHIEF OF BUNNET PARTY APPROVED AND SIGNED BY DATE **CHIEF OF BUNNET PARTY APPROVED AND SIGNED BY DATE **CHIEF OF BUNNET PARTY **CHIEF OF BUNNET PARTY APPROVED AND SIGNED BY DATE **CHIEF OF BUNNET PARTY **CHIEF OF BUNNET PARTY **APPROVED AND SIGNED BY DATE **CHIEF OF BUNNET PARTY **CHIEF OF BUNNET PARTY **APPROVED AND SIGNED BY DATE **CHIEF OF BUNNET PARTY **APPROVED AND SIGNED BY DATE **CHIEF OF BUNNET PARTY **DATE **CHIEF OF BUNNET PARTY **APPROVED AND SIGNED BY DATE *	Drove 5/8" x 36" rer	od w/RLS cap			.S cap #14102 &	added ced.
A" Maple N52°E 43.3 10" Maple S10°E 48.08 Set cedar post w/loc tag W 33' 8" Maple S57°W 46.16 B. Description of corner evidence found and/or method applied in restoring or re-establishing corner: -8 Restored 1/4 cor. in line with old fn. to east at 50.0' west ofold cor. post per hwy. R.O.W. sheet. Corner is on approx. line of M-66 B. top tangent to North and is midway between Sec. cor.'s to N & S. A comp. straight line between Sec. cor. to N & S would be 4.7' West. Corner falls at east edge of M-66 B. top in curve and is in line with gravel road to West. -9 Fd. J. G. Cavanagh 1909 mon. for S1/4 S-24, cor. also used by RLS J. Wilcox in 1977 Cer Survey. Estab. N1/8 cor. on E line S-22 per std. B.L.M. instructions. 5 Fd. 1/8 cor. as set by RLS J. Wilcox in 1977 Certificate Survey. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: -8 Br. Pine N65°E 63.55 tag9 P. Pole S15°E 73.85 tag9 R. Pine N65°E 63.55 *10" Cherry N80°W 32.46 Ctr. of b. top in curve W 11't *4" Cherry N80°E 19.83 *10'd cor. fn. post Due E 50.0' *7" Maple twin S16°E 47.52 (fn. N & E) **Replaced old cor. post w/new ced. post & *= Wits from RLS J. Wilcox loc tag	12" Maple	\$44°W \$46°E			<i>e</i>	0 10
B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:						48.08
Restored 1/4 cor. in line with old fn. to east at 50.0' west ofo/d cor. post per hwy. R.O.W. sheet. Corner is on approx. line of M-66 B. top tangent to North and is midway between Sec. cor.'s to N & S. A comp. straight line between Sec. cor. to N & S would be 4.7' West. Corner falls at east edge of M-66 B. top in curve and is in line with gravel road to West. 9 Fd. J. G. Cavanagh 1909 mon. for S1/4 S-24, cor. also used by RLS J. Wilcox in 1977 Cer Survey. Estab. N1/8 cor. on E line S-22 per std. B.L.M. instructions. 6 Fd. 1/8 cor. as set by RLS J. Wilcox in 1977 Certificate Survey. C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: G-8 Drove 5/8" x 36" rerod w/RLS cap P. Pole S15°E 73.85 40.1" pipe in conc. added ced. post w/1 tag. 8" R. Pine N65°E 63.55 *10" Cherry N80°W 32.46 Ctr. of b. top in curve W 11't *4" Cherry N80°E 19.83 *01d cor. fn. post Due E 50.0' *7" Maple twin S16°E 47.56 *Replaced old cor. post w/new ced. post & *= Wits from RLS J. Wilcox loc tag SIGNED BY APPROVED AND SIGNED BY MICHIGAN REGISTRATION NO. 12028 PIONEER TOWNSHIP PIONEER TOWNSHIP	•	tag W	33'			46.16
G-8 Drove 5/8" x 36" rerod w/RLS cap P. Pole S15°E 73.85 8" R. Pine N65°E 63.55 *10" Cherry N80°W 32.46 Ctr. of b. top in curve W 11't *4" Cherry N80°E 19.83 *01d cor. fn. post Due E 50.0' *7" Maple twin S16°E 47.52 (fn. N & E) *12" Beech twin S35°W 21.48 *Replaced old cor. post w/new ced. post & *= Wits from RLS J. Wilcox loc tag SIGNED BY SURVEYOR'S MICHIGAN REGISTRATION NO. 12028 FOR STATE AND UNITED STATES AGENCIES: SIGNED BY CHIEF OF BURVEY PARTY APPROVED AND SIGNED BY MICHIGAN REGISTRED LAND SURVEYOR MICHIGAN REGISTRED LAND SURVEYOR DATE PIONEER TOWNSHIP	road to West. -9 Fd. J. G. Cavanagh 1 Survey.	909 mon. for	S1/4 S-24,	cor. also used by RL	S J. Wilcox in	1977 Cert.
P. Pole S15°E 73.85 tag. 8" R. Pine N65°E 63.55 *10" Cherry N80°W 32.46 Ctr. of b. top in curve W 11'½ * 4" Cherry N80°E 19.83 *Old cor. fn. post Due E 50.0' * 7" Maple twin S16°E 47.52 (fn. N & E) *12" Beech twin S35°W 21.46 *Replaced old cor. post w/new ced. post & * = Wits from RLS J. Wilcox loc tag SIGNED BY APPROVED AND SIGNED BY DATE CARL SURVEYOR'S MICHIGAN REGISTRATION NO. 12028 SIGNED BY DATE CHIEF OF BURVEY PARTY APPROVED AND SIGNED BY DATE MICHIGAN REGISTERED LAND SURVEYOR (SEAL) PIONEER TOWNSHIP	r 0				1 0	
SIGNED BY CALT. POSEN 5-18-81 DATE SURVEYOR'S MICHICAN REGISTRATION NO. 12028 FOR STATE AND UNITED STATES AGENCIES: SIGNED BY DATE CHIEF OF BURVEY PARTY APPROVED AND SIGNED BY MICHIGAN REGISTERED LAND SURVEYOR MICHIGAN REGISTERED LAND SURVEYOR PIONEER TOWNSHIP	Drove 5/8" x 36" rer	od w/RLS cap	70.05	Fd. 1" pipe in co	nc. added ced.	post w/loc
SIGNED BY CALT. POSCY 5-18-81 DATE SURVEYOR'S MICHIGAN REGISTRATION NO. 12028 FOR STATE AND UNITED STATES AGENCIES: SIGNED BY DATE CHIEF OF BURVEY PARTY APPROVED AND SIGNED BY MICHIGAN REGISTERED LAND SURVEYOR MICHIGAN REGISTERED LAND SURVEYOR PIONEER TOWNSHIP	P. Pole 8" R. Pine	515°E N65°E	73.85 63.55	tag. *10" Cherry	N80°W	32.46
SIGNED BY CALT. POSCY 5-18-81 DATE SURVEYOR'S MICHIGAN REGISTRATION NO. 12028 FOR STATE AND UNITED STATES AGENCIES: SIGNED BY DATE CHIEF OF BURVEY PARTY APPROVED AND SIGNED BY MICHIGAN REGISTERED LAND SURVEYOR MICHIGAN REGISTERED LAND SURVEYOR PIONEER TOWNSHIP	Ctr. of b. top in cu	rve W	11 '±	* 4" Cherry	N80°E	19.83
SIGNED BY	*Old cor. fn. post	Due E	50.0'	* 7" Maple twin	\$16°E	47.52
SIGNED BY	*Replaced old cor. po	st w/new ced.	post &	* = Wits from RLS	J. Wilcox	21.40
MICHIGAN REGISTERED LAND SURVEYOR (SEAL) PIONEER TOWNSHIP	loc tag				we OF M	lander.
MICHIGAN REGISTERED LAND SURVEYOR (SEAL) PIONEER TOWNSHIP	SIGNED BY Carl 7.	Roser	5-	-/8-81 _{DATE}	SIG CARL	Q ₃
MICHIGAN REGISTERED LAND SURVEYOR (SEAL) PIONEER TOWNSHIP	SURVEYOR'S MICHIGAN R	EGISTRATION N	10. 12028	<u>.</u>	F. ROS	ER #
MICHIGAN REGISTERED LAND SURVEYOR (SEAL) PIONEER TOWNSHIP	FOR STATE AND UNITED	STATES AGENC	IES:	.	No. 12028	TO I
MICHIGAN REGISTERED LAND SURVEYOR (SEAL) PIONEER TOWNSHIP	SIGNED BY	CHIEF OF SUCUE	Y PARTY	DATE	PED LANG	Saline
PIONEER TOWNSHIP	APPROVED AND SIGNED	BY	· · · · · · · · · · · · · · · · · · ·	DATE		
		MICHIGA	N REGISTERED LAND	SURVEYOR	(SEAL)	
SURVEYOR'S MICHIGAN REGISTRATION NO. MISSAUKEE COUNTY				PI	ONEER TOWNSHIP	
	SURVEYOR'S MICHIGAN R	EGISTRATION N	Ю	MI	SSAUKEE COUNTY	