

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. 29 ^{N.} R. 2 ^{E.}	L-9; M-12
2. PROPERTY CONTROLLING IN SECTION 25	T. 29 ^{N.} R. 2 ^{E.}	14; 16
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ ^{N.} R. _____ ^{E.}	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on June 24, 1975, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

~~A. Description of original monuments as recovered or re-established:~~

C. (continued)

16
Set 1" Pipe
7" Maple N10°W 56.95
18" R. Pine N65°W 92.4


B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- L-9 Found 1/2" iron bar as established in a previous survey by G.F. DeLaMater.
- M-12 Found concrete monument in place, in line fence west.
- 14 Set by standard survey procedure for the subdivision of section.
- 16 Set by standard survey procedure for the subdivision of section.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-9	M-12	14
Added DNR monument	Left conc. mon. in place	Set 1" Pipe
9" B. Oak N35°W 22.30	12" Maple S65°W 29.5	8" Maple N22°E 54.0
10" B. Oak S20°W 53.35	8" Maple S36°E 65.1	8" R. Pine S73°W 53.0
20" R. Pine Stump		
S89°E 22.20		

SIGNED BY *Kenneth J. Ostling* DATE _____
 SURVEYOR'S MICHIGAN REGISTRATION NO. 10068



FOR STATE AND UNITED STATES AGENCIES:
 SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY
 APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET