## LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

	LOCATED IN-:	CORNER CODE NUMBER	
1. PUBLIC LAND SURVEY	T. 31 N. 14 E	B-12; A-12	_
2. PROPERTY CONTROLL- 3:	l ,T. 31 N., R. 4 E	15; 9;	
3. MISCELLANEOUS PROPERTY IN SECTION	, T		-
4. 1.OT NO,, REG	CORDED PLAT		-
5. PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND
I. KENNETH J. OSTLING	do hereby	certify that under requirement	is of P.A. 74, Michigan P.A. of 1970,
re-established, monumented, re and rules therefore as required Bureau of Land Management o and 5 above were, in a field sur	e-monumented, recovered or in the current manual of sur r by a decree of a court of law vey on	restored as expressed below a vey instructions of the United w. Furthermore, that the cor _, 19, found, recovered, a	, 1982, established, and in conformance with regulations I States Department of the Interior, ner points mentioned in lines 3, 4 restored, established or re-established istration for Land Surveyors or, by a
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	KKYTRYK XOEK OKOKA XKKYK KUKOKOK	жинжимжимж	
C. (CONTINUED)	<u>A-12</u>		
	IR MONUMENT :DAR S3°E 25.	1'	
	MAPLE N41°E 25.		
		SUBDIVISION OF SECTION FOR THE SUBDIVISION O	
SET CORNER BY STANDAR 2 SET CORNER BY STANDAR INTERSECTION OF 1/4 L	RD SURVEY PROCEDURE D SURVEY PROCEDURE F INES. NCE CORNER, PROBABLY	FOR THE SUBDIVISION OF OR THE SUBDIVISION OF AS RESTORED BY M.S.H	F SECTIONS. SET AT CALCULA
SET CORNER BY STANDAR 2 SET CORNER BY STANDAR INTERSECTION OF 1/4 L 2 FOUND 3/4" PIPE AT FE ACCEPTABLE AS PROPER  C. Description of monument for	RD SURVEY PROCEDURE D SURVEY PROCEDURE F INES. NCE CORNER, PROBABLY LOCATIONS FOR CORNER	FOR THE SUBDIVISION OF OR THE SUBDIVISION OF AS RESTORED BY M.S.H.	OF SECTIONS.  SECTIONS. SET AT CALCULA  I.D. SURVEY IN 1965. APPEA  the position of the corner:
SET CORNER BY STANDAR 2 SET CORNER BY STANDAR INTERSECTION OF 1/4 L 2 FOUND 3/4" PIPE AT FE ACCEPTABLE AS PROPER	RD SURVEY PROCEDURE  D SURVEY PROCEDURE F INES.  NCE CORNER, PROBABLY LOCATIONS FOR CORNER  or corner and accessories estal  SET 5/8" ROD WITH	FOR THE SUBDIVISION OF OR THE SUBDIVISION OF AS RESTORED BY M.S.H.  blished to perpetuate locating to the subdivision of the su	SECTIONS. SET AT CALCULA  I.D. SURVEY IN 1965. APPEA  the position of the corner:  1-12 H CAP
SET CORNER BY STANDAR  2 SET CORNER BY STANDAR  INTERSECTION OF 1/4 L  2 FOUND 3/4" PIPE AT FE  ACCEPTABLE AS PROPER  C. Description of monument for  15  5/8 ROD W/ RLS CAP	RD SURVEY PROCEDURE  D SURVEY PROCEDURE F INES.  NCE CORNER, PROBABLY LOCATIONS FOR CORNER  or corner and accessories estal  SET 5/8" ROD WITH	FOR THE SUBDIVISION OF OR THE SUBDIVISION OF AS RESTORED BY M.S.H.  blished to perpetuate locating to the subdivision of the su	SECTIONS. SET AT CALCULA  I.D. SURVEY IN 1965. APPEA  the position of the corner:  1-12 H CAP
SET CORNER BY STANDAR  2 SET CORNER BY STANDAR  INTERSECTION OF 1/4 L  2 FOUND 3/4" PIPE AT FE  ACCEPTABLE AS PROPER  C. Description of monument for  15  5/8 ROD W/ RLS CAP  BALSAM N26°W 35.2"  SPRUCE N65°E 9.1"	RD SURVEY PROCEDURE  D SURVEY PROCEDURE F INES.  NCE CORNER, PROBABLY LOCATIONS FOR CORNER  or corner and accessories estal  SET 5/8" ROD WITH 8" J. PINE N5°W 7" J. PINE N83°E	FOR THE SUBDIVISION OF OR THE SUBDIVISION OF AS RESTORED BY M.S.H.  blished to perpetuate locating to the substitution of the	SECTIONS. SET AT CALCULA  I.D. SURVEY IN 1965. APPEA  the position of the corner:  1-12 H CAP
SET CORNER BY STANDAR  2 SET CORNER BY STANDAR  INTERSECTION OF 1/4 L  2 FOUND 3/4" PIPE AT FE  ACCEPTABLE AS PROPER  C. Description of monument for  15  5/8 ROD W/ RLS CAP  BALSAM N26°W 35.2"  SPRUCE N65°E 9.1"	RD SURVEY PROCEDURE  D SURVEY PROCEDURE F INES.  NCE CORNER, PROBABLY LOCATIONS FOR CORNER  or corner and accessories estal  SET 5/8" ROD WITH 8" J. PINE N5°W 7" J. PINE N83°E	FOR THE SUBDIVISION OF OR THE SUBDIVISION OF AS RESTORED BY M.S.H.  blished to perpetuate locating to the substitution of the	SECTIONS. SET AT CALCULA  I.D. SURVEY IN 1965. APPEA  the position of the corner:  1-12 H CAP
SET CORNER BY STANDAR  2 SET CORNER BY STANDAR  INTERSECTION OF 1/4 L  2 FOUND 3/4" PIPE AT FE  ACCEPTABLE AS PROPER  C. Description of monument for  15  5/8 ROD W/ RLS CAP	RD SURVEY PROCEDURE D SURVEY PROCEDURE F INES. NCE CORNER, PROBABLY LOCATIONS FOR CORNER or corner and accessories estal 9 SET 5/8" ROD WITH 8" J. PINE N5°W 7" J. PINE N83°E	FOR THE SUBDIVISION OF OR THE SUBDIVISION OF AS RESTORED BY M.S.H.  blished to perpetuate locating to the substitution of the	SECTIONS. SET AT CALCULA  I.D. SURVEY IN 1965. APPEA  the position of the corner:  1-12 H CAP
SET CORNER BY STANDAR  2 SET CORNER BY STANDAR  INTERSECTION OF 1/4 L  2 FOUND 3/4" PIPE AT FE  ACCEPTABLE AS PROPER  C. Description of monument for  15  5/8 ROD W/ RLS CAP  BALSAM N26°W 35.2"  SPRUCE N65°E 9.1"	RD SURVEY PROCEDURE  D SURVEY PROCEDURE F INES.  NCE CORNER, PROBABLY LOCATIONS FOR CORNER  or corner and accessories estal  SET 5/8" ROD WITH 8" J. PINE N5°W 7" J. PINE N83°E  CISTRATION NO. #10	FOR THE SUBDIVISION OF OR THE SUBDIVISION OF AS RESTORED BY M.S.H.  blished to perpetuate locating to the substitution of the	SECTIONS. SET AT CALCULA  I.D. SURVEY IN 1965. APPEA  the position of the corner:  1-12 H CAP
SET CORNER BY STANDAR  2 SET CORNER BY STANDAR  INTERSECTION OF 1/4 L  2 FOUND 3/4" PIPE AT FE  ACCEPTABLE AS PROPER  C. Description of monument for  15  5/8 ROD W/ RLS CAP  BALSAM N26°W 35.2'  SPRUCE N65°E 9.1'  SURVEYOR'S MICHIGAN RE  FOR STATE AND UNITED S	RD SURVEY PROCEDURE  D SURVEY PROCEDURE F INES.  NCE CORNER, PROBABLY LOCATIONS FOR CORNER  or corner and accessories estal  9 SET 5/8" ROD WITH 8" J. PINE N5°W 7" J. PINE N83°E  GISTRATION NO. #10  TATES AGENCIES:	FOR THE SUBDIVISION OF OR THE SUBDIVISION OF AS RESTORED BY M.S.H.  blished to perpetuate locating to the substitution of the	SECTIONS. SECTIONS. SECTIONS. SET AT CALCULA  H.D. SURVEY IN 1965. APPEA  the position of the corner:  1-12 H CAP N89°E 12.6' S77°W 14.4'  KENNETH J. OSTLING JAND 10068  AND 10068
SET CORNER BY STANDAR  2 SET CORNER BY STANDAR  INTERSECTION OF 1/4 L  2 FOUND 3/4" PIPE AT FE  ACCEPTABLE AS PROPER  C. Description of monument for  15  5/8 ROD W/ RLS CAP  BALSAM N26°W 35.2'  SPRUCE N65°E 9.1'  SIGNED BY  SURVEYOR'S MICHIGAN RE  FOR STATE AND UNITED S  SIGNED BY	RD SURVEY PROCEDURE  D SURVEY PROCEDURE F INES.  NCE CORNER, PROBABLY LOCATIONS FOR CORNER  or corner and accessories estal  9 SET 5/811 ROD WITH 811 J. PINE N5°W 711 J. PINE N83°E  GISTRATION NO. #10  TATES AGENCIES:	FOR THE SUBDIVISION OF OR THE SUBDIVISION OF AS RESTORED BY M.S.H.  blished to perpetuate locating to the substitution of the	SECTIONS. SET AT CALCULA  I.D. SURVEY IN 1965. APPEA  the position of the corner:  1-12 H CAP

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971 REVISED MAY 14, 1975