LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 31 N., R. 4 E.	E-11; D-11; D-13;
2. PROPERTY CONTROLLING IN SECTION 32	,T. 31 N., R. 4 E.	11
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. _____ , RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, KENNETH J. OSTLING, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on APRIL 14, 1982, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. (CONTINUED)

11
5/8" ROD WITH CAP
9 " R. MAPLE N45°E 29.5'
12" R. OAK S10°E 6.4'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

E-11 FOUND 1 1/4" PIPE AT ROAD INTERSECTION, ORIGIN UNKNOWN BUT USED IN 1965 SURVEY BY MSHD.

D-11 FOUND 1/2" PIPE AS ESTABLISHED BY MSHD IN 1965 SURVEY. AT MIDPOINT ON LINE BETWEEN SECTION CORNERS.

D-13 SET CORNER BY SINGLE PROPORTIONATE MEASUREMENT BETWEEN SE CORNER OF SECTION 32 AND SW CORNER OF SECTION 31. COULD FIND NO PREVIOUS EVIDENCE OF CORNER.

11 SET CORNER BY STANDARD SURVEY PROCEDURE FOR THE SUBDIVISION OF SECTIONS.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-11			D-11			D-13		
1 1/4" PIPE (FOUND)			SET DNR MONUMENT AT PIPE			DNR MONUMENT		
14" CEDAR	N21°W	43.4'	8" R. OAK	N76°E	14.5'	8 " BALSAM	S15°W	3.4'
12" W. PINE	S16°W	27.5'	7" R. OAK	N75°W	9.0'	12" TAMRACK	S26°E	34.5'

SIGNED BY Kenneth J Ostling DATE 8/17/82

STATE OF MI KEN 10068 LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. #10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ MONTMORENCY COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET