LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 31 N., R. 4 E.	D-12;
2. PROPERTY CONTROLLING IN SECTION 32	,T. 31 N., R. 4 E.	12; 8; 9
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. _____, RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, KENNETH J. OSTLING, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on APRIL 15, 1982, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. (CONTINUED)

9

SET 5/8" ROD WITH CAP
14" CEDAR N81°E 43.2'
18" CEDAR S67°E 36.8'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

D-12 SET AT COMPUTED INTERSECTION OF TRUE 1/4 LINES, ACCORDING TO STANDARD SURVEY PROCEDURE FOR THE SUBDIVISION OF SECTIONS.

12 SET CORNER BY STANDARD SURVEY PROCEDURE FOR THE SUBDIVISION OF SECTIONS.

8 SET CORNER BY STANDARD SURVEY PROCEDURES FOR THE SUBDIVISION OF SECTIONS.

9 SET BY STANDARD SURVEY PROCEDURE FOR THE SUBDIVISION OF SECTIONS.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-12			12			8		
5/8" ROD WITH CAP			5/8" ROD WITH CAP			5/8" ROD WITH CAP		
5" R. MAPLE	S75°W	37.6'	20" S. MAPLE	S78°E	61.6'	6 " B. OAK	N20°E	17.0'
6" R. MAPLE	N72°E	33.3'				12" J. PINE	S20°E	73.'

NO OTHER BT'S AVAILABLE

SIGNED BY Kenneth J Ostling DATE 8/7/82

STATE OF MICHIGAN KENNETH J. OSTLING LAND SURVEYOR No. 10068 (SEAL) REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. #10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ MONTMORENCY COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET