LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For comers in	•		o, 1001 7-1, 10110111					
MONTHOREDICY	Located	in C	orner Code ##	1				
(County)		3 ()	Office Code		•			
		A		ł				
1. Public Land Survey			8-8					
								
		_ R						
		R	5, 6, 9					
2. Property Controlling			<u>5, 6, 9</u>]				
in Section		R		1		•		
3. Miscellaneous		R		Registr	er of Deeds Str	amp & File Number		
Property in Sec.	S T	R						
4. Lot No	, Recorded Plat				ABCDE	FGHIJKL		
5. Private Claims								
				2	- 6- 5- -	╶┊╼╃╾┊╼╂╌┇╼╂╌┆		
				3	├─┼─┼	·┼╸ ╂┈ ┞┈╂┈╏╸ ╂		
				4	├─┊─ ┼─ ┊─┼	- - 10 11 12		
I, <u>C.T. KIISKILA</u>				-	 	 		
do hereby certify that under						-181514		
in lines 1 and 2 above were current manual of survey in:								
Management or by a decree		•						
above were in conformance				-		-21		
Court of Law; established	re-established, mon	umented, re-monume	nted, recovered, fou	ind as		 		
expressed below:				10	- 30 - 28 - T	-2 18 27 26 25		
NOTE: Not more than 4	•	same town and rang	e, may be recorded	11	 	┤╞┋		
on this certificat	e.			12	31-32-	-33 - 34 - 38 - 36		
				13				
A. Description of original	I monument and ac	cessories and/or sul	osequent restoratio	n:		SERVICE OF THE PROPERTY.		
B-B	5		6		مجتو 9	TE OF MICHIGAN		
					<i>4</i> 8	CARL		
(NO EVIDENCE OF 6.L.O.	• •	•			7 3	KIISKILA .		
AS CALLED OUT IN THE 6.1	O. LINE NOTES; UNLI	ESS NOTED IN ITEM "B'	•		1 ★:	LAND *		
RELOW.)					4 1	SURVEYOR		
					1 - 3	No.		
					16	33981		
					J'68	JAN CURYE		
						33981 SURE AND SURE		
						SED LAND SURFER		
B. Description of corner	evidence found and	l/or method applied	in restoring or rees	tablishing cori	ner:			
9-0	5		é		9			
ESTABLISHED CTR S-19 AT ESTABLISHED THE NN COR OF ESTABL			ESTABLISHED CTR (F NE 1/4 5-19	ESTABLISHED SE COR OF SN 1/4			
INTERSECTION OF 1/4 LINE	S. 5N 1/4 OF I	IE 1/4 DF 5-19 PER	PER STANDARD BLM	INSTRUCTIONS.	DF NE 1/4 OF	5-19 PER STANDARD		
ROAD INTERSECTION	STANDARD BE	M INSTRUCTIONS.	FD 1 1/4" PIPE (N	IRE N-S-E-W)	BLM INSTRUCTI	IONS. FD 1 1/4"		
(W'LY-SE'LY-SW'LY) 15 24	6' TRAIL RD (RIVE TO CABIN)	S72°56'N, 100.4'.		PIPE (PIPE ST	TICKS 48" OUT OF		
WEST.	NE-SN 15 28	NE-SW IS 26' EAST & 20' SOUTH. FD 1 3/4" PIPE 865°54'W,				5ROUND & WIRE RUMS N-S-E-W) 572°52'N, 100.2'.		
	FD 1 3/4" F							
	215.0° (AT	E END OF FENCE).			·			
C. Description of monum	ent for corner and a	accessories establisi	hed to perpetuate I	ocating the po	sition of the co	orner:		
·				2 0-				
B-B	5		6		9			
SET DWR HOW & CED POST.		52" REROD W/CAP &	DR 5/8" X 32" RER	DD W/CAP &	SET 5/8 X 34°	' REROD W/CAP &		
	CED POST.		CED POST.		CED POST.			
4° QUAD HAPLE N42°N								
4" CLUMP MAPLE N62°E		N54°W 2.20		E 12.86		N44°W 10.44'		
11° DAK 572°E		N56°E 29.01'		W 21.12'		N67°E 23.85'		
3-8" TRPL MAPLE S60"W		\$50°€ 71.27'		E 24.93'		S45°E 20.21'		
	4° POPLAR	564°W 22.16'	10" DAK N519	£ 23.25°	10. OWK	\$17°W 15.98'		
						CED POST HAVE		
_					ROCK PILED AR	ICUMD.		
Signed byCar	L. T. Kus	Up. La	5-1-	2-2	7-97			
		accord	1 1918		• • •			
Surveyor's Michigan Licer		33981	Date					