LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 12 N. S., R. 12 E. W.	I-7;J-7;K-7;K-8;K-9
2. PROPERTY CONTROLLING IN SECTION	,T. N. S., R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on February 6, 19 79, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on , 19 , found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. continued

K-8

Fd. Conc. Mon. w/Bronze cap
Added Ced. Post w/Loc. Tag

*13" W.Pine	N60°E	28.40
*18" Maple in Clump of two	S20°E	33.55
*17" W.Pine	S55°W	23.47

*equals same Wits. as Lake State Sur. & Engr.

K-9

Fd. 3/4" Re-rod

4" B.Oak	N50°W	5.00'
*15" B.Oak	S35°E	17.85
*20" W.Oak	S45°W	48.67

*equals same Wits. as Lake State Surveyors & Engr's.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

I-7 Fd. 1" pipe & clam shells as set by RLS, Norm Ochs, 1977 From L.S. Shepherd evidence dated 1937. Corner falls in old E-W fence remains.

J-7 Fd. 3/4" pipe as recovered by RLS, Norm Ochs in 1978.

K-7 Fd. 1 1/2" angle iron as recovered by RLS, Ralph Smith, 1953 and subsequently used by RLS, Norm Ochs, 1978.

K-8 Fd. Conc. Mon. with bronze cap stamped Blass Surveys; witnessed by Lake State Surveyors and Engineers, 1973.

K-9 Fd. 3/4" re-rod as recovered by Lake State Surveyors and Engineers, 1973.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-7

Fd. 1" pipe; added Ced.Post w/Loc. Tag.

* 8"W.Oak	N30°W	13.58
* 4" W.Pine	N35°E	25.70
* 7" W.Oak	S45°E	13.93
*20" W.Pine	S50°W	29.24

*equals same Wits. as N.Ochs

J-7

Fd. 3/4" pipe

*Tw.R.Oak(13"&10")	N35°E	26.33
*18" Basswood	S30°E	29.28
*36" R.Oak	S50°W	76.04
Set Ced.Post w/Loc. Tag		
	Due W	33'
Ctr.N-S gravel rd.	Due W	13'±
Ctr. Trail rd. E'ly	Due S	4'±

*equals same Wits. as N.Och's.

K-7

Fd. 1 1/2" Angle Iron

*Twn.Swp.Oak(11"&14")	N65°W	33.58
*10" W.Oak	N05°W	20.85
*24" W.Pine	N70°E	107.48
Set Ced.Post w/Loc. Tag		
	Due N	16 1/2'
Ctr.E-W tr.rd.	Due S	2'±
Fork in Trail	Due E	100'±

*equals same Wits. as N.Ochs.

SIGNED BY Carl F. Roser 2-12-79 DATE

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY DATE
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY DATE
MICHIGAN REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO.

BROOKS TOWNSHIP
NEWAYGO COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET