MAR 1 3 2000

NEWAYGO COUNTY REGISTER OF DEEDS

1999 Newaygo County Remonumentation Project LINDA M. BROWN

SECTION

LAND CORNER RECORDATION CERTIFICATED FEB 28 PM 1 11

For corners in			O	7
Newaygo (County)	Located in:	Corner Code#	Sinda?	M. Brown
1. Public Land Survey	T <u>13N</u> R <u>12W</u> T R T R	H-3	1	
Property Controlling     in Section	TR STR STR		vol. <b>2</b>	327
<ol><li>Miscellaneous Property in Sec.</li></ol>	STR STR		Register of Deeds Star	mp & File Number
4. Lot No, Record	ed Plat		ABCDEF	
I, Norman L. Ochs, in do hereby certify that under require points mentioned in lines 1 and 2 a therefore as required in the current Department of the Interior, Bureau Law and/or that the corner points	a field survey on October 5 ements of P. A. 74, Michigan P bove were in conformance with t manual of survey instructions of Land Management or by a s mentioned in lines 3.4 as	7.A. of 1970, the corner or regulations and rules of the United States and decree of a Court of ond 5. above, were in	5   1   1   1   6   6   18   17   16	- 3 - 2 - 1 - - 10 - 11 - 12 - - 15 - 14 - 13 -
conformance with the rules of t Decree of a Court of Law; establis recovered, found as expressed below	he Michigan Board of Land hed, re-established, monumer	Surveyors or hy a	7 8 19 - 20 - 21 9	- 22 - 23 - 24 -
Note: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.			$   \begin{array}{c cccccccccccccccccccccccccccccccccc$	<del>- - - - </del> -
South One Quarter Corner, Se	ction 3, Everett Township,	Newaygo County, Michigan.	$\frac{12}{13}$ $\frac{31}{13}$ $\frac{32}{13}$ $\frac{33}{13}$	34 + 35 + 36 -
A. DESCRIPTION OF ORI	GINAL MONUMENT AN	ND ACCESSORIES AND/C	R SUBSEQUENT RE	ESTORATION:
G.L.O. J.H. Mullett 1837 8" Beech S33°E 39 Links (2 14" Beech N16°W 27 Links	(25.74')#1 September 10, 1906 Book 21 Page 108 (s (17.82')#2 Book B Page 22 and 25 24" Pine Stump N011%" (39 Links (25.74')#3			
Delos G. Anderson (County Surveyor) Book A Pages 217 January 1 & 2, 1898 Old Government Corner		Newaygo County Ro	pad Commission Shee	•
		Telephone Pole N60 12" Ash S12°E 34.9	#5	
B BESSELEN		8" Maple S53°E 49.5		OVER 🔖
B. DESCRIPTION OF COR REESTABLISHING CORNE	INER EVIDENCE FOUN ER:	ID AND/OR METHOD APP	PLIED IN RESTORING	G OR
Found 4" diameter Harrison centerline of the East and Wino obvious occupation to the condition.	rosi diluminuus road is 7	' TRRI to South and the Wood	to line anima Cauth ia	4444E ( =) .
C. DESCRIPTION OF MON THE POSITION OF THE CO	IUMENT FOR CORNER PRNER:	R AND ACCESSORIES ES	TABLISHED TO PER	RPETUATE LOCATING
Accepted 4" diameter Harris quarter corner and is accept	on cast iron monument : ed as a careful and faith	20" long marked "County S Iful reestablishment of the	Surveyor" as a substar original corner.	ntial marker for the
Power Pole S60°W 104.73'   20" Maple N60°E 100.72' Se 12" Maple S08°E 73.07' Set 6" X 8" Wood Fence Post N3 6" X 8" Wood Post N04°E 25	it spike with tag #22439 i spike with tag #22439 in 36°W 31.38' Set spike wi	in South side of tree. #9	t Corner, #11	
Signed by Norman L. Ochs	J. Ochs	DateOctobe	er 22, 1999	
Surveyor's Michigan License No	. 22439	Form approved by Mich	nigan State Board of Land S	Surveyors, Jan 28, 1971
Approved by Peer Review Group On Norman L. Ochs, County Representa	October 28, 1999		A WICH	Revised May 14, 1975 Revised Jan., 1983

NORMAN L OCHS

## A. Description (cont.)

Patrick A. Salisbury R.L.S. #13594
May 21, 1974 Found ½" Rod raised with Railroad Spike
Telephone Pole N21°E 29.88' #7
8" - 6" Twin Ash S10°E 35.74' #5
Power Pole S65°W 104.80' #8

SURVEY & REMONUMENTATION

MAR 1 3 2000

Norman L. Ochs, R.L.S. #22439
March 21, 1989 Drawing Number 89044B
Found ½" Rod raised with Railroad Spike
10" Maple N55°E 100.70' #9
6" Maple S10°E 73.12' #10
Square Fence Post N25°W 31.09' #11
Power Pole S65°W 104.80' #8

SECTION

Norman L. Ochs, R.L.S. #22439

December 4, 1990 LCRC #1058

Found ½" Rod raised with Railroad Spike - Removed and set a 4" diameter Harrison cast iron monument marked "County Surveyor"

Power Pole S65°W 104.83' #8
6" Maple S10°E 73.00' #10

12" Maple N60°E 100.75' #9

Wood Post North 25.23' #12