

LAND CORNER RECORDATION CERTIFICATE
 Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Oakland Located in: Highland Township Corner Code # _____
 (County)

38635

1. Public Land Survey T3N R7E I-9
 T R
 T R
 T R
 T R
 T R
 T R
 T R

2. Property Controlling in Section S T R
 S T R
 S T R
 S T R

3. Miscellaneous Property in Sec. S T R
 S T R

LIBER 21077 PAGE 440
 \$9.00 MISC RECORDING
 \$2.00 REMONUMENTATION
 02/08/2000 09:04:03 A.M. RECEIPT# 10181
 PAID RECORDED - OAKLAND COUNTY
 G. WILLIAM CADDELL, CLERK/REGISTER OF DEEDS

RECORDED ON 12-14-99
 OAKLAND COUNTY REGISTER OF DEEDS
 DEED GROUP COMMITTEE

Register of Deeds Stamp & File Number

4. Lot No. _____ Recorded Plat _____ SECTION _____
 5. Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Huston K. Kennedy, in a field survey on October 15, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

- A. Description of original monument and accessories and/or subsequent restoration:
 1817-GLO Wampler, D.S.; Set Post 18" White Oak S58°E 64 Links; 10" Black Oak S08°W 28 Links
- 1976-Hooth, PS# 7966; LCRC L.6770, pgs.855 & 856 - Fnd a 1/2" Iron
 - 1992-Ward, PS #22445; LCRC L.12593, pg.400 - Fnd a 1/2" Iron Rod
 - 1926-Baldwin, PS #1298; unrecorded Survey book #33, pg.11 - Set a Iron Bar
 - 1926-Baldwin, PS #1298; unrecorded Survey book #33, pg. 1 - Object found not stated, no witnesses
 - 1936-Baldwin, PS #1298; unrecorded Survey book #33, pg.42 - Object found not stated, no witnesses
 - 1962-Oakland County Road Commission unrecorded witnesses - Fnd a 1/2" Iron
 - 1992-Ward, PS #22445; unrecorded Survey - Fnd a 1/2" Iron Rod, used same wit as 1992 LCRC
 - M.DOT Right of Way Map, object found not stated, no witnesses

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
 1999-Kennedy Surveying, Inc. - Kennedy, PS #17623 - Fnd a old 5/8" Iron Rod located 3 feet South of the existing centerline of Livingston Road extending to the East & West, which has a gravel surface, also in the existing centerline of Pettibone Lake Road extending to the South, which has a gravel surface.

Witnesses from LCRC #1 & unrecorded witnesses #6 were used to recover and verify the location of the found 5/8" Iron Rod.
 I accepted the found 5/8" Iron Rod as the best evidence of the original corner position.

Measurements on back side of LCRC

- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
 I-9 I replaced the found 5/8" Iron Rod with a 5/8" x24" Iron Rod w/2" diameter brass cap stamped Oak
 Remonumentation, PS #17623
 N53°W 78.07' Set Mag Nail & Remon Washer SW face 38" Oak
 N37°W 50.47' Set Mag Nail & Remon Washer SW face 9" Hickory
 N54°E 63.35' Set Mag Nail & Remon Washer South face 36" Oak
 S38°E 38.93' Set Mag Nail & Remon Washer West face 29" Oak



The selected location is accepted by me and is generally accepted by Professional Surveyors as the best available evidence of the position of the original corner.

Signed by: [Signature] Date 12-16-99
 Surveyor's Michigan License No. 17623

SURVEY &
RECORD REVISION

MAR 21 2000

FIELD MEASUREMENTS BETWEEN

SECTION

I-9 to H-9

GLO = 39.50 chains or 2607.00 Ft.
Unrecorded Survey by Grant Ward, PS #22445 dated 4/30/92 (Sec 22) = 2620.70 Ft.
2620.54 Ft. (GPS-MEA)

I-9 to I-8

GLO = 40 chains or 2640.00 Ft.
Unrecorded Survey by Grant Ward, PS #22445 dated 4/30/92 (Sec 22) = 2652.00 Ft.
M.DOT Right of Way Map = 2648.20 Ft.
2647.82 Ft. (GPS-MEA)

I-9 to I-10

GLO = 40 chains or 2640.00 Ft.
No sidwell or plat distances
2648.84 Ft. (GPS-MEA)

I-9 to J-9

GLO = 39.845 chains or 2629.77 Ft.
No sidwell or plat distances
2627.07 Ft. (GPS-MEA)
2627.40 Ft. (EDM)