UBER 19516 PG 275

MAY 2 4 2000

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in				9.00 MISC F 2.00 RENONL		·		1
Oakland (county)	Located In: Rose Township	Corner Code #	. Q.	3/01/1999()2:59:15 P IRDED - OAI	KLAND CO	JHI Y	or DEG
Public Land Survey	T R			AC1	mpiionee w 345, P.A.	1990		C 0 11
Property Controlling S	T R		OVE	OVED ON: AND COU PEER GI ter of Dee	NTY KEMU ROUP COM	MITTEE	1/01/1/	
4. Lot No, Recor				A D	C D E	FGH	i i J	ł K I
5. Private Claims			-	2 8			1	
I, Joseph C. Kapelczak, in a firequirements of P.A. 74, Michigan were in conformance with regulation instructions of the United States if decree of a Court of Law and/or the conformance with the rules of the Law; established, re-established, below: NOTE: Not more than 4 c	P.A. of 1970, the comons and rules therefore Department of the Interest the corner points me Michigan Board of Lamonumented, re-more corners, all in the	er points mentioned in as required in the cumerior, Bureau of Land Mentioned in lines 3, 4 and Surveyors or by a Inumented, recovered,	lines 1 and 2 above ent manual of surve Management or by and 5 above were i Decree of a Court of found as expresse	9 6 -18- n 7	20	21 - 22	1 2 2	28
recorded on this cert A. Description of original mont				1231	-32	33-34		5
Set post in 1816 G.L.O. Su There are four LCRC's reco Ward, rerod. Witnesses we B. Description of corner evide Recovered a ½" iron at Rat recorded in L.12501 P.328	orded at Oakland Co ere recovered and a nce found and/or m talee Lake and Fish	ethod applied in res	"B" of enclosed toring or reestabl	Oakland (County LC	CRC.		
*N 50°E 42.99' PK with Gra *S 63°E 63.42' nail west sic *S 63°E 63.56' double head *S 31°W 51.79' PK nail with *S 31°W 51.79' nail northw *N 37°W 69.22' nail northe *N 37°W 69.22' double head	de power pole. ded nail with tag nor n Grant Ward Tag n est side 8" Elm. ast side power pole	rtheast side power p orthwest side 8" Eln	ole.			90		2012
C. Description of monument for	or corner and acces	sories established to	perpetuate loca	ting the p	osition of	the cor		7
Set Oakland County Remo	numentation Brass	Cap and 5/8" iron.			ATE OF	MCN/G	C. P. L.	
Set Witnesses: N 73°E 79.15' Mag nail with *S 63°E 63.56' Mag nail with *S 31°W 51.79' Mag nail with *N 37°W 69.22' Mag nail with *Reused Recovered Witne	n OCRT stamped #2 h OCRT stamped # h OCRT stamped #	24598 northeast side 24598 northwest sid	e power pole. le 8" Elm.	THE WAY	SUNVA SUNVA PMOFESSI	•	TO ALL	:
Signed by suppl	Spelejak	<u>/</u>	Date 2/5/	99				
Surveyor's Michigan License	No. <u>24598</u>	F	FORM APPROVED BY MICH	IGAN STATE BO	DARD OF LAND	REVIS	RS, JAN. 1 ED MAY VISED JA	14, 1975