

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY <u>14</u> T. <u>5</u> N. S., R. <u>8</u> E. W.		<u>I-5, I-6, J-7</u>
2. PROPERTY CONTROLLING IN SECTION _____, T. _____, N. S., R. _____ E. W.		_____
3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____, N. S., R. _____ E. W.		_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Donald L. Bissell, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on April, 1977, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on April, 1977, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- | | |
|---|--|
| <p>I-5 Recovered iron, placed plastic cap.</p> <p>N.60°W. 28.62' 12" oak
 N.10°W. 51.43' 24" oak
 N.10°E. 26.42' 24" oak</p> | <p>I-6 Recovered iron along fence line.</p> <p>West 20.20' nail in fence post
 South 9.20' nail in 12" oak
 S.50°E. 16.40' nail in 13" oak
 N.0°40'E.22.00' 3/4" iron bar</p> |
|---|--|

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- J-7** Recovered "T" bar in pavement
- North 45.00' 15" oak (nail)
 S.70°W. 70.22' 16" triple oak
 N.50°E. 63.89' 25" oak
 N60°E. 70.81' 25" oak

SIGNED BY Donald L. Bissell DATE June 13, 1977
 SURVEYOR'S MICHIGAN REGISTRATION NO. 18655 (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
 APPROVED AND SIGNED BY Donald L. Bissell DATE June 13, 1977
CHIEF OF SURVEY PARTY
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. 18655