LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 15 N. S., R. 18 E. W.	I-2;J-2
2. PROPERTY CONTROLLING IN SECTION 2	,T. 15 N. S., R. 18 E. W.	3; 5
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. _____, RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on Aug. 29, 19 78, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. (continued)

5

Set 5/8"X40" re-rod &
Ced.Post w/Loc. Tag

2" W.Pine	Due E	26.54
3" W.Pine	S20°E	18.93
Ctr.N-S rd.	Due W	18'

B. Description of corner evidence found and or method applied in restoring or re-establishing corner:

I-2 Re-established 1/4 Cor. on line between Sec. Cor's to N. & S. & at pro-rated distance to U.S. (G.L.O.). Corner falls at N'ly edge of small island in leather-leaf bog and fits U.S. Swamp ties very well.

J-2 Established ctr. of Sec. 2 at intersection of one-quarter lines.

3 Established 1/8 Corner per Std. B.L.M. instructions, pro-rated to G.L.O. Corner falls in leather leaf bog and fits U.S. Swamp ties.

5 Established 1/16 Cor. per Std. B.L.M instructions; pro-rated to G.L.O.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-2

Set DNR Mon. & Ced. Post

4" Maple	N45°E	18.5
12" R.Oak	S80°E	70.5
7" Maple	S05°W	54.8
4" Maple	S85°W	18.4
N-S Rand	Due E.	15.5

J-2

Set 5/8"X40" Re-rod

27" W.Oak	N65°W	22.69
4" R.Pine	N70°E	36.65
4" W.Pine	S65°W	40.13

Set Ced.Post w/Loc.Tag Due W 16.5

Ctr. N-S dirt rd. Due E. 11'±

3

Set 6' steel fn. post & Ced.Post

3" Maple	N45°W	34.8
8" Tamarack	N15°W	18.2
3" W.Pine	S80°W	57.3
N-S Rand.	Due E.	25.5

SIGNED BY Carl F. Roser 10-2-78 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

STATE OF MICHIGAN
CARL F. ROSER
LAND SURVEYOR
No. 12028
REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

GOLDEN TOWNSHIP
OCEANA COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET