(4)

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 16 N. S., R. 18 E. W.	G-12; H-11; J-13
2. PROPERTY CONTROLLING IN SECTION 34	T. 16 N. S., R. 18 E. W.	15
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S., R. E. W.	

4. LOT NO. _____, RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on Sept. 25, 1978, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. (continued) 15 W 1/16 on S line 34

Set 1 1/4" well point &
Ced.Post w/Loc. Tag
12" W.Ash N15°E 12.8'
11" W.Birch S70°E 23.2'
W 1/16 on N line S-3
T15N-R18W S88°16'E 4.95

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

G-12 Fd. Conc. Mon. & Wit. as noted above (Item C) per notes in old booklet of County Notes dated 1962.

H-11 Fd. Iron bar & accepted same. Above wits (Item C) previously marked, probably by S. Barnett.

J-13 Re-established 1/4 Cor. per RLS, Sam Barnett's survey of Sec's. 34 & 35.

15 Established W 1/8 Corner on So. line S-34, equidistant & on line between Sec. Cor. to W. & 1/4 Cor. to E.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-12 W 1/4 34

Fd. 4" Conc. Mon. w/1/2" iron rod in Ctr.N-S bit. rd.
8" Oak N55°W 39.7'
12" Maple S30°W 65.0'
15" Apple S50°E 56.8'
Set Ced Post w/Loc.Tag beside fd. Conc. Mon.
West 33'

H-11 N 1/4 34

Fd. 3/4"X1 1/2" iron bar Ctr.E-W Dirt rd.
Due N. 5'+
8" W.Oak N25°E 48.70
10" J.Pine N60°E 56.10
5" W.Pine S05°E 23.95
Set Ced.Post w/Loc. Tag
Due N 33'

J-13 S 1/4 35

Set DNR Mon. & Ced.Post
3" Maple N05°W 17.6'
14" R.Oak N60°E 28.25
N 1/4 S-2
T15N-R18W S87°53'E 26.40

SIGNED BY Carl F. Roser 10-2-78 DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

STATE OF MICHIGAN — SEAL — CARL F. ROSER — LAND SURVEYOR No. 12028 — REGISTERED LAND SURVEYOR

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

PENTWATER TOWNSHIP
OCEANA COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET