LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. ___ N. S., R. ___ E. W.	
2. PROPERTY CONTROLLING IN SECTION	T. 23 N. S., R. 1 E.	C-12;B-13;A-13
3. MISCELLANEOUS PROPERTY IN SECTION	T. ___ N. S., R. ___ E. W.	
4. LOT NO. ___ , RECORDED PLAT ___		
5. PRIVATE CLAIMS ___		

REGISTER OF DEEDS STAMP AND FILING NUMBER ___

I, KENNETH J. OSTLING, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on OCTOBER 26, 1982, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on ___, 19___, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

C. CONTINUED:

A-13

LEFT 1 1/4" PIPE WITH CONCRETE BASE IN PLACE
12" RED OAK N37°E 18.8'
7" BLACK OAK N30°W 28.4'

FENCE CORNER - S10°E 2.5'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

C-12 SET CORNER BY PROPORTIONATE MEASUREMENT BETWEEN SECTION CORNERS. UNABLE TO IDENTIFY U.S. EVIDENCE OR A PREVIOUS CORNER.
B-13 SET CORNER BY PROPORTIONATE MEASUREMENT BETWEEN SECTION CORNERS. FALLS IN E-W FENCE LINE.
A-13 FOUND MONUMENT BY M. SCHAAF IN PLACE, IN LINE WITH FIRELINES N & W AND FENCE S.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-12
SET DNR MONUMENT
7" RED OAK N24°W 17.2'
5" RED OAK S59°W 7.1'

B-13
SET DNR MONUMENT
8" RED OAK N47°W 23.8'
8" RED OAK N44°E 19.1'

STATE OF MICHIGAN KENNETH J. OSTLING LAND SURVEYOR No. SURVEYOR

SIGNED BY Kenneth J. Ostling DATE 1/18/83
KENNETH J. OSTLING

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068 (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY ___ DATE ___
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY ___ DATE ___
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. ___ OGEMAW COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET