LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:			
1. PUBLIC LAND SURVEY	T. 23 N. R. 1	H-5; H-6	
		5	
3. MISCELLANEOUS PROPERTY IN SECTION	,T N. R W	;;	
4. LOT NO, RE	CORDED PLAT		
5. PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND FILING NUMBER
the corner points mentioned in re-established, monumented, rand rules therefore as required Bureau of Land Management of and 5 above were, in a field sur	lines 1 and 2 above were, in e-monumented, recovered or I in the current manual of sur or by a decree of a court of la rvey on	a field survey onAUGUST_restored as expressed below an evey instructions of the United w. Furthermore, that the corn_, 19, found, recovered, re	of P.A. 74, Michigan P.A. of 1970, 27, 1981., established, and in conformance with regulations States Department of the Interior, er points mentioned in lines 3, 4 stored, established or re-established stration for Land Surveyors or, by a
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	KANKKANAKKANKKANKK	KANDANGAKKAKAKAKA	
H-5 FT 1/2" ROD IN PLACE 6" J. PINE N19°E 2" J. PINE STP S3°W			
4" W. PINE N62°W	11.4'		
6" R. PINE DU€ SOUTH	36.31		
×old NBTS - RICHARDS			
B. Description of corner evide	ence found and/or method ap	plied in restoring or re-establish	ing corner: DSON, R.L.S. PROBABLY USED
B. Description of corner evidence 5 FOUND 1/2" BAR AS R SUBDIVISION OF SECT	ence found and/or method ap RESTORED IN A PREVIOU FION 10.	S SURVEY BY J. RICHARD	
B. Description of corner evide FOUND 1/2" BAR AS R SUBDIVISION OF SECT SET CORNER PER STAN	ence found and/or method ap RESTORED IN A PREVIOU FION 10. NDARD SURVEY PROCEDUR	S SURVEY BY J. RICHARD	SON, R.L.S. PROBABLY USED
B. Description of corner evide FOUND 1/2" BAR AS R SUBDIVISION OF SECT SET CORNER PER STAN	ence found and/or method ap RESTORED IN A PREVIOU FION 10. NDARD SURVEY PROCEDUR	S SURVEY BY J. RICHARD	SON, R.L.S. PROBABLY USED
B. Description of corner evide FOUND 1/2" BAR AS R SUBDIVISION OF SECT SET CORNER PER STAN SET BY STANDARD SUR	ence found and/or method ap RESTORED IN A PREVIOU FION 10. WDARD SURVEY PROCEDUR RVEY PROCEDURE FOR TH	S SURVEY BY J. RICHARD E, AT CALCULATED INTER E SUBDIVISION OF SECTI	SON, R.L.S. PROBABLY USED SECTION OF TRUE 1/4 LINES.
B. Description of corner evide FOUND 1/2" BAR AS R SUBDIVISION OF SECT SET CORNER PER STAN SET BY STANDARD SUR C. Description of monument	ence found and/or method ap RESTORED IN A PREVIOU FION 10. WDARD SURVEY PROCEDUR RVEY PROCEDURE FOR TH	S SURVEY BY J. RICHARD E, AT CALCULATED INTER E SUBDIVISION OF SECTI	SON, R.L.S. PROBABLY USED SECTION OF TRUE 1/4 LINES ONS.
B. Description of corner evides FOUND 1/2" BAR AS R SUBDIVISION OF SECT SET CORNER PER STAN SET BY STANDARD SUR C. Description of monument H-6 SET 5/8 ROD WITH C	ence found and/or method ap RESTORED IN A PREVIOU FION 10. DARD SURVEY PROCEDUR RVEY PROCEDURE FOR TH for corner and accessories esta	S SURVEY BY J. RICHARD E, AT CALCULATED INTER BE SUBDIVISION OF SECTI Ablished to perpetuate locating the SET 5/8 ROD WITH	SON, R.L.S. PROBABLY USED SECTION OF TRUE 1/4 LINES ONS. The position of the corner:
B. Description of corner evidence FOUND 1/2" BAR AS RESUBDIVISION OF SECT SET CORNER PER STANGED SUFF C. Description of monument of the SET 5/8 ROD WITH CORNER PINE N37°V	ence found and/or method appression in A PREVIOUTION 10. NDARD SURVEY PROCEDUR RVEY PROCEDURE FOR THe for corner and accessories esta	S SURVEY BY J. RICHARD E, AT CALCULATED INTER BE SUBDIVISION OF SECTI Ablished to perpetuate locating the section of s	SON, R.L.S. PROBABLY USED SECTION OF TRUE 1/4 LINES ONS. The position of the corner: I CAP 161°E 21.0°
B. Description of corner evide FOUND 1/2" BAR AS R SUBDIVISION OF SECT SET CORNER PER STAN SET BY STANDARD SUR C. Description of monument H=6 SET 5/8 ROD WITH C	ence found and/or method appression in A PREVIOUTION 10. NDARD SURVEY PROCEDUR RVEY PROCEDURE FOR THe for corner and accessories esta	S SURVEY BY J. RICHARD E, AT CALCULATED INTER BE SUBDIVISION OF SECTI Ablished to perpetuate locating the SET 5/8 ROD WITH	SON, R.L.S. PROBABLY USED SECTION OF TRUE 1/4 LINES ONS. The position of the corner: I CAP 161°E 21.0°
B. Description of corner evidence of FOUND 1/2" BAR AS RESUBDIVISION OF SECTOR SET CORNER PER STANSET BY STANDARD SURFACE OF THE SET 5/8 ROD WITH CORNER PINE N37°W	ence found and/or method appression in A PREVIOUTION 10. NDARD SURVEY PROCEDUR RVEY PROCEDURE FOR THe for corner and accessories esta	S SURVEY BY J. RICHARD E, AT CALCULATED INTER BE SUBDIVISION OF SECTI Ablished to perpetuate locating the section of s	SON, R.L.S. PROBABLY USED SECTION OF TRUE 1/4 LINES ONS. The position of the corner: I CAP 161°E 21.0°
B. Description of corner evides 5 FOUND 1/2" BAR AS R SUBDIVISION OF SECT 6 SET CORNER PER STAN SET BY STANDARD SUR C. Description of monument H=6 SET 5/8 ROD WITH C 7" J. PINE N37°V 12" J. PINE S52°V	ence found and/or method appression 10. ADARD SURVEY PROCEDURE RVEY PROCEDURE FOR THe for corner and accessories esta CAP 7.6† 4.2†	S SURVEY BY J. RICHARD E, AT CALCULATED INTER BE SUBDIVISION OF SECTI Ablished to perpetuate locating the section of s	SON, R.L.S. PROBABLY USED SECTION OF TRUE 1/4 LINES ONS. The position of the corner: I CAP 161°E 21.0°
B. Description of corner evidence FOUND 1/2" BAR AS RESUBDIVISION OF SECT SET CORNER PER STANSET BY STANDARD SUR C. Description of monument H-6 SET 5/8 ROD WITH CORNER PINE N37°V 12" J. PINE N37°V 12" J. PINE S52°V	ence found and/or method appression 10. ADARD SURVEY PROCEDURE RVEY PROCEDURE FOR THe for corner and accessories esta CAP 7.6† 4.2†	S SURVEY BY J. RICHARD E, AT CALCULATED INTER BE SUBDIVISION OF SECTI Ablished to perpetuate locating the section of s	SON, R.L.S. PROBABLY USED SECTION OF TRUE 1/4 LINES ONS. The position of the corner: I CAP 161°E 21.0°
B. Description of corner evides 5 FOUND 1/2" BAR AS R SUBDIVISION OF SECT 6 SET CORNER PER STAN SET BY STANDARD SUR C. Description of monument H=6 SET 5/8 ROD WITH C 7" J. PINE N37°V	ence found and/or method appression 10. ADARD SURVEY PROCEDURE RVEY PROCEDURE FOR THe for corner and accessories esta CAP 7.6† 4.2†	S SURVEY BY J. RICHARD E, AT CALCULATED INTER BE SUBDIVISION OF SECTI Ablished to perpetuate locating the section of s	SON, R.L.S. PROBABLY USED SECTION OF TRUE 1/4 LINES ONS. The position of the corner: I CAP 161°E 21.0°
B. Description of corner evides 5 FOUND 1/2" BAR AS R SUBDIVISION OF SECT 6 SET CORNER PER STAN SET BY STANDARD SUR C. Description of monument H=6 SET 5/8 ROD WITH C 7" J. PINE N37°V 12" J. PINE S52°V	ence found and/or method appression 10. ADARD SURVEY PROCEDURE RVEY PROCEDURE FOR THe for corner and accessories esta CAP N 7.6† N 4.2†	S SURVEY BY J. RICHARD E, AT CALCULATED INTER BE SUBDIVISION OF SECTI Ablished to perpetuate locating the section of s	SON, R.L.S. PROBABLY USED SECTION OF TRUE 1/4 LINES ONS. The position of the corner: I CAP 161°E 21.0°
B. Description of corner evidence of FOUND 1/2" BAR AS RESUBDIVISION OF SECTOR SET CORNER PER STANSET BY STANDARD SUBSET 5/8 ROD WITH CORNER PINE N37°W 12" J. PINE N37°W 12" J. PINE S52°W SIGNED BY MALL MALL MALL MALL MALL MALL MALL MAL	EEGISTRATION NO. 16	S SURVEY BY J. RICHARD E, AT CALCULATED INTER BE SUBDIVISION OF SECTI Ablished to perpetuate locating the section of s	SON, R.L.S. PROBABLY USED SECTION OF TRUE 1/4 LINES ONS. The position of the corner: I CAP 161°E 21.0°
B. Description of corner evides FOUND 1/2" BAR AS R SUBDIVISION OF SECT SET CORNER PER STAN SET BY STANDARD SUR C. Description of monument H-6 SET 5/8 ROD WITH C 7" J. PINE N37°V 12" J. PINE S52°V SURVEYOR'S MICHIGAN R FOR STATE AND UNITED	ERSTORED IN A PREVIOUR RESTORED IN A PREVIOUR TION 10. **DARD SURVEY PROCEDURE FOR THE FOR CORNER and accessories established by the second s	S SURVEY BY J. RICHARD E, AT CALCULATED INTER BE SUBDIVISION OF SECTI Abhished to perpetuate locating the second secon	SSON, R.L.S. PROBABLY USED SECTION OF TRUE 1/4 LINES SONS. The position of the corner: H CAP H61°E 21.0' H88°W 10.5' KENNETH J. OSTLING LAND NO. 10068 LAND NO. 10068
B. Description of corner evides FOUND 1/2" BAR AS R SUBDIVISION OF SECT SET CORNER PER STAN SET BY STANDARD SUR C. Description of monument H-6 SET 5/8 ROD WITH C 7" J. PINE N37" 12" J. PINE S52" SIGNED BY SURVEYOR'S MICHIGAN R FOR STATE AND UNITED SIGNED BY	RESTORED IN A PREVIOUR RESTORED IN A PREVIOUR TION 10. ADARD SURVEY PROCEDURE FOR THE FOR CORNER and accessories established by the process of the process	E, AT CALCULATED INTER BE SUBDIVISION OF SECTION Abhished to perpetuate locating the second	SON, R.L.S. PROBABLY USED SECTION OF TRUE 1/4 LINES ONS. The position of the corner: I CAP 161°E 21.0°

_ MAY PLACE SKETCH ON BACK OF ATTACHED SHEET.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971 REVISED MAY 14, 1975