

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--: <u>Ogemaw</u>	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>23</u> N. <input checked="" type="radio"/> R. <u>2</u> E. <input checked="" type="radio"/>	<u>G-11; G-12; G-13</u>
2. PROPERTY CONTROLLING IN SECTION _____	T. _____ N. <input type="radio"/> S. <input type="radio"/> R. _____ E. <input type="radio"/> W. <input type="radio"/>	_____
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. <input type="radio"/> S. <input type="radio"/> R. _____ E. <input type="radio"/> W. <input type="radio"/>	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on June 6, 1978, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:


A. Description of original monument and accessories and/or subsequent restoration:

- B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:
- G-11 Found 3/4" pipe as established by unknown. Fits good corners east and west and swamp edge and stream east; 9' south of E-W fence.
 - G-12 Set corner by proportionate measurement, midpoint on line, between section corners. No previous corner.
 - G-13 Set corner by proportionate measurement between 1/4 corners, 1/2 mile east and west. No evidence of a previous corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-11	G-12	G-13
Set DNR mon. in place of 3/4" pipe & red-top post	Set DNR mon. & red-top post	Set DNR mon. & red-top post
10" Oak N30°W 14.1	6" Oak N45°W 12.45	12" Oak N22°W 9.65
6" Oak N75°W 20.9	8" Oak S74°W 21.05	8" Oak N80°W 36.7

SIGNED BY *Kenneth J. Ostling* DATE 8/27/78
 SURVEYOR'S MICHIGAN REGISTRATION NO. 10068



FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY
 APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ OGEMAW COUNTY

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET