LAND CORNER RECORDATION CERTIFICATE

14

12

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

1. PUBLIC LAND SURVEY	T N E. W.		
2. PROPERTY CONTROLL- 22 ING IN SECTION 22	2 ,T. 23 N. R. 2 E.	14; 12	
3. MISCELLANEOUS PROPERTY IN SECTION			
4. LOT NO , RECO	ORDED PLAT		
5. PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND
re-established, monumented, re- and rules therefore as required i Bureau of Land Management or and 5 above were, in a field surve	monumented, recovered or real the current manual of survively a decree of a court of lawey on	estored as expressed below and ey instructions of the United 3 v. Furthermore, that the corner, 19, found, recovered, res Michigan State Board of Register	of P.A. 74, Michigan P.A. of 1970, 18, 1983, established, d in conformance with regulations States Department of the Interior, er points mentioned in lines 3, 4 stored, established or re-established tration for Land Surveyors or, by a
B. Description of corner evidence - SET CORNER BY STA	e found and/or <mark>method app</mark> NDARD SURVEY PRO	lied in restoring or re-establishi CEDURE FOR THE SUBI	ng corner: DIVISION OF SECTIONS.
			DIVISION OF SECTIONS.
			DIVISION OF SECTIONS.
	NDARD SURVEY PROC	CEDURE FOR THE SUBI	DIVISION OF SECTIONS.
- SET CORNER BY STA C. Description of monument for 14	NDARD SURVEY PROC	CEDURE FOR THE SUBI	DIVISION OF SECTIONS.
- SET CORNER BY STA C. Description of monument for	NDARD SURVEY PROC	DEDURE FOR THE SUBI	e position of the corner: CAP E N63°W 27.3' E N47°W 33.6' POST W/LOCATION
- SET CORNER BY STA C. Description of monument for 14 ROD W/RLS CAP CEDAR N40°W	NDARD SURVEY PROC	Dished to perpetuate locating the substantial state of the substantial	e position of the corner: CAP E N63°W 27.3' E N47°W 33.6' POST W/LOCATION
- SET CORNER BY STA C. Description of monument for 14 ROD W/RLS CAP CEDAR N40°W CEDAR N74°E	corner and accessories estab	cedure for the substance to perpetuate locating the 12 5/8" ROD W/RLS 16" WHITE PINE 6" WHITE PINE SET 4" CEDAR FOR TAG BY CORN	position of the corner: CAP N63°W 27.3' N47°W 33.6' POST W/LOCATION NER KENNETH
- SET CORNER BY STA C. Description of monument for 14 ROD W/RLS CAP CEDAR N40°W CEDAR N74°E SIGNED BY Jennet	corner and accessories estab	DATE	position of the corner: CAP N63°W 27.3' N47°W 33.6' POST W/LOCATION NER KENNETH
C. Description of monument for 14 ROD W/RLS CAP CEDAR N40°W CEDAR N74°E SIGNED BY Jewall SURVEYOR'S MICHIGAN REG	corner and accessories estab	DATE	position of the corner: CAP N63°W 27.3' N47°W 33.6' POST W/LOCATION NER KENNETH
C. Description of monument for 14 ROD W/RLS CAP CEDAR N40°W CEDAR N74°E SIGNED BY Jewal SURVEYOR'S MICHIGAN REG	corner and accessories estab 28.2' 41.7' 4	DATE	position of the corner: CAP N63°W 27.3' N47°W 33.6' POST W/LOCATION NER KENNETH
C. Description of monument for 14 ROD W/RLS CAP CEDAR N40°W CEDAR N74°E SIGNED BY WICHIGAN REG FOR STATE AND UNITED ST SIGNED BY	corner and accessories estab 28.2' 41.7' 4	DATE	e position of the corner: CAP N63°W N47°W S3.6 POST W/LOCATION NER KENNETH OF NO. NO. AND NO.
C. Description of monument for 14 PROD W/RLS CAP CEDAR N40°W CEDAR N74°E SIGNED BY Jewal SURVEYOR'S MICHIGAN REG	corner and accessories estab 28.2' 41.7' 4	DATE	e position of the corner: CAP N63°W N47°W S3.6 POST W/LOCATION NER KENNETH OF NO. NO. AND NO.
C. Description of monument for 14 ROD W/RLS CAP CEDAR N40°W CEDAR N74°E SIGNED BY Jewal SURVEYOR'S MICHIGAN REG FOR STATE AND UNITED ST SIGNED BY	corner and accessories estab 28.2† 41.7† 41.7† ATES AGENCIES: CHIEF OF SURVEY PARTY MICHIGAN REGISTERED LA	DATE DATE DATE DATE	POST W/LOCATION KENNETH OSTLING AND SURVEYOR NO.68