

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>24</u> N. <u>1</u> E. <u>1</u>	<u>E-2; C-3</u>
2. PROPERTY CONTROLLING IN SECTION <u>5</u>	T. <u>24</u> N. <u>1</u> E. <u>1</u>	<u>14</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ N. _____ E. _____	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on August 21, 1980, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- E-2 Found 1 1/2" pipe 1' below surface of old grade thru swamp, as established in old surveys by Marcus Schaaf.
- C-3 Found 1/2" iron bar at corner as established in 1965 survey by G. D. Henning. Falls at road intersection.
- 14 Set corner by standard survey procedure for the subdivision of sections. Found 1/2" bar and 1 1/2" pipe about 2' west of proper location and removed to avoid confusion on corner location.


C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-2	C-3	14
Left 1 1/2" pipe in place	Left 1/2" bar in place	Set 5/8" rod w/RLS cap
5" Jack Pine N29°W 3.6'	7" Jack Pine N39°E 49.9'	4" Red Pine N88°W 33.7'
5" Jack Pine S36°W 6.0'	8" Jack Pine N45°W 60.1'	4" Jack Pine S57°W 36.4'

SIGNED BY Kenneth Ostling

DATE 3-18-84

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068



FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

OGEMAW COUNTY