LAND CORNER RECORDATION CERTIFICATE ,

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

		I .		
1. PUBLIC LAND SURVEY	T S., R	E. W.		
2. PROPERTY CONTROLL- ING IN SECTION-14	T. 24 N. R. 2	E.	5′	
3. MISCELLANEOUS PROPERTY IN SECTION 14		I .	I-5,3;	
4. LOT NO , REC	CORDED PLAT			
5. PRIVATE CLAIMS	•			REGISTER OF DEEDS STAMP
I. Carl R. Johnson		,	or at a large transfer	nents of P.A. 74, Michigan P.A. of
re-established, monumented, re and rules therefore as required Bureau of Land Management of and 5 above were, in a field surv	e-monumented, recovered in the current manual or in the current manual or by a decree of a court vey on	l or rest of survey of law, 1	ored as expressed belo- instructions of the Un Furthermore, that the 9, found, recovere	nry 15, 19.85, estable wand in conformance with regulated States Department of the Ircorner points mentioned in lines and, restored, established or re-estable Registration for Land Surveyors or
A. Description of original mon	aiment and accessories a	nd/or su	bsequent restoration:	
	6 1 1/ 41.	1	3 to	Llishing appropri
B. Description of corner evider	nce found and/or metho	d applie	d in restoring or re-esta	blishing corner:
5 Set by standard sur	vey procedure for	subd:	ivision of section	ons
	vey procedure for	subd:	ivision of section	ons
5 Set by standard sur	vey procedure for	subd:	ivision of section	ons
5 Set by standard sur	vey procedure for	subd:	ivision of section	ons
5 Set by standard sur	vey procedure for	subd:	ivision of section	ons
5 Set by standard sur	vey procedure for	subd:	ivision of section	ons
5 Set by standard sur	vey procedure for vey procedure for	r subdi	ivision of section of section in the section of section of section of sections.	ons ons
5 Set by standard sur, 3 Set by standard sur C. Description of monument for	vey procedure for vey procedure for or corner and accessories	r subdi r subdi	ivision of section of	ons ons ing the position of the corner:
5 Set by standard sur, 3 Set by standard sur C. Description of monument for	vey procedure for vey procedure for or corner and accessories	r subd r subd s establis	ivision of section ivision of section ivision of section hed to perpetuate location in the section in the secti	ons ons ing the position of the corner:
5 Set by standard sur ,3 Set by standard sur C. Description of monument for Set 5/8" bar w/cap	vey procedure for vey procedure for or corner and accessories and cedar post	r subd r subd s establis	ivision of section ivision of section ivision of section hed to perpetuate location in the section in the secti	ons ons ing the position of the corner:
5 Set by standard sur, 3 Set by standard sur C. Description of monument for	vey procedure for vey procedure for or corner and accessories and cedar post	r subd r subd s establis	ivision of section ivision of section ivision of section ivision of section ivision in the section is a section in the section in the section is a section in the section i	ons ons ing the position of the corner: 3 p 6°W 36.1' 0°W 63.1'
5 Set by standard sur ,3 Set by standard sur C. Description of monument for Set 5/8" bar w/cap	vey procedure for vey procedure for or corner and accessories and cedar post	r subd r subd s establis	ivision of section ivision of section ivision of section hed to perpetuate location in the section in the secti	ons ons ing the position of the corner: 3 p 6°W 36.1' 0°W 63.1'
5 Set by standard sur ,3 Set by standard sur C. Description of monument for Set 5/8" bar w/cap	vey procedure for vey procedure for or corner and accessories and cedar post	r subd r subd s establis	ivision of section ivision of section ivision of section ivision of section ivision in the section is a section in the section in the section is a section in the section i	ons ons ing the position of the corner: 3 p 6°W 36.1' 0°W 63.1'
5 Set by standard sur ,3 Set by standard sur C. Description of monument for Set 5/8" bar w/cap	vey procedure for vey procedure for or corner and accessories and cedar post	r subd r subd s establis	ivision of section ivision of section ivision of section ivision of section ivision in the section is a section in the section in the section is a section in the section i	ons ons ing the position of the corner: 3 p 6°W 36.1' 0°W 63.1'
5 Set by standard sur ,3 Set by standard sur C. Description of monument for Set 5/8" bar w/cap	vey procedure for vey procedure for or corner and accessories and cedar post	r subd r subd s establis	ivision of section ivision of section ivision of section ivision of section ivision in the section is a section in the section in the section is a section in the section i	ons ons ing the position of the corner: 3 p 6°W 36.1' 0°W 63.1'
5 Set by standard sur, 3 Set by standard sur C. Description of monument for 5 Set 5/8" bar w/cap 6" R. Oak N30°W 4" Cherry S34°W	vey procedure for vey procedure for or corner and accessories and cedar post 21.6' 16.0'	r subd r subd s establis	ivision of section ivision of section I-5, et 5/8" bar w/car 10" J. Pine N4 10" J. Pine S6 Cedar Post East	ing the position of the corner: 3 9 6°W 36.1' 0°W 63.1' 11.0' CARL R. JOHNSON LAND
5 Set by standard sur ,3 Set by standard sur C. Description of monument for Set 5/8" bar w/cap	vey procedure for vey procedure for or corner and accessories and cedar post 21.6' 16.0'	r subd r subd s establis	ivision of section ivision of section ivision of section ivision of section ivision in the section is a section in the section in the section is a section in the section i	ing the position of the corner: 3 P 6°W 36.1' 0°W 63.1' 11.0' CARL R. JOHNSON
5 Set by standard sur, 3 Set by standard sur C. Description of monument for 5 Set 5/8" bar w/cap 6" R. Oak N30°W 4" Cherry S34°W SIGNED BY All	vey procedure for vey procedure for or corner and accessories and cedar post 21.6' 16.0'	r subd	hed to perpetuate location of section of section in the section of section in the section in the section is a section in the s	ing the position of the corner: 3 9 6°W 36.1' 0°W 63.1' 11.0' CARL R. JOHNSON LAND
5 Set by standard sur, 3 Set by standard sur C. Description of monument for 5 Set 5/8" bar w/cap 6" R. Oak N30°W 4" Cherry S34°W	or corner and accessories and cedar post 21.6' 16.0'	r subd	hed to perpetuate location of section of section in the section of section in the section in the section is a section in the s	ing the position of the corner: 3 9 6°W 36.1' 0°W 63.1' 11.0' CARL R. JOHNSON LAND
Set by standard sur, 3 Set by standard sur C. Description of monument for 5 Set 5/8" bar w/cap 6" R. Oak N30°W 4" Cherry S34°W SIGNED BY SURVEYOR'S MICHICAN REFOR STATE AND UNITED S	vey procedure for vey procedure for or corner and accessories and cedar post 21.6' 16.0'	establis	hed to perpetuate location of section of section in the section of section in the section in the section is a section in the s	ing the position of the corner: 3 9 6°W 36.1' 0°W 63.1' 11.0' CARL R. JOHNSON LAND LAND SURVEYOR NO. 30083 JOHNSON LAND SURVEYOR NO. 30083
5 Set by standard sur, 3 Set by standard sur C. Description of monument for 5 Set 5/8" bar w/cap 6" R. Oak N30°W 4" Cherry S34°W SIGNED BY	or corner and accessories and cedar post 21.6' 16.0'	s establis	hed to perpetuate location I-5, et 5/8" bar w/ca 10" J. Pine N4 10" J. Pine S6 Cedar Post East DATE	ing the position of the corner: 3 p 6°W 36.1' 0°W 63.1' 11.0' CARL R. JOHNSON LAND LAND NO. 30083
5 Set by standard sur, 3 Set by standard sur C. Description of monument for 5 Set 5/8" bar w/cap 6" R. Oak N30°W 4" Cherry S34°W SIGNED BY	or corner and accessories and cedar post 21.6' 16.0'	s establis	hed to perpetuate location I-5, et 5/8" bar w/ca 10" J. Pine N4 10" J. Pine S6 Cedar Post East DATE	ing the position of the corner: 3 9 6°W 36.1' 0°W 63.1' 11.0' CARL R. JOHNSON LAND LAND SURVEYOR NO. 30083 JOHNSON LAND SURVEYOR NO. 30083
5 Set by standard sur, 3 Set by standard sur C. Description of monument for 5 Set 5/8" bar w/cap 6" R. Oak N30°W 4" Cherry S34°W SIGNED BY	or corner and accessories and cedar post 21.6' 16.0'	s establis	hed to perpetuate location I-5, et 5/8" bar w/ca 10" J. Pine N4 10" J. Pine S6 Cedar Post East DATE	ing the position of the corner: 3 p 6°W 36.1' 0°W 63.1' 11.0' CARL R. JOHNSON LAND LAND SURVEYOR NO. 30083
5 Set by standard sur, 3 Set by standard sur C. Description of monument for 5 Set 5/8" bar w/cap 6" R. Oak N30°W 4" Cherry S34°W SIGNED BY	or corner and accessories and cedar post 21.6' 16.0' EGISTRATION NO3 STATES AGENCIES: CHIEF OF BURYEY PARTY NICHIGAN REGIST	establis September 1	hed to perpetuate location I-5, et 5/8" bar w/ca 10" J. Pine N4 10" J. Pine S6 Cedar Post East DATE DATE DATE	ing the position of the corner: 3 6°W 36.1' 0°W 63.1' 11.0' CARL R. JOHNSON LAND SURVEYOR No. 30083 SPEAL) TE (SEAL)