LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 24 N. S., R. 2 E. W.	J-6;
2. PROPERTY CONTROLLING IN SECTION 14	,T. 24 N. S., R. 2 E. W.	8; 10; 3
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. _____, RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl R. Johnson, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on January 15, 1985, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. Continued:

10

Set 5/8" bar w/LLS cap & cedar post

8" Jack Pine	S25°E	19.5'
9" Jack Pine	N19°E	26.2'

3

Set 5/8" bar w/LLS cap & cedar post

8" Jack Pine	N24°E	16.3'
6" Jack Pine	S26°E	24.2'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

J-6 - Set by standard survey procedure for subdivision of sections.

8 - Set by standard survey procedure for subdivision of sections.

10 - Set by standard survey procedure for subdivision of sections.

3 - Set by standard survey procedure for subdivision of sections.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J-6

Set 5/8" bar w/LLS cap & cedar post

6" Jack Pine	S35°W	8.0'
6" Jack Pine	N69°W	13.0'

8

Set 5/8" bar w/LLS cap & cedar post

10" Jack Pine	S34°E	60.0'
8" Jack Pine	N11°E	50.0'

SIGNED BY Carl R. Johnson DATE 4/3/85

STATE OF MICHIGAN CARL R. JOHNSON LAND SURVEYOR No. 30083 LICENSED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 30083

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ OGEMAW COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET