LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 24 N., R. 2 E.	I-2; H-1; I-1;
2. PROPERTY CONTROLLING IN SECTION 3	T. 24 N., R. 2 E.	2
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S., R. E. W.	
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, KENNETH J. OSTLING, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on MARCH 28, 19 84, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on , 19 , found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. CONTINUED:

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

2

SET 5/8" ROD W/RLS CAP
10" RED PINE S35°E 59.3'
14" RED PINE S55°W 33.2'

I-1

FOUND 3/4" I.D. PIPE IN PLACE
12" RED OAK S50°E 69.2'
NAIL IN SIDE
OF POWER POLE S33°W 22.2'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

I-2 - FOUND T-IRON IN PLACE AS ESTABLISHED IN 1968 SURVEY AND USE IN SUBSEQUENT SURVEY IN SECTION 2.
H-1 - FOUND CORNER AS RESTORED IN 1968 SURVEY BY CONSUMER POWER COMPANY.

2 - SET CORNER BY STANDARD SURVEY PROCEDURE FOR THE SUBDIVISION OF SECTIONS.

I-1 - FOUND 3/4" PIPE AS ESTABLISHED IN PREVIOUS SURVEY, AND USED IN SECTION 2 SURVEY BY R. HIGGINS, R.L.S.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner.

I-2

CONS. POW. T-IRON IN PLACE
*10" W. OAK N23°W 41.0'
*12" R. OAK S63°W 23.8'
*12" R. OAK S38°E 36.9'
*14" R. OAK N79°E 24.95'

H-1

CONS. POWER T-IRON IN PLACE
7" RED OAK S33°W 25.6'
5" RED MAPLE S32°E 38.8'

*WITNESSES ARE SPIKES IN SIDE OF TREE

STATE OF MICHIGAN KENNETH J. OSTLING No. 10068 REGISTERED LAND SURVEYOR

SIGNED BY Kenneth J Ostling DATE 4-28-84

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ OGEMAW COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET