LAND CORNER RECORDATION CERTIFICATE

the second secon

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN -:	CORNER CODE NUMB	ER
1. PUBLIC LAND SURVEY	T. 24_ N. R. 2_ E.	B-2;	
2. PROPERTY CONTROLL- ING IN SECTION	6 ,T. 24 N., R. 2 E.	1;-8	
	,T		
4. LOT NO	CORDED PLAT		
5. PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND FILING NUMBER
the corner points mentioned in re-established, monumented, of and rules therefore as required Bureau of Land Management of and 5 above were, in a field sur as expressed below and in con- Decree of a Court of law: C. CONTINUED:	hues I and 2 above were, in a e monumented, recovered or re I in the current manual of surve or by a decree of a court of law rvey on	field survey on JANU stored as expressed belo ey instructions of the Un Furthermore, that the 19, found, recovere Michigan State Board of	nents of P.A. 74, Michigan P.A. of 197 ARY 31 , 1984 , established we and in conformance with regulation of the luteric corner points mentioned in lines 3, and, restored, established or re-established Registration for Land Surveyors or, by
**************************************	8		
	SET 5/8" ROD W 36" RED PINE 28" RED PINE	/RLS CAP N80°W 50.0' S50°E 56.2'	<i>,</i>
SET BY STANDARD <u>2 </u> - SET BY STANDARD	SET 5" CEDAR P BY CORNER Price found and, or method appl O SURVEY PROCEDURE O PROCEDURE, AT THE	ed in restoring or re-esta FOR THE SUBDIV	
SET BY STANDARD 2 SET BY STANDARD 1/4 LINES.	BY CORNER ence found and, or method appl SURVEY PROCEDURE	ed in restoring or re-esta FOR THE SUBDIV CALCULATED IN	ISION OF SECTIONS. TERSECTION OF THE TRUE
SET BY STANDARD 2 - SET BY STANDARD 1/4 LINES. SET BY STANDARD	BY CORNER Price found and, or method appl D SURVEY PROCEDURE D PROCEDURE, AT THE	ed in restoring or re-esta FOR THE SUBDIV CALCULATED IN FOR SUBDIVISIO	ISION OF SECTIONS. TERSECTION OF THE TRUE N OF SECTIONS.
SET BY STANDARD 2 - SET BY STANDARD 1/4 LINES. - SET BY STANDARD C. Description of monument for the second continuous process.	BY CORNER Since found and, or method appl SURVEY PROCEDURE PROCEDURE, AT THE SURVEY PROCEDURE for corner and accessories estable 18.6	ed in restoring or re-esta FOR THE SUBDIV CALCULATED IN FOR SUBDIVISIO	ISION OF SECTIONS. TERSECTION OF THE TRUE N OF SECTIONS. ing the position of the corner: 2 W/RLS CAP 578°E 29.01
- SET BY STANDARD 2 - SET BY STANDARD 1/4 LINES. - SET BY STANDARD C. Description of monument b 1 1 P.K. NAIL 1 RED PINE N41°E	BY CORNER Pince found and, or method appl D SURVEY PROCEDURE D PROCEDURE, AT THE D SURVEY PROCEDURE for corner and accessories estable 18.6' 26.38'	ed in restoring or re-esta FOR THE SUBDIV CALCULATED IN FOR SUBDIVISION ished to perpetuate location B- SET 5/8" ROD 1 15" RED OAK 12" RED OAK	ISION OF SECTIONS. TERSECTION OF THE TRUE N OF SECTIONS. ing the position of the corner: 2 W/RLS CAP 578°E 29.01
- SET BY STANDARD 2 - SET BY STANDARD 1/4 LINES. - SET BY STANDARD C. Description of monument by the second of	BY CORNER Pince found and, or method appl D SURVEY PROCEDURE D PROCEDURE, AT THE D SURVEY PROCEDURE for corner and accessories estable 18.6' 26.38'	ed in restoring or re-esta FOR THE SUBDIV CALCULATED IN FOR SUBDIVISION ished to perpetuate location B- SET 5/8" ROD 1 15" RED OAK 12" RED OAK SET 6" CEDAR	ISION OF SECTIONS. TERSECTION OF THE TRUE N OF SECTIONS. ing the position of the corner: 2 W/RLS CAP S78°E 29.0' N16°E 45.6'
- SET BY STANDARD 2 - SET BY STANDARD 1/4 LINES SET BY STANDARD C. Description of monument for 1 T P.K. NAIL RED PINE N41°E JACK PINE N58°W F. MARKER ON SIDE OF STATE AND UNITED STATE	BY CORNER The found and or method apple SURVEY PROCEDURE DEPROCEDURE, AT THE SURVEY PROCEDURE For corner and accessories estable 18.6' 26.38' DE GEGISTRATION NO. 1006 STATES AGENCIES:	ed in restoring or re-esta FOR THE SUBDIV CALCULATED IN FOR SUBDIVISION ished to perpetuate location B- SET 5/8" ROD 1 15" RED OAK 12" RED OAK 12" RED OAK SET 6" CEDAR BY CORNER DATE	TERSECTION OF THE TRUE N OF SECTIONS. Ing the position of the corner: 2 W/RLS CAP S78°E 29.0' N16°E 45.6' POST W/LOC TAG KENNIFTH LAND SURVEYOR N6.1 10068 AND SURVEYOR 10068
- SET BY STANDARD 2 - SET BY STANDARD 1/4 LINES SET BY STANDARD C. Description of monument for the state and united a signed by	BY CORNER Since found and or method appl SURVEY PROCEDURE PROCEDURE, AT THE SURVEY PROCEDURE for corner and accessories estable 18.6' 26.38' DE EGISTRATION NO. 1006	ed in restoring or re-esta FOR THE SUBDIV CALCULATED IN FOR SUBDIVISION ished to perpetuate location B- SET 5/8" ROD 15" RED OAK 12" RED OAK 12" RED OAK SET 6" CEDAR BY CORNER DATE 8 DATE	TERSECTION OF THE TRUE N OF SECTIONS. Ing the position of the corner: 2 W/RLS CAP \$78°E 29.0' N16°E 45.6' POST W/LOC TAG KENNIF LAND SURVEYOR NOGS LAND SURVEYOR 10068

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971 REVISED MAY 14, 1975