

SURVEY & REMONUMENTATION

JUL 23 1997

COMMISSION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
OGEMAW
(County)

Located In:

Corner Code #:

- | | | | | | |
|------------------------------------|---|-------------|-----------|---------------|--|
| 1. Public Land Survey | T | <u>24NR</u> | <u>3E</u> | <u>G-13</u> | |
| | T | <u>24NR</u> | <u>3E</u> | <u>H-13</u> | |
| | T | <u>24NR</u> | <u>3E</u> | <u>I-13</u> ✓ | |
| | T | R | R | | |
| 2. Property Controlling in Section | S | T | R | <u>Seg. 1</u> | |
| | S | T | R | | |
| 3. Miscellaneous Property in Sec. | S | T | R | | |
| | S | T | R | | |

LIBER 2 PAGE 274
STATE OF MICHIGAN
OGEMAW COUNTY
RECORDED
3 JAN 95 9:42 A.M.

WANDA MUZIK
REGISTER OF DEEDS
Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K	L
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

I, Timothy L. Lapham, in a field survey on December, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
G-13: COMMON CORNER WITH G-1, T23N, R3E, SEE LCRC FOR THAT CORNER AND REMONUMENTATION DOSSIER FOR ADDITIONAL INFORMATION. CORNER APPROVED AT PEER REVIEW MEETING HELD ON DECEMBER 21, 1994

H-13: COMMON CORNER WITH H-1, T23N, R3E, SEE LCRC FOR THAT CORNER AND REMONUMENTATION DOSSIER FOR ADDITIONAL INFORMATION. CORNER APPROVED AT PEER REVIEW MEETING HELD ON DECEMBER 21, 1994

I-13: COMMON CORNER WITH I-1, T23N, R3E, SEE LCRC FOR THAT CORNER AND REMONUMENTATION DOSSIER FOR ADDITIONAL INFORMATION. CORNER APPROVED AT PEER REVIEW MEETING HELD ON DECEMBER 21, 1994

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
G-13:
H-13:
I-13:

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
G-13:
H-13:
I-13:



Signed by [Signature]
Surveyor's Michigan License No. 27595

Date 12/29/94

SURVEY & REMONUMENTATION

MAY 03 1995

LAND CORNER RECORDATION CERTIFICATE COMMISSION Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
OGEMAW
(County)

Located In:

Corner Code ##

LIBER **3** PAGE **05**

STATE OF MICHIGAN
OGEMAW COUNTY
RECORDED

20 APR 95 10:20 A.M.

WANDA MUZIK
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

- | | | | |
|---------------------------------------|--------------------------|---------------|------------------|
| 1. Public Land Survey | T <u>24N</u> R <u>3E</u> | G-13 | |
| | T <u>24N</u> R <u>3E</u> | H-13 | |
| | T <u>24N</u> R <u>3E</u> | <u>I-13</u> ✓ | |
| | T _____ R _____ | | |
| 2. Property Controlling in Section | S _____ T _____ R _____ | | |
| | S _____ T _____ R _____ | | |
| 3. Miscellaneous Property in Sec. | S _____ T _____ R _____ | | |
| | S _____ T _____ R _____ | | <i>Def #2 pm</i> |
| 4. Lot No. _____, Recorded Plat _____ | | | |
| 5. Private Claims _____ | | | |

	A	B	C	D	E	F	G	H	I	J	K	L	I
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Timothy L. Lapham, in a field survey on December, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
G-13: COMMON CORNER WITH G-1, T23N, R3E, SEE LCRC FOR THAT CORNER AND REMONUMENTATION DOSSIER FOR ADDITIONAL INFORMATION. CORNER APPROVED AT PEER REVIEW MEETING HELD ON DEC 21, 1994

H-13: COMMON CORNER WITH H-1, T23N, R3E, SEE LCRC FOR THAT CORNER AND REMONUMENTATION DOSSIER FOR ADDITIONAL INFORMATION. CORNER APPROVED AT PEER REVIEW MEETING HELD ON DEC 21, 1994

I-13: COMMON CORNER WITH I-1, T23N, R3E, SEE LCRC FOR THAT CORNER AND REMONUMENTATION DOSSIER FOR ADDITIONAL INFORMATION. CORNER APPROVED AT PEER REVIEW MEETING HELD ON DEC 21, 1994

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
G-13: COMMON CORNER WITH G-1, T23N, R3E, SEE LCRC FOR THAT CORNER AND REMONUMENTATION DOSSIER FOR ADDITIONAL INFORMATION.
H-13: COMMON CORNER WITH H-1, T23N, R3E, SEE LCRC FOR THAT CORNER AND REMONUMENTATION DOSSIER FOR ADDITIONAL INFORMATION.
I-13: COMMON CORNER WITH I-1, T23N, R3E, SEE LCRC FOR THAT CORNER AND REMONUMENTATION DOSSIER FOR ADDITIONAL INFORMATION.

APPROVED BY
PEER REVIEW

12-21-94 *TW*

DATE P.A. 645 OF 1990

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
G-13: COMMON CORNER WITH G-1, T23N, R3E, SEE LCRC FOR THAT CORNER AND REMONUMENTATION DOSSIER FOR ADDITIONAL INFORMATION.
H-13: COMMON CORNER WITH H-1, T23N, R3E, SEE LCRC FOR THAT CORNER AND REMONUMENTATION DOSSIER FOR ADDITIONAL INFORMATION.
I-13: COMMON CORNER WITH I-1, T23N, R3E, SEE LCRC FOR THAT CORNER AND REMONUMENTATION DOSSIER FOR ADDITIONAL INFORMATION.

Signed by *[Signature]*

Date 4/20/95

Surveyor's Michigan License No. 27595

Attach to: T24N R3E I-13 Sec #2 MRD

SURVEY & REMONUMENTATION

MAY 03 1995

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
OGEMAW

(County)	Located In:	Corner Code #
1. Public Land Survey	T <u>23NR</u> <u>3E</u>	<u>I-1</u>
	T _____ R _____	_____
	T _____ R _____	_____
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	<u>Sec. 1</u>
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

LIBER **2** PAGE **258**
 STATE OF MICHIGAN
 OGEMAW COUNTY
 RECORDED
 3 JAN 95 9:34 A.M.
 WANDA HUZIK
 REGISTER OF DEEDS
 Register of Deeds Stamp & File Number

- 4. Lot No. _____, Recorded Plat _____
- 5. Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K
2	6		5		4		3		2		
3											
4	7		8		9		10		11		
5											
6	16		17		18		15		14		
7											
8	19		20		21		22		23		
9											
10	30		29		28		27		26		
11											
12	31		32		33		34		35		
13											

I, Timothy L. Lapham, in a field survey on December, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
 I-1: GLO CLASON 1846, SET POST
 CEDAR 8" N44E 29LKS
 CEDAR 9" N58W 7 LKS
 SPRUCE 10" S38W 53LKS
 CEDAR 8" S13E 37LKS
 1945 SHADKO(DNR), ESTABLISHED CORNER BASED ON FENCE SOUTH
 *** NOTE: CORNER COMMON TO I-13 T24N R3E

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
 I-1: FOUND 1/2" IRON
 DISTANCE EAST & WEST AGREE WITH GLO
 REMNENT OF OLD PAGE WIRE FENCE SOUTH ON CORNER
 ACCEPTED FOUND IRON AS BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER
 CORNER APPROVED AT PEER REVIEW MEETING HELD DECEMBER 21, 1994
 SEE DOSSIER FOR ADDITIONAL INFORMATION

APPROVED BY
 PEER REVIEW
 12-21-94
 DATE P.A. 345 of 1990

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
 I-1: SET 5/8"x36" REROD WITH 3-1/4" ALUMINUM OGEMAW REMON CAP IN MON BOX
 N59E 81.20' FD NAIL IN 10" TAMARACK
 S23E 50.05' FD NAIL IN 10" TAMARACK
 S70W 88.54' FD NAIL IN POWER POLE
 N15W 74.86 FD NAIL IN 10" TAMARACK

Signed by [Signature]
 Surveyor's Michigan License No. 27595

Date 12/29/94
 FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JI
 REVISED IN
 REVIEW