REMONUMENTATION

JUL 2 3 1997

Surveyor's Michigan License No. ____27595

COMMIS	31614	IER RECORDATION CERTIL Irement of Act 74, Mich. P.		
OGEMAW (County) 1. Public Land Survey	Located In: T _24N R _3E	Corner Code ≠	LIBER	2 PAGE 269 STATE OF MICHIGAN OGEMAN COUNTY RECORDED
	T <u>24N</u> R <u>3E</u> T R T R	M-13) 34 #1		3 JAN 95 9:38 A.M.
 Property Controlling in Section Miscellaneous Property in Sec. 	S T R S T R S T R S T R		Register of [WANDA MUZIK REGISTER OF DEEDS Deeds Stamp & File Number
	Recorded Plat		<u>A B</u>	CDEFGHIJKL
do hereby certify that under red in lines 1 and 2 above were in current manual of survey instr Management or by a decree of above were in conformance will Court of Law; established, expressed below: NOTE: Not more than 4 con this certificate. A. Description of original A-13: COMMON CORNER FOR ADDITIONAL 1994 M-13: COMMON CORNER	in a field survey on Dece quirements of P.A. 74, Michigan P. no conformance with regulations a uctions of the United States Department of Law and/or that the contit the rules of the Michigan Board re-established, monumented, recently the same town and the same tow	A. of 1970, the corner points mention and rules therefore as required in artment of the Interior, Bureau of Liner points mentioned in lines 3, 4 and of Land Surveyors or by a Decree e-monumented, recovered, found	the and 7 18-19-19-19-19-19-19-19-19-19-19-19-19-19-	ELD ON DECEMBER 21, ONUMENTATION DOSSIER
B. Description of corner e	evidence found and/or method	d applied in restoring or reesta	iblishing corner:	
M-13:				
C. Description of monume	ent for corner and accessories	s established to perpetuate loc	cating the position	n of the corner:
M-13:	7		•	OL MIC, J. PROFESSIONAL PROFESSIONAL SURVEICE NO. 27895

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1
REVISED MAY 14, 1
REVISED JAN.. 1

SURVEY & REMONUMENTATION

MAY 0 5 1997

LAND CORNER RECORDATION CERTIFICATE

For corners @OMMISSION	Filing Requir	ement of Act 74, Mich. I	A. 1970	
OGEMAW (County)	Located In:	Corner Code ##	LIEER 3 FALE STATE OF NICH	
1. Public Land Survey	T 24NR 3E T 24NR 3E T 23NR 3E T 23NR 3E	A-13 M-13 A / A 5 1/7/90 M-1 k 5 1/7/90	OGEMAN COUNT RECORDED 20 APR 95 10:2	
In Section S 3. Miscellaneous S	T R T R T R T R	Seg #2pm	WANDA HUZ Register of Deeds Stamp &	
4. Lot No, Recorde 5. Private Claims	d Plat	U	A B C D E F G	HIJKE
i, Timothy L. Lapham, in a find ohereby certify that under requirement in lines 1 and 2 above were in confor current manual of survey instructions of Management or by a decree of a Court of above were in conformance with the ru Court of Law; established, re-estable expressed below: NOTE: Not more than 4 corners, on this certificate. A. Description of original monum A-13: COMMON CORNER WITH	nts of P.A. 74, Michigan P.A. mance with regulations are of the United States Depart Law and/or that the corneles of the Michigan Board lished, monumented, reall in the same town a ent and accessories and A-1, T23N, R3E,	of 1970, the corner points mend rules therefore as required thent of the Interior, Bureau-oer points mentioned in lines 3, 4 of Land Surveyors or by a Decremonumented, recovered, found range, may be recorded d/or subsequent restoration SEE LCRC FOR THAT	in the Land 7 and 5 8 19 20 21 and and 5 8 19 20 21 and and as 10 30 29 28 11 12 31 32 33 13 13 15 CORNER AND REMONUMENTATION	-10 -11 -12 -15 -14 -13 -22 -23 -24 -27 -26 -25 -25 -25 -25 -25 -25 -25 -25 -25 -25
M-13: COMMON CORNER WITH	I M-1, T23N, R3E,	SEE LCRC FOR THAT	VIEW MEETING HELD ON DEC	ON DOSSIER
FOR ADDITIONAL INFO	I A-1, T23N, R3E, DRMATION. R WITH M-1, T23N,	SEE LCRC FOR THAT	lablishing corner: CORNER AND REMONUMENTATI THAT CORNER AND REMONUME	
FOR ADDITIONAL INFO	H A-1, T23N, R3E, DRMATION. R WITH M-1, T23N,	SEE LCRC FOR THAT	ocating the position of the corner: CORNER AND REMONUMENTATI THAT CORNER AND REMONUME	
Signed by Asset 1		Date:	4-20-75	
Surveyor's Michigan License No.	27595		FORM APPROVED BY MICHIGAN STATE BUARD OF LAN	ID SURVEYORS, JAM. 28, 1971 REVISED MAY 14, 1975 REVISED JAM 1989

SURVEYA

	OOL	W	اسا	Ç.	
REMO	UNC	М	EN	TAT	ION

LAND CORNER RECORDATION CERTIFICATE MAY 0 3 1995

For on	WIALV orners in	० ।४५०	Filing Requi	rement of Act 74, Mich.	. P.A. 1970	
	MAW COMM	IISSION	Located In:	Corner Code ≠≠	LIBER 2 PAGE 261 STATE OF MICHIGAN	
t. Pu	ublic Land Survey		T _23N R _3E T R	M-1	OGEMAN COUNTY RECORDED	
in 3. M	roperty Controlling Section iscellaneous roperty in Sec.	s s	T R T R T R T R T R		3 JAN 95 9:35 A.M. NANDA MUZIK REGISTER OF DEEDS Register of Deeds Stamp & File Number	H*
5. Prindo her in line currer Managabove Court expres	rivate Claims othy L. Lapham rebycertify that under rest and 2 above were in an	in a field equirements in conformations of the factor of Link the rules re-establish corners, all s. I monument SET POST 1974, St. 1974, St. 1974, St. 1974, St. 1975, St. 1/1976.	I survey on	A. of 1970, the corner points me and rules therefore as require sartment of the Interior, Bureau rer points mentioned in lines 3 of Land Surveyors or by a Dee-monumented, recovered, for and range, may be record and/or subsequent restorate N66E 34L., S. MAPLE NO CORNER MATERIAL OF CORNER MATERIAL OF CORNER MATERIAL OF NO CORNER MATERIAL OF NO CORNER MATERIAL	2 6 5 3 3 2 2 3 3 4 4 5 10 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	AT
В. (М-1	PREVIOUS, DIS DURING ROAD I TO BE LEANING ACCEPTED FOUR APPROVED AT 1	STANCE W RECONSTR 3, ND IRON PEER REV	EST 1.6' SHORM UCTION MEASURE AS BEST AVAIL	T OF PREVIOUS, CAPP ES 51.32° TO TOP OF ABLE EVIDENCE OF OR ELD ON DECEMBER 21,	eestablishing corner: DAD E-W, DISTANCE EAST MATCHES PED IRON NORTH BENT TO NORTH APPARIS F IRON AS IS, ENTIRE R/W IRON APPERIGINAL CORNER POSITION, CORNER 1994. APPROVED BY PEER REVIEW	en: Ar:

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: M-1: SET 5/8"x36" REROD WITH 3-1/4" ALUMINUM REMON CAP IN MON BOX

SO2W 42.39 SET SPIKE IN POWER POLE

S32W 54.75 SET SPIKE IN 6" BALSAM FIR N56W 76.39 SET SPIKE IN 10" OAK

N34E 48.85 SET SPIKE IN 8" OAK

Surveyor's Michigan License No.