SURVEY & REMONUMENTATION

Surveyor's Michigan License No.

	OCT 2 9 1996		ER RECORDATION to the second section of the second section in the section in								
Fo	r corners in OSCEOLA COMMISSION			ı							
_	(County)	cated In:	Corner Code	#							
•	, county	17N 10W	C-13		APP	ROVED L			R		
1.	Public Land Survey T	R				P.A. 345					
		R		4	1	USCEOR	County	71	A.)	
		R			M	MILLU	W)		La	and the	
					2	1111	1 19	96			
2.					Min H	_422- 1	fr	1			
	• •	_				•					
3.					aister o	Deeds S	Stamp &	File	Num	ber	
		R					· · · · ·				
4	Lot No, Recorded Plat	í			_ •	3 C D	E			ĸ.	
	Private Claims				_ ^_	, ř ř		' 	, <u>, ,</u>	``	<u>``</u>
٥.	Tivato oranio				2 6		 	_ \$	ş·	+	\vdash
					3 🖳						
	Matthew McClung		July 1	96	4 💄	\		 10			2
	, in a field su	IDION OD			5	- ĭ	ΙĬΙ	Ĭ	Ï		Ī
٦, . do	hereby certify that under requirements of P	A 74 Michigan P A	of 1970, the corner of	oints mentioned							
in	lines 1 and 2 above were in conformance	with regulations an	nd rules therefore as	required in the	6 -1	B 7	116	15 !	14	1	3 1
cu	rrent manual of survey instructions of the t	United States Depart	rtment of the Interior,	, Bureau of Land	7		╂╌┼╌╂		┢		
Ma	nagement or by a decree of a Court of Law a	and/or that the corne	er points mentioned i	n lines 3, 4 and 5	8 -1	920	 	22	23	+-	4
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as						-	+++	~	╁┷┼		-
	urt of Law; established, re-established, pressed below:	, inditalinented, re-i	monumented, recov	erea, touria ps	10 _3	029	28	27	26		ļ 5
		the name town o	nd range may be	racordad	11				\perp		<u></u>
N	OTE: Not more than 4 corners, all in	the same town at	ilu ralige, tijay be	recorded	12			34	1 25		
	on this certificate.				13			34 	Ĭ		j
В.	Beech 24" N41E 50 Beech 8" N56W 33 From 1891 to 1904 appr program, in which surv most part, a 3" glazed at each government set tile per corner, place Description of corner evidence foun Found 5/8" X 30" Iron excavated to 28" below Removed rod and place County Corner is 1.95 To the East it is 2.61	lks. reximately, revers Temp l tile fille c corner in ed atop of e d and/or method n Rod set Se surface an Osceola Con feet North	ed with circle ded with circle townsheach other, applied in restoring the court of big and found not monument and 6.6 fe	abull, did aders from aip. There (continu gorreestablishing blue rock to other evi- at 6" below eet West of	the wa for were ed on g conner 4" b dence surf	ork. ge, w suppo back elow of c ace. ola M	For terms to the second to the	the lac to b		3	
C.	Description of monument for corner		established to pe ment, which						n s	à	

FORM APPROVED BY MICHIGAN STATE BDARD OF LAND SURVEYORS, JAN. 28, 1971 Revised May 14, 1975 Revised Jan., 1983

July

OSCEOLA COUNTY REGISTER OF DEEDS

96 AUG 30 AM 10: 29

Mancy Crawford

thereby making the corner 4 feet long. Sometimes a solid tile, with a cross in the top was used, and sometimes a 1/2" iron bars were added to the tile. Notes of the work were kept in ledgers, and given to the townships, and 5 of the townships have been recorded in the County records.

There is 1 LCRC; Liber 2, Page 30

Richmond Township Book Pages 28 and 29.

SURVEY & REMONUMENTATION

OCT 2 D 1996

COMMISSION