JAN 17 1996

## COMMISSION LAND CORNER RECORDATION CERTIFICATE

For corners in	Filing Requirem	nent of Act 74, Mich. P.A	. 1970	•
Osceola	Located In:	0	:	
(County)		Corner Code ##		
1. Public Land Survèy	19N 10W T R T R T R	D-13	APPROVED LAND CORNER P.A. 345 OF 1990 Osceola County	₹
2 Property Controlling S	T R		19 Oct. 1995	<del>/.</del>
	T R T R		mather Shell	the said
3. Miscellaneous S _	T R		Register of Deeds Stamp & File	// Number
Property in Sec. S _	T R			
4. Lot No, Records	ed Plat		A B C D E F G H	
5. Private Claims		•		
			3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	2-1-1-
Matthew McClung	Oc	tober 14,	95 4 7 8 9 10	11 -12-
1,, in a do hereby certify that under requireme in lines 1 and 2 above were in confo current manual of survey instructions Management or by a decree of a Court above were in conformance with the recourt of Law; established, re-established below:	ents of P.A. 74, Michigan P.A. of the rmance with regulations and rate of the United States Department of Law and/or that the corner putes of the Michigan Board of Li	1970, the corner points mention ules therefore as required in t ent of the Interior, Bureau of La oints mentioned in lines 3, 4 an and Surveyors or by a Decree o	ned 6 18 17 16 15 16 15 16 15 16 17 16 15 16 17 16 17 16 17 17 16 17 17 18 17 18 17 18 17 18 18 18 18 18 18 18 18 18 18 18 18 18	23 24
NOTE: Not more than 4 corners	, all in the same town and	range, may be recorded	11 29 29 20	
on this certificate.			12 31 32 33 34	35 36
A. Description of original monum	nent and accessories and/o	r subsequent restoration:	13	L
program, in which part, a 3" glazed	2 42 lks. approximately, 0 surveyors Temple tile filled with t corner in the	e and Trumbull, of a cinders from a township. There	forge, were placed at were supposed to be	
B Description of corner evidence	e found and/or method app	lied in restoring or reestab	lishing corner:	
East and barbed fe 12.48 feet.	ine of fence linence West, N741/2	e to East. Found RW 9.6 feet. Lir	MATTHEW  A. McCLUNG LAND SURVEYOR NO.  13037	re
C. Description of monument for c	orner and accessories esta	ablished to perpetuate loca	ting the position of the comer:	
1" pipe 30" in len 22" Maple 4" Maple 9" spruce		anting N3OW 103	3" brass cap mounted o	n a
m D	Tucol.	٠	- 1 4 4 4005	•
igned by Malithew 7	11 Cluy	Date Oct	tober 14, 1995	
urveyor's Michigan License No		F0	IRM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEY	
	•		2 REV	VISED MAY 14, 1975 NEVISED JAR., 1983

thereby making the corner 4 feet long. Sometimes a solid tile, with a cross in the top was used, and sometimes a 1/2" iron bars were added to the tile. Notes of the work were kept in ledgers, and given to the townships, and 5 of the townships have been recorded in the County records.