LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF–:	LOCATED IN–:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 19 N., R. 8 W.	C-11, D-11, E-11
2. PROPERTY CONTROLLING IN SECTION	,T. N. S., R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. , RECORDED PLAT

5. PRIVATE CLAIMS

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on July 16, 1980, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument:

E-11
Fd Brass Cap Mon &
3-3" Tiles; added
Ced Post w/loc tag

6" R.Oak	N35°E	14.6'
4" Blk.Cherry	S5 °W	12.8'
13" Maple	S70°W	25.4'
Nly edge hdwd swp.	Due S	32'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

C-11 Fd. 4" round conc. monument at old fence corner, fence's on ground to E. & S. Same corner as used by RLS - Matt McClung.

D-11 Fd. and accepted 1 1/4" Ir. in conc. that fits one McClung Wit.

E-11 Fd. Brass Capped Osceola County Monument that fits four McClung Wit.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-11
Fd 4" round conc. mon.;
added ced post w/loc tag

6" R.Oak	N55°W	25.1'
4" R.Oak	N55°E	20.8'
Ctr E-Wgr. rd.	Due S	21'
Fd conc Plat Mon.	Due S	67.30'

D-11
Fd 1 1/4" round ir.
in 18" round ruffpoured
conc w/ stones;
added Ced post w/loc tag

13" R.Oak	S85°E	30.8'
5" Maple	S60°E	28.1'
13" R.Oak	S20°E	38.1'
Ely edge Lake	Due W	15'

SIGNED BY Carl F. Roser DATE 7-17-80

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

STATE OF MICHIGAN
CARL F. ROSER
(SEAL) LAND SURVEYOR
No. 12028
REGISTERED LAND SURVEYOR

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

HARTWICK TOWNSHIP
OSCEOLA COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET