LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 19 N. S., R. 8 E. W.	E-10,C-10
2. PROPERTY CONTROLLING IN SECTION 29	,T. 19 N. S., R. 8 E. W.	9
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	

4. LOT NO. _____, RECORDED PLAT _____

5. PRIVATE CLAIMS _____

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on July 16, 1980, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. (cont.)

E-10
Fd 3/4" x 34" rod in tile;
added DNR Mon & ced post.
11" Sug Map. S40°E 63.8'
3" Soft Map. S20°E 47.0'
9" Sug Map. S30°W 35.6'
Approx. ctr. 4' x 4' rock
S60°E 34'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

C-10 Fd. and accepted brass capped Osceola County Mon. that fits 3 McClung Wits.

9 Estab. E1/8 Cor. on E-W one-quarter line, mid-way & on line betw. E1/4 Cor. & ctr. of S29. An unused, crooked E-W trail is 163'± S. A beautiful 20" W. Birch is 160' W.

E-10 Recovered 3/4" x 34" rod in 3" tile in S Edge of Beaver Pond. Corner fits two McClung Wits.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-10
Fd. brass cap. mon & 5/8" iron.
Ctr. N-S gravel rd Due W 2'±
5" R. Oak N30°W 60.84'
28" R. Oak N55°E 48.30'
27" Beech S50°E 61.16'
Set Ced post w/loc. tag. Due E 33'

9
Set 5/8" x 34" re-rod w/RLS cap & ced post w/loc. tag.
N-S smooth wire on trees Due W 163'±
3" R. Oak N45°E 7.1
3" Ash S35°E 11.7'
3" R. Oak S85°W 4.9'

SIGNED BY Carl F. Roser 7-17-80 DATE _____

STATE OF MICHIGAN CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

HARTWICK TOWNSHIP
OSCEOLA COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET