## SURVEY & REMONUMENTATION

OCT 2 9 1996

## COMMISSION LAND CORNER RECORDATION CERTIFICATE

For corners in	Filing Requir	ement of Act 74, Mic	ch. P.A. 1970		
Osceola	Located In:	Corner Code ##			
(County)	19N 8W	I-8			
Public Land Survey	TR			APPROVED LAN P.A. 345 O	
·	T R			Osceola C	
	TR	<del></del>	··   4	Muthew	M Elling
2. Property Controlling	S R		i i	27 Aug	1996
in Section	<b>S</b> T R		_		-
3. Miscellaneous	S T R		- Reg	ister of Deeds Sta	mp & File Number
Property in Sec.	S R				
4. Lot No , Ro	ecorded Plat			ABCDE	FGHIJKŁM
				2 6 5	4 - 1 - 3 2 - 1 - 1 - 1
Matthew McClung	g 14 .	August	1996	4 7 8	9 10 11 12
	in a field survey on			5	
do hereby certify that under requ	uirements of P.A. 74, Michigan P.A. conformance with regulations ar	. of 1970, the corner points	mentioned	6 18 17	16151413
current manual of survey instru	ictions of the United States Depai	rtment of the Interior, Bure	au of Land	7	
	Court of Law and/or that the corne h the rules of the Michigan Board i	'		8 19 20	21 22 23 24
Court of Law; established, re-	e-established, monumented, re-			9	
expressed below:				10 30 29	28 27 26 25
on this certificate.	orners, all in the same town a	na range, may be reco	raea	12 31 32	33 34 35 36
				13	
	nonument and accessories an				
	set by deputy sur			on July 7,	
	l post 40.00 chain 522W 18 Lks.	s irom the bou	ttn.		
	560E 17 Lks.				
	004 approximately,	Osceola Count	y had a	remonumenta	tion
program, in whi	ch surveyors Temp	le and Trumbul	.l, did t	he work. Fo	r the
	glazed tile fill				
	nent set corner in r, placed atop of o				d to be 3
		,		r	
,	vidence found and/or method	•			
	el pipe in monumen				
distance from E	erner is in fence to 1/4 Cor to the N	rows going mas E Corner of Se	ection 22	is 2.6017	asurea 1 feet
	stance from the E				
is 2,638.02 fee	:t.				
	•				
			•		
C Description of manufact	nt for corner and accessories	established to pernetus	ate locating the	nosition of the co	rner
-					4
Corner 1-8. 1s a 1" pipe 18" i	Osceola County Mon	nument, which	15 a 3" k	orass cap m	ounted on
	r Fence Post West	38.40 feet.			OF MICH
Power Pole	N460W 38.40 feet	-		, d	W. F. C.
	er Fence Post East			<b>F</b>	% MATTHEW Y
pourn wood	Gate Post N74E 4	o.ou reet.			A. McCLUNG
				والمرادة وال	SURVEYOR
				The state of the s	NO. NO.
					1303/
MrA	Mucol.		August	14, 1996	E CO LAND
Signed by Thursday	W TH Cly	Date	9	,	- ASSESSMENT OF THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TO PERSON NAMED
Surveyor's Michigan License	e No13037		FORM APPROV	/ED BY MICHIGAN STATE BOARI	D OF LAND SURVEYORS, JAN. 28, 1971
				× .	REVISED MAY 14, 1975 REVISED JAN., 1983

OSCEOLA COUNTY REGISTER OF DEEDS

96 AUG 30 AH 10: 30

Nancy Crawford

thereby making the corner 4 feet long. Sometimes a solid tile, with a cross in the top was used, and sometimes a 1/2" iron bars were added to the tile. Notes of the work were kept in ledgers, and given to the townships, and 5 of the townships have been recorded in the County records.

Hartwick Township Records Book; Front Pages, Page 4 and Pages 20 and 21. South 1/2 East Section Line 22=2,615.00 feet. North 1/2 East Section Line 22=2,594.00 feet.

SURVEY & REMONUMENTATION

OCT 2 9 1996

COMMISSION