# SURVEY & REMONUMENTATION

NOV 01 1999

SECTION

## LAND CORNER RECORDATION CERTIFICATE

(County)	Located in: Corner Code #			
1. Dublic Land Comm.	т 19N 8W K-	7		
1. Public Land Survey	TRTR	<del></del>		
·	TR			
2 Branach Cauta-III-				
2. Property Controlling in Section	\$ TR			
3. Miscellaneous	S TR	<u> </u>		
Property in Sec.	S TR			
			Register of Deeds Stamp & File Numbe	r
4. Lot No, Record	ded Plat			
5. Private Claims		<del></del>	A B C D E F G H I J K L	
			2 6 5 4 3 2	_
. Dobout T. West			3	
requirements of P.A. 74 Michigan	in a field survey on Aug. 11 , 19 <sup>99</sup> on P.A. of 1970, the corner points mentioned in lin	do hereby state that under	4 - 7 - 9 - 9 - 10 - 11 - 1	<u>,</u>
comormance with requisitions and	fules inereinte as required in the current manual of		5 F	
that the corner points mentioned i	nterior, Bureau of Land Management or by a decree	of a Court of Law and /or	6 19 17 16 15 14 13	<b></b> .
Coard of Land Surveyors of Dy	a Decree of a Court of law established re-e-	i me rules of the Michigan stablished, monumented,	7	_
recovered, found as expressed beli	ow:	·	8 19 20 21 22 23 24	_
NOTE: Not more than 2 corne on this certificate.	ers, all in the same town and range, may be re	corded	9	
on this certificate.			10 30 29 28 27 26 25	_
K-7 - SW Corner of Section	n 13, T19N, R8W		11	
			12 31 32 33 34 35 36	<u> </u>
A. Description of original mon	nument and accessories and/or subsequent	restoration:	13	
1838 –Sibley	1891 – 1904 – A. Temple		Undated Hartwick Twp Book	
#1-16" Sugar N621/4E 41Lks	Remonumentation of T19		Cor 13,14,23 & 24	
#2- 20" Sugar N27W 36 Lks	Set 3" Clay tiles		#3 Elm SW 47'.	
			#4 Elm NW 43½'	
,				
,				
•	(SFF AVED FOR CON	TIME ATION OF		
Description of corner evide	(SEE OVER FOR CON		"A")	
	ence found and/or method applied in restorir	ng or reestablishing co	"A") rner:	
I found an Osceola County M	ence found and/or method applied in restoring for the following at the intersection of C/L's of Recomment at the intersection of C/L's of Recomment at the intersection of C/L's of Recommendation in the following forms are the following forms and the following forms are the following forms and the following forms are	ng or reestablishing col pad East and West an	"A") rner: d North and South. The road at this location b	as
I found an Osceola County M	ence found and/or method applied in restorir	ng or reestablishing col pad East and West an	"A") rner: d North and South. The road at this location b	as
I found an Osceola County Mobeen raised aprox. 6'. McClu	ence found and/or method applied in restoring for the intersection of C/L's of Roung had measurement to 1/4Corner North (	ng or reestablishing colored East and West and 1/4 Ea	"A") rner: d North and South. The road at this location h st corner of 2690,85"	
I found an Osceola County Mobeen raised aprox. 6'. McClu Condition of the accessories	ence found and/or method applied in restoring forument at the intersection of C/L's of Rung had measurement to 1/4Corner North of the follows: #1 Gone, #2Gone, #3Gone	ng or reestablishing colored East and West an of 2630.96' and 1/4 Ea	"A") rner: d North and South. The road at this location hast corner of 2690,85"	
I found an Osceola County Mobeen raised aprox. 6'. McClu Condition of the accessories	ence found and/or method applied in restoring for the intersection of C/L's of Roung had measurement to 1/4Corner North (	ng or reestablishing colored East and West an of 2630.96' and 1/4 Ea	"A") rner: d North and South. The road at this location hast corner of 2690,85"	
I found an Osceola County Mobeen raised aprox. 6'. McClu Condition of the accessories	ence found and/or method applied in restoring from the intersection of C/L's of Roung had measurement to 1/4Corner North of the follows: #1 Gone. #2Gone. #3Gone.	ng or reestablishing colored East and West an of 2630.96' and 1/4 Ea	"A") rner: d North and South. The road at this location hast corner of 2690,85"	
I found an Osceola County Mobeen raised aprox. 6'. McClu Condition of the accessories	ence found and/or method applied in restoring from the intersection of C/L's of Roung had measurement to 1/4Corner North of the follows: #1 Gone. #2Gone. #3Gone.	ng or reestablishing colored East and West an of 2630.96' and 1/4 Ea	"A") rner: d North and South. The road at this location hast corner of 2690,85"	
I found an Osceola County Meen raised aprox. 6'. McClu Condition of the accessories at #7 Found in good condition,	ence found and/or method applied in restoring from the intersection of C/L's of Roung had measurement to 1/4Corner North of the areas follows: #1 Gone, #2Gone, #3Gone, #8 Found in good condition, #9 Found in g	ng or reestablishing colored East and West an of 2630.96° and ¼ East, #4Gone, #5 Found in good condition and #1	"A") rner: d North and South. The road at this location hast corner of 2690,85" n good condition, #6 Found in good condition, 10 Found in good condition.	
I found an Osceola County Meen raised aprox. 6'. McClu Condition of the accessories at #7 Found in good condition,	ence found and/or method applied in restoring from the intersection of C/L's of Roung had measurement to 1/4Corner North of the follows: #1 Gone. #2Gone. #3Gone.	ng or reestablishing colored East and West an of 2630.96° and ¼ East, #4Gone, #5 Found in good condition and #1	"A") rner: d North and South. The road at this location hast corner of 2690,85" n good condition, #6 Found in good condition, 10 Found in good condition.	
I found an Osceola County Mobeen raised aprox. 6'. McClu Condition of the accessories: #7 Found in good condition,  C. Description of monument for	Annument at the intersection of C/L's of Roung had measurement to 1/4Corner North are as follows: #1 Gone, #2Gone, #3Gone, #8 Found in good condition, #9 Found in good condition, #9 Found in good corner and accessories established to perpendicular to the corner and the corner a	ng or reestablishing coload East and West and for 2630.96° and ½ East, #4Gone, #5 Found in good condition and #1	"A") rner: d North and South. The road at this location has corner of 2690,85' n good condition, #6 Found in good condition, 10 Found in good condition.	•
I found an Osceola County Mobeen raised aprox. 6'. McClu Condition of the accessories: #7 Found in good condition, C. Description of monument for I accept Osceola County Mor	Annument at the intersection of C/L's of Roung had measurement to 1/4Corner North are as follows: #1 Gone, #2Gone, #3Gone, #8 Found in good condition, #9 Found in good condition, #9 Found in good corner and accessories established to perpendicular to the corner and the corner a	ng or reestablishing colored East and West and of 2630.96° and ¼ East, #4Gone, #5 Found in good condition and #1 petuate locating the poetuate locating the poetuate locating as a substitution of the poetuate locating the	"A") rner: d North and South. The road at this location hast corner of 2690,85" n good condition, #6 Found in good condition, 10 Found in good condition.	•
I found an Osceola County Mobeen raised aprox. 6'. McClu Condition of the accessories at #7 Found in good condition,  C. Description of monument for I accept Osceola County More careful and faithful reestablish	Annument at the intersection of C/L's of Roung had measurement to 1/4Corner North of the are as follows: #1 Gone, #2Gone, #3Gone, #8 Found in good condition, #9 Found in good condition of the position of the original corner had been as follows: #1 Gone of the original corner and accessories of the original corner and the position of the original corner and the pos	ng or reestablishing colored East and West and of 2630.96° and ¼ East, #4Gone, #5 Found in good condition and #1 petuate locating the poetuate locating the poetuate locating as a substitution of the poetuate locating the	"A") rner: d North and South. The road at this location has corner of 2690,85' n good condition, #6 Found in good condition, 10 Found in good condition.	•
I found an Osceola County Mobeen raised aprox. 6'. McClu Condition of the accessories at #7 Found in good condition,  C. Description of monument for I accept Osceola County More careful and faithful reestablish.  Center of Tele Ped. S12W 71 P. Pole N30W 60.27' #5	Annument at the intersection of C/L's of Roung had measurement to 1/4Corner North are as follows: #1 Gone, #2Gone, #3Gone, #8 Found in good condition, #9 Found in good condition are corner and accessories established to perform the corner of the position of the original corner.	ng or reestablishing colored East and West and of 2630.96° and ¼ East, #4Gone, #5 Found in good condition and #1 petuate locating the poetuate locating the poetuate locating as a substitution of the poetuate locating the	"A") rner: d North and South. The road at this location has corner of 2690,85' n good condition, #6 Found in good condition, 10 Found in good condition.	•
I found an Osceola County Mobeen raised aprox. 6'. McClu Condition of the accessories at #7 Found in good condition,  C. Description of monument for I accept Osceola County Mor careful and faithful reestablish. Center of Tele Ped. S12W 71 P. Pole N30W 60.27' #5 Center of 4" Iron Post N65E	Annument at the intersection of C/L's of Roung had measurement to 1/4Corner North of the are as follows: #1 Gone, #2Gone, #3Gone, #8 Found in good condition, #9 Found in good condition of the position of the original corner. The corner and accessories established to perform the position of the original corner. The corner and accessories established to perform the position of the original corner. The corner and accessories established to perform the position of the original corner.	ng or reestablishing colored East and West and of 2630.96° and ¼ East, #4Gone, #5 Found in good condition and #1 petuate locating the poetuate locating the poetuate locating as a substitution of the poetuate locating the	"A") rner: d North and South. The road at this location has corner of 2690,85' n good condition, #6 Found in good condition, 10 Found in good condition.	•
I found an Osceola County Mobeen raised aprox. 6'. McClu Condition of the accessories at #7 Found in good condition,  C. Description of monument for I accept Osceola County More careful and faithful reestablish.  Center of Tele Ped. S12W 71 P. Pole N30W 60.27' #5	Annument at the intersection of C/L's of Roung had measurement to 1/4Corner North of the are as follows: #1 Gone, #2Gone, #3Gone, #8 Found in good condition, #9 Found in good condition of the position of the original corner. The corner and accessories established to perform the position of the original corner. The corner and accessories established to perform the position of the original corner. The corner and accessories established to perform the position of the original corner.	ng or reestablishing colored East and West and of 2630.96° and ¼ East, #4Gone, #5 Found in good condition and #1 petuate locating the poetuate locating the poetuate locating as a substitution of the poetuate locating the	"A") rner: d North and South. The road at this location has corner of 2690,85' n good condition, #6 Found in good condition, 10 Found in good condition.	•
I found an Osceola County Mobeen raised aprox. 6'. McClu Condition of the accessories at #7 Found in good condition,  C. Description of monument for I accept Osceola County Mor careful and faithful reestablish. Center of Tele Ped. S12W 71 P. Pole N30W 60.27' #5 Center of 4" Iron Post N65E	Annument at the intersection of C/L's of Roung had measurement to 1/4Corner North of the are as follows: #1 Gone, #2Gone, #3Gone, #8 Found in good condition, #9 Found in good condition of the position of the original corner. The corner and accessories established to perform the position of the original corner. The corner and accessories established to perform the position of the original corner. The corner and accessories established to perform the position of the original corner.	ng or reestablishing colored East and West and of 2630.96° and ¼ East, #4Gone, #5 Found in good condition and #1 petuate locating the poetuate locating the poetuate locating as a substitution of the poetuate locating the	"A") rner: d North and South. The road at this location has corner of 2690,85' n good condition, #6 Found in good condition, 10 Found in good condition.	•
I found an Osceola County Mobeen raised aprox. 6'. McClu Condition of the accessories: #7 Found in good condition,  C. Description of monument for I accept Osceola County More careful and faithful reestablist Center of Tele Ped. S12W 71 P. Pole N30W 60.27' #5 Center of 4" Iron Post N65E of N. Cor. Of Conc. R/W Market	Annument at the intersection of C/L's of Rung had measurement to 1/4Corner North are as follows: #1 Gone, #2Gone, #3Gone, #8 Found in good condition, #9 Found in goor corner and accessories established to perhaument (1 ½" Pipe with Osceola County R hment of the position of the original corne .7'  60.62' #9 ex S56E 58.25' #6	ng or reestablishing colored East and West and for 2630.96° and ½ East, #4Gone, #5 Found in good condition and #1 petuate locating the potential east as substant.	"A") rner: d North and South. The road at this location has corner of 2690,85" in good condition, #6 Found in good condition, 10 Found in good condition.  esition of the corner: antial marker for the corner and is accepted as	•
I found an Osceola County Mobeen raised aprox. 6'. McClu Condition of the accessories at #7 Found in good condition,  C. Description of monument for I accept Osceola County Mor careful and faithful reestablish.  Center of Tele Ped. S12W 71 P. Pole N30W 60.27' #5 Center of 4" Iron Post N65E	Annument at the intersection of C/L's of Roung had measurement to 1/4Corner North of the are as follows: #1 Gone, #2Gone, #3Gone, #8 Found in good condition, #9 Found in good condition of the position of the original corner. The corner and accessories established to perform the position of the original corner. The corner and accessories established to perform the position of the original corner. The corner and accessories established to perform the position of the original corner.	ng or reestablishing colored East and West and for 2630.96° and ½ East, #4Gone, #5 Found in good condition and #1 petuate locating the potential east as substant.	"A") rner: d North and South. The road at this location has corner of 2690,85' n good condition, #6 Found in good condition, 10 Found in good condition.	•
I found an Osceola County Meen raised aprox. 6'. McChe Condition of the accessories #7 Found in good condition, #7	Annument at the intersection of C/L's of Rung had measurement to 1/4Corner North are as follows: #1 Gone, #2Gone, #3Gone, #8 Found in good condition, #9 Found in gor corner and accessories established to performent of the position of the original corne are some of the position of the original corne are som	ng or reestablishing colored East and West and for 2630.96° and ½ East, #4Gone, #5 Found in good condition and #1 petuate locating the potential east as substant.	"A") rner: d North and South. The road at this location has corner of 2690,85" in good condition, #6 Found in good condition, 10 Found in good condition.  esition of the corner: antial marker for the corner and is accepted as	•
I found an Osceola County Mobeen raised aprox. 6'. McChe Condition of the accessories: #7 Found in good condition,  C. Description of monument for I accept Osceola County More careful and faithful reestablist  Center of Tele Ped. S12W 71 P. Pole N30W 60.27' #5 Center of 4" Iron Post N65E N. Cor. Of Conc. R/W Market  Signed by Surveyor's Michigan License No APPROVED P.A. 34	Annument of the position of the original corner.  To corner and accessories established to perform the position of the original corner.  To corner and accessories established to perform the position of the original corner.  To corner and accessories established to perform the position of the original corner.  To corner and accessories established to perform the position of the original corner.  To corner and accessories established to perform the position of the original corner.  To corner and accessories established to perform the position of the original corner.  To corner and accessories established to perform the position of the original corner.  To corner and accessories established to perform the position of the original corner.  To corner and accessories established to perform the position of the original corner.  To corner and accessories established to perform the position of the original corner.	ng or reestablishing colored East and West and for 2630.96° and ½ East, #4Gone, #5 Found in good condition and #1 petuate locating the potential east as substant.	"A") rner: d North and South. The road at this location has corner of 2690,85" in good condition, #6 Found in good condition, 10 Found in good condition.  esition of the corner: antial marker for the corner and is accepted as	•
I found an Osceola County Mobeen raised aprox. 6'. McChe Condition of the accessories: #7 Found in good condition,  C. Description of monument for I accept Osceola County More careful and faithful reestablist  Center of Tele Ped. S12W 71 P. Pole N30W 60.27' #5 Center of 4" Iron Post N65E N. Cor. Of Conc. R/W Market  Signed by Surveyor's Michigan License No APPROVED P.A. 34	Annument at the intersection of C/L's of Rung had measurement to 1/4Corner North are as follows: #1 Gone, #2Gone, #3Gone, #8 Found in good condition, #9 Found in good condition, #9 Found in good condition of the original corner and accessories established to perform the position of the original corner.  The corner and accessories established to perform the position of the original corner.  The corner and accessories established to perform the position of the original corner.  The corner and accessories established to perform the position of the original corner.  The corner and accessories established to perform the position of the original corner.	ng or reestablishing coload East and West and for 2630.96° and ½ East, #4Gone, #5 Found in good condition and #1 petuate locating the poetuate locating the poetuate.	"A") rner: d North and South. The road at this location has corner of 2690,85" In good condition, #6 Found in good condition, 10 Found in good condition.  Position of the corner: antial marker for the corner and is accepted as	aa a
I found an Osceola County Mobeen raised aprox. 6'. McChe Condition of the accessories: #7 Found in good condition,  C. Description of monument for I accept Osceola County More careful and faithful reestablist  Center of Tele Ped. S12W 71 P. Pole N30W 60.27' #5 Center of 4" Iron Post N65E N. Cor. Of Conc. R/W Market  Signed by Surveyor's Michigan License No APPROVED P.A. 34	And the position of the original corner.  To the position of the original corner.	ng or reestablishing coload East and West and for 2630.96° and ½ East, #4Gone, #5 Found in good condition and #1 petuate locating the poetuate locating the poetuate.	"A") rner:  d North and South. The road at this location hast corner of 2690.85"  In good condition, #6 Found in good condition, 10 Found in good condition.  Position of the corner:  antial marker for the corner and is accepted as  AN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 19 REVISED MAY 14,19	
I found an Osceola County Mobeen raised aprox. 6'. McChe Condition of the accessories: #7 Found in good condition,  C. Description of monument for I accept Osceola County More careful and faithful reestablist  Center of Tele Ped. \$12W 71 P. Pole N30W 60.27' #5 Center of 4" Iron Post N65E No. Cor. Of Conc. R/W Market  Signed by Polytic Surveyor's Michigan License No APPROVED P.A. 34 Osceola County More Conc. R/W Market  Osceola County More  APPROVED P.A. 34 Osceola County More  Condition of the accessories of the of	And the position of the original corne of the position of the position of the original corne of the original corne of the position of the original corne of the position of the original corne of the original corne of the position of the original corne of the or	ng or reestablishing coload East and West and for 2630.96° and ½ East, #4Gone, #5 Found in good condition and #1 petuate locating the poetuate locating the poetuate.	"A") rner: d North and South. The road at this location hast corner of 2690,85" In good condition, #6 Found in good condition, 10 Found in good condition.  Position of the corner:  antial marker for the corner and is accepted as  AN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 19.	71 75 73

### CONTINUATION OF DESCRIPTION OF ORIGINAL MONUMENT AND ACCESSORIES AND/OR SUBSEQUETNT RETORATION.

### <u>1976 – McClung LS 13037</u> LCRC

L. 1, Page 423 Fd. 3/4" Rod

#5 - P. Pole #118 N40W 59.8'

#6 - Proj. Maker S45E 58.3°

### 1976- McClung LS 13037

Survey record

L.601, Pg. 463 Fd. ¾" Rod Set ¼' Angle Iron

#5 - P. Pole #118 N40W 59.8'

#6-Proj. Marker S45E 58.3'

### 1993 Pullen LS 39035

Survey record L 601 Pg 463

#6 - Concrete Proj. Marker S40E 58.3'

#7 - St. Sign N30E 50.90'

#5 - P. Pole N30W 60.27'

#8 - Ctr. Tele Ped S30E 71.55°

### 1997- McClung LS 13037

Fd. 2"x3"x20' angle iron,

5/8' rod & Male sucker rod

Set Osceola County Monument over sucker Rod.

#6 - N. Cor Cem. R/W Marker S56E 58.25'

#9 - Cen. 4" Iron Post N52E 60.6'

#5 - Electric Post N34W 60.3°

#10-Top Cen. Tele Ped S12W 71.7'

**SURVEY &** REMONUMENTATION

NOV 01 1999

**SECTION**