## LAND CORNER RECORDATION CERTIFICATE

1 1 10 10 1 1 1 1 1 1 1 25x p

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN -:	CORNER CODE NUMBER	
1. PUBLIC LAND SURVEY	T. 28 N. R. 1	K-9; L-10	
2. PROPERTY CONTROLL- 2 ING IN SECTION—2	25 ,T. 28 N. R. 1	12	
3. MISCELLANEOUS PROPERTY IN SECTION —	,T		
4. LOT NO , RE	CORDED PLAT		
5. PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND
re-established, monumented, re and rules therefore as required Bureau of Land Management of and 5 above were, in a field sur	lines 1 and 2 above were, in se-monumented, recovered or a in the current manual of surer by a decree of a court of law vey on	restored as expressed below an expressed as expressed as a feel of the expressed below an expressed below an expressed below an expressed below as expressed below an	of P.A. 74, Michigan P.A. of 19' 13, , 19_76, established in conformance with regulation States Department of the Interier points mentioned in lines 3, stored, established or re-established restablished for Land Surveyors or, by
A. Description of original mon	nument and accessories and/or	subsequent restoration:	
B. Description of corner evider	nce found and/or method app	lied in restoring or re-establishi	ng comer;
Found 1" pipe as lo	cated and witnessed l	by Henning in 1954 sur	<del>-</del>
Found 1" pipe as lo  Set at calculated i  Set by standard sur  C. Description of monument fo	ncated and witnessed land intersection of true land invey procedure.	by Henning in 1954 sur	vey of Section 23.
Found 1" pipe as lo  Set at calculated i  Set by standard sur  C. Description of monument for  K-9  Set DNR monument	ntersection of true of	by Henning in 1954 sur	e position of the corner:
Found 1" pipe as loop Set at calculated in Set by standard sur  C. Description of monument for K-9	cated and witnessed lantersection of true servey procedure.  From corner and accessories estable to the servey procedure and accessories accessories and accessories and accessories accessories and accessories accessories and accessories accessori	by Henning in 1954 sure a lines.  Since to perpetuate locating the lines are the locating the lo	e position of the corner:
Found 1" pipe as lo  Set at calculated i  Set by standard sur  C. Description of monument for  K-9  Set DNR monument	cated and witnessed lantersection of true servey procedure.  From corner and accessories estable to the servey procedure and accessories accessories and accessories and accessories accessories and accessories accessories and accessories accessori	by Henning in 1954 sure a lines.  Since to perpetuate locating the lines are the locating the lo	e position of the corner:
Found 1" pipe as lo  Set at calculated i  Set by standard sur  C. Description of monument for  K-9  Set DNR monument	cated and witnessed lantersection of true servey procedure.  or corner and accessories estable L-10 Set 14"x24" pi red-top post 6" J. Pine S7 4 7" J. Pine N2	by Henning in 1954 sure lines.  Set lines Set	e position of the corner:
Found 1" pipe as look  Set at calculated in  Set by standard sur  C. Description of monument for  K-9  Set DNR monument  12" R. Oak S71°W 72.  12" R. Oak N49°E 98.  6" J. Pine S75°E 30.	cated and witnessed lantersection of true servey procedure.  The corner and accessories estable to the corne	by Henning in 1954 sure lines.  Set lines Set	e position of the corner:
Found 1" pipe as 10  Set at calculated in the control of the contr	cated and witnessed intersection of true intersection of true invey procedure.  To corner and accessories established in the corner and accessories establis	by Henning in 1954 sure lished to perpetuate locating the pe & Set re So E 5.5 5" J O E 24.85 8" J	e position of the corner: