

# LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF --:	LOCATED IN --:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>28</u> N. <u>●</u> , R. <u>1</u> E. <u>●</u>	<u>A-6</u>
2. PROPERTY CONTROLLING IN SECTION <u>31</u>	, T. <u>28</u> N. <u>●</u> , R. <u>1</u> E. <u>●</u>	<u>6; 13;</u>
3. MISCELLANEOUS PROPERTY IN SECTION _____	, T. _____ N. _____, R. _____ E. _____	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, KENNETH J. OSTLING, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on APRIL 23, 1982, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- 6 SET CORNER BY STANDARD SURVEY PROCEDURE FOR THE SUBDIVISION OF SECTIONS.
- 13 SET CORNER BY STANDARD SURVEY PROCEDURE FOR THE SUBDIVISION OF SECTIONS.
- A-6 SET CORNER MIDPOINT, ON LINE BETWEEN SECTION CORNERS. FOUND SCHAAF CORNER WITHIN 1' OF TRUE POSITION.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

<u>6</u>	<u>13</u>	<u>A-6</u>
SET 5/8" ROD W/RLS CAP	SET 5/8" ROD W/RLS CAP	SET DNR MONUMENT & RED TOP POST
6" J. PINE N60°E 29.0'	10" J. PINE S12°W 14.2'	2" R. PINE S35°E 51.25'
8" J. PINE N72°W 10.0'	8" J. PINE N58°W 20.7'	2" R. PINE N31°E 21.18'
		E: 1/4 SEC 13, T28-1W NORTH 69.7'

SIGNED BY Kenneth Ostling

DATE 9

SURVEYOR'S MICHIGAN REGISTRATION NO. #10068



FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_

OSCODA COUNTY