OSCODA ✓

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF–:	LOCATED IN–:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 28 N., R. 3 E.	B-7 C-8 C-2 G-1
2. PROPERTY CONTROLLING IN SECTION	,T. N., R. E.	
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N., R. E.	
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram – over) were, in a field survey on 12-28 19 72, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19__, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

B-7 Set corner by proportionate measurement between section corners.

C-2 Set corner by proportionate measurement between section corners.

C-8 Set corner by proportionate measurement between section corners.

G-1 Set on line and double distance the West 1/2 mile, which fits Randall's record measurement exactly and holds to Randall's 1/4 corner. Witness stump NE facing near this point, which could apply to this corner but can find no record in road cut.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-7	C-2	C-8	G-1
Set DNR Mon.	Set DNR Monument	Set DNR Mon	Set DNR Mon & Ced
13" R Oak S08W 10.2'	5" R Pine S12E 50.1'	9" Ironwood S14W 4.3'	Post 16.5' North
5" R.Pine N79E 7.3'	17" R Pine S77E 77.4'	10" Maple N73E 12.2'	(28" W.P.STP S61E 40.3')
18" R.P.StpN42W 41.3'			(20" W.P.Stp N50E 20.8')
			(Cor N33-34 E 33.0')
			(4" Poplar S 35E 22.7')

SIGNED BY Kenneth J Ostling DATE 1/4/73

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

STATE OF MICHIGAN KENNETH J. OSTLING LAND SURVEYOR No. 10068 REGISTERED LAND SURVEYOR (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ (CHIEF OF SURVEY PARTY) DATE _____

APPROVED AND SIGNED BY _____ (MICHIGAN REGISTERED LAND SURVEYOR) DATE _____ (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

Form No. MLM735
DOUBLEDAY BROS. & CO., KALAMAZOO, MICH.

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS