

OSCODA ✓

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER	
		C-6	D-7
1. PUBLIC LAND SURVEY _____	T. <u>28</u> N. <u>●</u> , R. <u>3</u> E. <u>●</u>	C-7	
2. PROPERTY CONTROLLING IN SECTION _____	, T. _____ N. _____ S., R. _____ E. _____ W. _____		
3. MISCELLANEOUS PROPERTY IN SECTION _____	, T. _____ N. _____ S., R. _____ E. _____ W. _____		
4. LOT NO. _____, RECORDED PLAT _____			
5. PRIVATE CLAIMS _____			

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Kenneth J. Ostling do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on 12-26 1972, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:


- C-6 Set corner by proportionate measurement between Section corners.
- C-7 Set corner by double proportionate measurement between corners one mile all directions. Found evidence of an old corner, probably Randall's, about 160' Westerly, but could not justify the great distortion of sections this location would create. Our position fits U.S. record very well, and provides the most equitable distribution of the available lands.
- D-7 Set corner by proportionate measurement between section corners.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-6	C-7	D-7
Set DNR Monument	Set DNR Monument	Set DNR Monument
6" Maple N84W 20.5'	14" R. Pine N39W 54.7'	8" Maple N41E 13.7'
6" Beech N28W 20.0'	9" R. Pine S65E 36.1'	11" Maple S67E 17.9'
	Top of steep hill.	

SIGNED BY Kenneth Ostling DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068



FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____