

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:			
Otsego	Located In	Corner Code #	
(County)			
1. Public Land Survey	T _____ R _____		
	T _____ R _____		
2. Property Controlling in Section	S 25 T 29N R 4W	3	
	S _____ T _____ R _____		
3. Miscellaneous Property in Section	S _____ T _____ R _____		
	S _____ T _____ R _____		
4. Lot No: _____	Recorded Plat: _____		
5. Private Claims: _____			

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

I, Carl T. Kiiskila, in a field survey on October 31, 2002 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

3- Gerald R. McKelvey R.L.S. #19001 set this corner while doing a survey in the area in 1974.

B. Description of corner evidence found and/or method applies in restoring or re-establishing corner:

3- Found and accepted a 4" concrete monument with a 1/2" iron bar as set by Gerald R. McKelvey.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

3- 4" Concrete Monument

Wit: 24" W Pine	N30°E	24.09'
24" W. Pine	S69°E	18.62'
10" W. Pine	S25°W	12.38'
8" W. Pine	S89°W	59.80'
E-W smooth fence	South	45'±
Carsonite Post	North	1'±



Signed by: Carl T. Kiiskila
Surveyor's Michigan License No.: 33981

Date: 1-8-03