LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:	LOCATED IN-:	CORNER CODE NUMBER	1
I, PUBLIC LAND SURVEY	т. <u>31 </u> N: к. <u>1</u> v.	D-10; E-10	
2. PROPERTY CONTROLL- ING IN SECTION—	28 ,T. 31 N. R. 1 W.	12; 10	
	N. S., R. — E. W.		
4. LOT NO , RI	ECORDED PLAT		
5. PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND FILING NUMBER
the corner points mentioned in re-established, monumented, and rules therefore as require Bureau of Land Management and 5 above were, in a field su	n lines 1 and 2 above were, in a re-monumented, recovered or re d in the current manual of surve or by a decree of a court of law,	field survey onNovemberstored as expressed below and expressed below and expressed below and expressed for the United Expressed for the corner of the	of P.A. 74, Michigan P.A. of 1970, er 10 , 1980 , established, d in conformance with regulations States Department of the Interior, er points mentioned in lines 3, 4 stored, established or re-established tration for Land Surveyors or, by a
እአአማፍኛክክማማለጃጀማጃዝኞቹ C. Continued:	⁽	XKXXKXXX XXXXXXXXX	
10 Set 5/8" rod w/RLS	can	Fd. DNR mon. in	E-10
6" Cedar	S80°E 3.5' N13°E 11.3'	*8" Cedar *6" Cedar	N10°E 6.3' S52°W 19.1'
		*Old Wit.	
Found corner as a section subdivis Set corner by sta		e for the subdivision	•
C. Description of monument	for corner and accessories established	lished to perpetuate locating th	ne position of the corner:
n 10			12
Set 5/8" rod W/RLS 4" cedar 5" Cedar	cap S48°W 5.8' S20°E 9.1'	Nail in 8" Maple Nail in 5" Maple	e N65°W 30.3' e in clump N24°E 23.1'
			WHITE OF A
<i>~</i>	REGISTRATION NO. 1000		
SIGNED BELLINIE	The Welling	DATE	3/12/81
SURVEYOR'S MICHIGAN	REGISTRATION NO. 1006	58	(SEAL)
FOR STATE AND UNITED	STATES AGENCIES:		· · · · · · · · · · · · · · · · · · ·
SIGNED BY	CUISE OF SUBVEY PARTY	DATE	
APPROVED AND SIGNED	BYMICHIGAN REGISTERED L	DATE_	(SEAL)
SURVEYOR'S MICHIGAN	REGISTRATION NO	0	TSEGO COUNTY