## LAND CORNER RECORDATION CERTIFICATE

## FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF -:			
1. PUBLIC LAND SURVEY	T S., R E	:	
2. PROPERTY CONTROLL- ING IN SECTION—	5 ,T. 31 N. R. 1 W	5; 6; 9	
3. MISCELLANEOUS PROPERTY IN SECTION—	,T		
4. 1.OT NO	CORDED PLAT	· · · · · · · · · · · · · · · · · · ·	
5. PRIVATE CLAIMS			REGISTER OF DEEDS STAMP AND FILING NUMBER
the corner points mentioned in re-established, monumented, re- and rules perefore as required Bureau of Land Management of and 5 above were, in a field sur-	lines 1 and 2 above were, in e-monumented, recovered or in the current manual of sur or by a decree of a court of law evey on	a field survey on FEBRUARY restored as expressed below and vey instructions of the United w. Furthermore, that the corner, 19, found, recovered, respectively.	of P.A. 74, Michigan P.A. of 1970 [22], 1982, established d in conformance with regulation States Department of the Interior er points mentioned in lines 3, stored, established or re-establishe tration for Land Surveyors or, by
A. Description of original mor	nument and accessories and/or	subsequent restoration:	
B. Description of corner evide	ence found and/or method app	plied in restoring or re-establishi	ng corner:
-		plied in restoring or re-establishi	
5 SET CORNER BY STANDAR	RD SURVEY PROCEDURE F	OR THE SUBDIVISION OF	SECTIONS.
5 SET CORNER BY STANDAR	RD SURVEY PROCEDURE F	OR THE SUBDIVISION OF	SECTIONS.
5 SET CORNER BY STANDAR 6 SET CORNER BY STANDAR	RD SURVEY PROCEDURE F	OR THE SUBDIVISION OF	SECTIONS.
5 SET CORNER BY STANDAR 6 SET CORNER BY STANDAR 9 SET CORNER BY STANDAR	RD SURVEY PROCEDURE F RD SURVEY PROCEDURE F RD SURVEY PROCEDURE F	OR THE SUBDIVISION OF OR THE SUBDIVISION OF OR THE SUBDIVISION OF	SECTIONS. SECTIONS.
5 SET CORNER BY STANDAR 6 SET CORNER BY STANDAR 9 SET CORNER BY STANDAR C: Description of monument f	RD SURVEY PROCEDURE F RD SURVEY PROCEDURE F RD SURVEY PROCEDURE F for comer and accessories esta	OR THE SUBDIVISION OF OR THE SUBDIVISION OF OR THE SUBDIVISION OF blished to perpetuate locating the	SECTIONS.  SECTIONS.  SECTIONS.  de position of the corner:
5 SET CORNER BY STANDAR 6 SET CORNER BY STANDAR 9 SET CORNER BY STANDAR C: Description of monument f	RD SURVEY PROCEDURE F RD SURVEY PROCEDURE F RD SURVEY PROCEDURE F for comer and accessories esta	OR THE SUBDIVISION OF OR THE SUBDIVISION OF OR THE SUBDIVISION OF blished to perpetuate locating the	SECTIONS.  SECTIONS.  SECTIONS.  de position of the corner:
5 SET CORNER BY STANDAR 6 SET CORNER BY STANDAR 9 SET CORNER BY STANDAR C: Description of monument f	RD SURVEY PROCEDURE F RD SURVEY PROCEDURE F RD SURVEY PROCEDURE F for comer and accessories esta	OR THE SUBDIVISION OF OR THE SUBDIVISION OF OR THE SUBDIVISION OF blished to perpetuate locating the	SECTIONS.  SECTIONS.  SECTIONS.  de position of the corner:
5 SET CORNER BY STANDAR 6 SET CORNER BY STANDAR 9 SET CORNER BY STANDAR	RD SURVEY PROCEDURE F RD SURVEY PROCEDURE F RD SURVEY PROCEDURE F for comer and accessories esta	OR THE SUBDIVISION OF OR THE SUBDIVISION OF OR THE SUBDIVISION OF blished to perpetuate locating the	SECTIONS.  SECTIONS.  SECTIONS.  de position of the corner:
5 SET CORNER BY STANDAR 6 SET CORNER BY STANDAR 9 SET CORNER BY STANDAR C: Description of monument f	RD SURVEY PROCEDURE F RD SURVEY PROCEDURE F RD SURVEY PROCEDURE F for comer and accessories esta	OR THE SUBDIVISION OF OR THE SUBDIVISION OF OR THE SUBDIVISION OF blished to perpetuate locating the	SECTIONS.  SECTIONS.  SECTIONS.  de position of the corner:
5 SET CORNER BY STANDAR 6 SET CORNER BY STANDAR 9 SET CORNER BY STANDAR  C. Description of monument f SET 5/8" SOD W/CAP O" J. PINE N37°W 23.8 O" J. PINE N11°E 28.2	RD SURVEY PROCEDURE F  RD SURVEY PROCEDURE F  for corner and accessories esta  SET 5/8" ROD W/  8' 6" R. MAPLE NI 2' 5" R. MAPLE NE	OR THE SUBDIVISION OF OR THE SUBDIVISION OF OR THE SUBDIVISION OF blished to perpetuate locating the CAP SET 5/8 <sup>7</sup> 3°W 6.8' 20" W. F 3°E 11.6' 12" R. F	SECTIONS.  SECTIONS.  SECTIONS.  de position of the corner:
5 SET CORNER BY STANDAR 6 SET CORNER BY STANDAR 9 SET CORNER BY STANDAR  C. Description of monument f  ET 5/8" SOD W/CAP 0" J. PINE N37°W 23.8 0" J. PINE N11°E 28.2	RD SURVEY PROCEDURE F  RD SURVEY PROCEDURE F  for corner and accessories esta  SET 5/8" ROD W/  8' 6" R. MAPLE NI 2' 5" R. MAPLE NE	OR THE SUBDIVISION OF OR THE SUBDIVISION OF OR THE SUBDIVISION OF blished to perpetuate locating the CAP SET 5/8 <sup>7</sup> 3°W 6.8' 20" W. F 3°E 11.6' 12" R. F	SECTIONS.  SECTIONS.  SECTIONS.  de position of the corner:
5 SET CORNER BY STANDAR 6 SET CORNER BY STANDAR 9 SET CORNER BY STANDAR  C. Description of monument f  ET 5/8" ROD W/CAP 0" J. PINE N37°W 23.8 0" J. PINE N11°E 28.2	RD SURVEY PROCEDURE F  RD SURVEY PROCEDURE F  FOR corner and accessories esta  SET 5/811 ROD W/  81 611 R. MAPLE NO  21 511 R. MAPLE NO	OR THE SUBDIVISION OF OR THE SUBDIVISION OF OR THE SUBDIVISION OF blished to perpetuate locating the CAP SET 5/8 <sup>1</sup> 3°W 6.8' 20" W. F 3°E 11.6' 12" R. F	SECTIONS.  SECTIONS.  SECTIONS.  de position of the corner:
5 SET CORNER BY STANDAR 6 SET CORNER BY STANDAR 9 SET CORNER BY STANDAR  C. Description of monument f SET 5/8" SOD W/CAP O" J. PINE N37°W 23.8 O" J. PINE N11°E 28.2	RD SURVEY PROCEDURE F  RD SURVEY PROCEDURE F  FOR corner and accessories estated for c	OR THE SUBDIVISION OF OR THE SUBDIVISION OF OR THE SUBDIVISION OF blished to perpetuate locating the CAP SET 5/8 <sup>1</sup> 3°W 6.8' 20" W. F 3°E 11.6' 12" R. F	SECTIONS.  SECTIONS.  SECTIONS.  de position of the corner:
5 SET CORNER BY STANDAR 6 SET CORNER BY STANDAR 9 SET CORNER BY STANDAR  C. Description of monument for the standar of the standard of	RD SURVEY PROCEDURE F  RD SURVEY PROCEDURE F  FOR corner and accessories esta  SET 5/8" ROD W/  8' 6" R. MAPLE NI 2' 5" R. MAPLE NI 2' 5" R. MAPLE NE  EGISTRATION NO. #1006  STATES AGENCIES:	OR THE SUBDIVISION OF OR THE SUBDIVISION OF OR THE SUBDIVISION OF blished to perpetuate locating the CAP SET 5/8 <sup>1</sup> 3°W 6.8' 20" W. F 3°E 11.6' 12" R. F	SECTIONS.  SECTIONS.  SECTIONS.  de position of the corner:
5 SET CORNER BY STANDAR 6 SET CORNER BY STANDAR 9 SET CORNER BY STANDAR  C: Description of monument f  ET 5/8" ROD W/CAP  O" J. PINE N37°W 23.8  O" J. PINE N11°E 28.2  SURVEYOR'S MICHIGAN RI  FOR STATE AND UNITED  SIGNED BY	RD SURVEY PROCEDURE F  RD SURVEY PROCEDURE F  FOR corner and accessories esta  SET 5/8" ROD W/  8" 6" R. MAPLE NO  2" 5" R. MAPLE NO  EGISTRATION NO. #1006  STATES AGENCIES:	OR THE SUBDIVISION OF OR THE SUBDIVISION OF OR THE SUBDIVISION OF blished to perpetuate locating the CAP SET 5/8 <sup>1</sup> 3°W 6.8' 20" W. F 3°E 11.6' 12" R. F  DATE DATE DATE	SECTIONS.  SECTIONS.