LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF –:	LOCATED IN –:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 31 N., R. 4 W.	H-3;H-5;G-3;G-5
2. PROPERTY CONTROLLING IN SECTION	T. N. S., R. E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. S., R. E. W.	
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, KENNETH J. OSTLING, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on OCTOBER 18, 19 83, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19___, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. CONTINUED:

G-5

LEFT 3/4" PIPE W/RLS CAP IN PLACE

8" TWIN CHERRY	N81°E	46.3'
8" R. MAPLE	S1°W	11.3'
P. POLE	S24°W	34.9'

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

H-3 - FOUND 1/2" IRON BAR IN PLACE OF RECORD FROM SURVEY BY G.F.D. IN 1922.
H-5 - FOUND 1/2" IRON BAR IN PLACE, PROBABLY ESTABLISHED BY A G.F. DELAMATER IN 1938 SURVEY.
G-3 - FOUND CORNER AS ESTABLISHED BY G.F.D. SURVEY AND USED BY C.I. ROBINSON ASSOC. IN SECTION 4 SURVEY.
G-5 - FOUND 3/4" PIPE IN PLACE IN E-W ROAD, AS PREVIOUSLY LOCATED AND USED BY WYNN WAKENHUT, R.L.S.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

H-3			H-5			G-3		
SET DNR MONUMENT			SET DNR MONUMENT			FOUND 1/2" BAR W/RLS CAP 19001		
6" S. MAPLE	S24°W	10.5'	7" R. MAPLE	S56°E	7.6'	SET POST W/LOC TAG	N4°E	20.0'
7" S. MAPLE	S57°E	10.0'	5" R. MAPLE	S59°W	10.0'	FD ENCASED CONC 4"DIA	S41°E	46.8'

SIGNED BY Kenneth J Ostling DATE 2/6/

SURVEYOR'S MICHIGAN REGISTRATION NO. 10068

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

STATE OF MICHIGAN KENNETH J. OSTLING LAND SURVEYOR No. 10068 REGISTERED LAND SURVEYOR SEAL

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ OTSEGO COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET