## LAND CORNER RECORDATION CERTIFICATE FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

	FOR CORNERS OF -:	EQUALE:	D IN-:	CORNER CODE NUMBER	
	1. PUBLIC LAND SURVEY	т. 31	N. R. 4	G=2;1-2;1-3	
	2. PROPERTY CONTROLL- ING IN SECTION	_ ,T	N. E. S., R W.		
	3. MISCELLANEOUS PROPERTY IN SECTION	_ ,T	N. S., R E.		
	4. LOT NO , REC	ORDED PLA	Т		
	5. PRIVATE CLAIMS				REGISTER OF DEEDS STAMP AND
		•			FILING NUMBER
	the corner points mentioned in li- re-established, monumented, re- and rules therefore as required i Bureau of Land Management or and 5 above were, in a field surve	mes 1 and 2 monumented in the curren by a decree ey on	above were, in a , recovered or re t manual of surve of a court of law.	field survey on <u>OCTOBER</u> stored as expressed below are sy instructions of the United Furthermore, that the correct 19, found, recovered, re-	of P.A. 74, Michigan P.A. of 1970, 18, , , 19 83, established, and in conformance with regulations States Department of the Interior, er points mentioned in lines 3, 4 estored, established or re-established stration for Land Surveyors or, by a
	Decree of a Court of law:  C. CONTINUED:  Academorphism of period manual	ment, and, no	operanies, and our	subsecuent, sectoration:	
	XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	(XXXXXXXXX	XXXXXXXXXXXX I-3	XXXXXXXXXXXXXXX	
			R MONUMENT		
	,	4" S. I 7" S. I		°E 7.9' °W 31.5'	
G-2	<ul><li>B. Description of corner evidence</li><li>SET CORNER BY PROPORT</li><li>&amp; ASSOC.</li></ul>			=	ing corner: RNISHED BY C.T. ROBINSON
I-2	- SET CORNER BY PROPORT & ASSOC.	TIONATE MI	EASUREMENT,	ACCORDING TO DATA FUL D IN COUNTY SURVEY RE	RNISHED BY C.T. ROBINSON ECORDS, PROBABLY BY G.F.D
I-2 1-3	- SET CORNER BY PROPORT & ASSOC. - FOUND 1/2" IRON BAR F	TIONATE MEROM WITH	EASUREMENT, A ESS OF RECOR  D BY WITNESS  accessories establ	ACCORDING TO DATA FULL  D IN COUNTY SURVEY RE  ES OF RECORD IN COUNT  ished to perpetuate locating the   I-2  SET DNR MONUMENT	RNISHED BY C.T. ROBINSON ECORDS, PROBABLY BY G.F.D TY SURVEY RECORDS. THE position of the corner:
I-2 1-3	- SET CORNER BY PROPORT & ASSOC FOUND 1/2" IRON BAR F - SET CORNER AT POINT F  C. Description of monument for G-2  DNR MONUMENT . MAPLE . MAPLE . ROD W/RLS CAP 16390  SIGNED BY SURVEYOR'S MICHIGAN RECE FOR STATE AND UNITED ST  SIGNED BY	TONATE MEROM WITHING RESCRIBER  CORNER and S65°W SN47°E N4°E LESTRATION STATES AGE	EASUREMENT, A ESS OF RECOR  D BY WITNESS  accessories establ  20.0' 9.6' 44.92'  WNO. 1006:  NCIES:	ACCORDING TO DATA FULL D IN COUNTY SURVEY RES ES OF RECORD IN COUNT  ished to perpetuate locating the I-2  SET DNR MONUMENT 7" S. MAPLE N7°W 5" S. MAPLE S71°W  DATE 2  DATE 2	ECORDS, PROBABLY BY G.F.D  EY SURVEY RECORDS.  The position of the corner:  7.5' 17.4'  KENNETH  OSTLING