## Ottawa County Remonumentation LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

97 JUL 24 PM 2: 25

		Filing Requirer	ment of Act 74, Mich. P.A. 1970	(D1 a)
For	corners in		· 1	REGISTER OF DEEDS
	Ottawa (County)	Located In:	Corner Code ##	OTTAWA COUNTY, MI
2.	Public Land Survey  Property Controlling in Section	T <u>5N</u> R <u>14W</u> T R T R T R S T R S T R	C-4 (W½, 8) Zeeland Twp.	
3.	Miscellaneous	S T R	Reg	gister of Deeds Stamp & File Number
	Property in Sec.	\$ T R		
4.	Lot No	Recorded Plat		A B C D E F G H I J K L !
do in I cur Ma abo Cor exp	hereby certify that under r lines 1 and 2 above were trent manual of survey ins nagement or by a decree ove were in conformance urt of Law; established pressed below:	, in a field survey onApri requirements of P.A. 74, Michigan P.A. of in conformance with regulations and structions of the United States Departn of a Court of Law and/or that the corner with the rules of the Michigan Board of , re-established, monumented, re-mi	f 1970, the corner points mentioned rules therefore as required in the ment of the Interior, Bureau of Land points mentioned in lines 3, 4 and 5 Land Surveyors or by a Decree of a onumented, recovered, found as	3 4 7 8 9 10 11 12 11 12 31 32 33 34 35 36 15 16 17 17 18 18 19 20 21 22 23 24 11 11 12 31 32 33 34 35 36
A.	Description of origina	al monument and accessories and	or subsequent restoration:	
	C-4 GLO April, 1 Calvin Brita Set 1/2 mile Beech 20 S 2 Beech 8 N 2	ain, DS Nail in side post Nail in side 22 E 17 NW 69.05' 22 W 11 Nail in side SW 39.25' SW cor. hse. NE 85.40'	, 1972	L3, P109 pipe Sept., 1976 aple SW 39.25' 53.07' aple WSW 31.87' aple ENE 42.00'
В.	B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:			
		st iron mon. in Mon. c., 1988 NE 42.0' NW 69.48'	Box. (4" Harrison)	A. 345 OTTAWA COUNTY PPROVED 4/21/97
		oted as a careful and ginal corner.	d faithful perpetuati	on of the position
C.	Description of monu	ment for corner and accessories e	established to perpetuate locating t	he position of the corner:
C-4 Cast iron mon. in Mon. Box (4" Harrison)  NW cor. brick garg. N 37° E 137.76'  SW cor. brick hse. N 66° E 85.32'  Nail & Ottawa Co. Remon. Tag in S side PP S 88° E 53.20'  Nail & Ottawa Co. Remon. Tag in S side 28" Maple S 27° W 64.75'  Nail & Ottawa Co. Remon. Tag in SE side 34" Maple S 70° W 31.76'  NW cor. conc. dr. N 15° E 113.06'  C/L bit. N-S, West 1'±  JOHN C.				
	gned byJohn C.	John C Busche  Byeche, P.S.		BUECHE * LAND * SURVEYOR S
Su	urveyor's Michigan Lice	ensje NO	REMON LIBER 3 PAGE 504	PROVED BY MILHERAN STATE BOARD OF LINEYSUFEYORS, JAM. 28, 1 REVISED MAY 14, 1 REVISED JAN., 1

PART A - continued

LCRC L5, P346
Set CIM, Dec., 1988
PP E 53.07'
15" Maple ENE 42.0'
33" Cherry NW 69.48'
26" Maple SW 39.25'

new Adden 2 DAGE

REMON LIBER 3 PAGE 505

ander Stagenstaden

# (1985년 - **AW 1** ) - 국민 (1987년 - 1984년 - 1987년

1 · · · · ·