Ottawa County Remonumentation LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

97 JUL 24 PH 2: 25

For corners in	,gqu	oment of Act 14, mici	Doly dein Bullman
Ottawa	Located In:	C	REGISTER OF DEEDS
(County)	Located III.	Corner Code ##	THE REPORT OF THE PROPERTY OF
			Committee of the state of the s
 Public Land Survey 	. T <u>5N</u> R <u>14W</u>	$I-2 (W_2^1, 2)$	THE WAR CONTRACTOR SHOWS AND SHOW THE
	T R	Zeeland Twp.	A Company of the State of the Company
	· TR		
	T R		
2. Property Controlling	S T R		
in Section	S T R		.)
3. Miscellaneous	S T R		Register of Deeds Stamp & File Number
Property in Sec.	S T R		register of becas clamp at the Humber
	Recorded Plat		A B C D E F G H I J K L M
Private Claims			
			2
			³┡ ┤╌┞╌┞┈┠┈╏╌╏┈ ┩
			4-7-4-8-4-9-4-10-4-11-4-12-4
	, in a field survey on <u>Apr</u>		
	equirements of P.A. 74, Michigan P.A in conformance with regulations a		
	ructions of the United States Depa	•	_
-	f a Court of Law and/or that the corn	· · · · · · · · · · · · · · · · · · ·	
	vith the rules of the Michigan Board		ecree of a
	re-established, monumented, re-	monumented, recovered,	found as
expressed below:			10 - 302928272625
IOTE: Not more than 4	corners, all in the same town a	nd range, may be record	ded 11
on this certificate	9.		12 31 32 33 34 35 36
			13
 Description of original 	I monument and accessories an	d/or subsequent restora	ation:
1-2	LCRC L2, P5	551	LCRC L1, P345
GLO April, 18		iron Sept., 19	74 Set cast iron mon. Sept., 198
	in, DS Spk. in 30"	Manle NF 44 0	9' 18" Maple NNW 59.78'
Set 1/2 mile		Maple NNW 59.	
Sugar 30 S 8		de PP SW 67.13	
Beech 10 N 6		le PP WNW 101.0	
			0/ L 001 0/5/1 0L 4/120
,			OVER
Description of corner	evidence found and/or method	applied in restoring or re	eestablishing corner:
T 0 F			P.A. 345 OTTAWA COUNTY
	st iron mon. (4" Ha		I'M' 949 OT TAWA COUNTY
	PP S 50° W 67.11'		PEER APPROVED 4/21/97
	PP WNW 101.00'		
	e 16" Maple N 25° W		(O) 1)
PK in W side	24" Maple N 25° E	53.44'	10.0.1.
And is accept of the orig		d faithful per	petuation of the position
. Description of monum	ent for corner and accessories	established to perpetua	te locating the position of the corner:
I-2 Cast iron	n mon. (4" Harrison	.	
	PP N 73° W 101.12'		Age.
	PP S 62° W 67.03'		***************************************
	a Co. Remon. Tag in		CAPIE N 20 N 00./0
	. fnd. N 50° W 143.		0° E 114.46'
	. Tha. N 50° W 143. fnd. N 65° E 115.0		OF MICHAEL
		· •	The second of th
	d. E-W, South 5'±		* JOHN C
C/L graver fo	d. N-S, East 2' <u>+</u>		BUECHE **
	A A	A	LAND X
*	John C E	2.1	4-16-976 No.
igned by John C. Bu	ache P John C B	wiche Date	13027
urveyor's Michigan Licen			My Comment of the second
stroyor a mioringan Licen	-V		FORM APPROVED BY MICHIGAN STATE BOARDON LIND SUBSTITUTES, JAN. 28, 1971 MALLON MAY 14, 1975
		REMON LIBER 3 PA	AGE 510 REVISED JAN., 1983

PART A - continued

LCRC L6, P18
Cast iron mon. Dec., 1989
PK in NW side PP S 50° W 67.11'
PK in S side PP WNW 101.00'
PK in NE side 16" Maple N 25° W 59.80'
PK in W side 24" Maple N 25° E 53.44'

•

and the second of the second o

The straight of the straight o

A Depth A Man Application (A Depth Application) Application (A Depth Application)

. ...

The second secon