

SURVEY & REMONUMENTATION

APR 24 1995

COMMISSION

**OTTAWA COUNTY REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE**

RECORDED
94 DEC 15 AM 11:45

D. J. Koning
REGISTER OF DEEDS
OTTAWA COUNTY, MI

For corners in

Filing Requirement of Act 74, Mich. P.A. 1970

Ottawa (County)	Located in:	Corner Code #
1. Public Land Survey	T <u>6N</u> R <u>15W</u>	<u>E-9</u>
	T _____ R _____	(SE cor., Sec.
	T _____ R _____	<u>20, Olive Twp.)</u>
	T _____ R _____	
2. Property Controlling in Section	S _____ T _____ R _____	
	S _____ T _____ R _____	
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	
	S _____ T _____ R _____	
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

I, Douglas J. Koning, in a field survey on August 17, 1994, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/of subsequent restoration:

E-9 Government Notes	L.C.R.C. Liber 5, Page 96, December 1983
Set Post May 1832	E-9 Set Cast Iron Monument
By Calvin Britain D.S.	24" Maple NE 52.00'
Beech 24" S80°W 18 Links	Pwr Pole NW 74.63'
Leo 20" N35°E 4 Links	Pwr Pole SW 65.45'
	Pwr Pole SE 54.09'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner.

E-9 Found Cast Iron Monument in Mon. Box
 Nail NW Side 24" Maple NE 52.00'
 Nail & Tag in SW Side Pwr Pole NW 74.62'
 PK Nail in W Side Pwr Pole SE 54.03'

P.A. 345 OTTAWA COUNTY


PEER APPROVED 12/12/94

Walter D. Nedewell

This marker is accepted as a careful and faithful perpetuation of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner.

E-9 Cast Iron Monument in Mon. Box (Centerline "X" Roads N, E, & W)
 O.C. Remon Tag & Nail SW side Pwr Pole N30°W 74.60'
 O.C. Remon Tag & Nail SW side Pwr Pole S20°E 53.93'
 O.C. Remon Tag & Nail NW side 28" Maple N45°E 52.15'
 O.C. Remon Tag & Nail S side 30" Maple N68°W 77.08'



Signed by Douglas J. Koning
 Surveyor's Michigan License No. 35995

Date November 14, 1994