

**SURVEY &
REMONUMENTATION**

FEB 27 1998

SECTION

Ottawa County Remonumentation

LAND CORNER RECORDATION CERTIFICATE

RECORDED

For corners in

Filing Requirement of Act 74, Mich. P.A. 1970

97 DEC -8 AM 11:31

Ottawa (County)	Located in:	Corner Code #
1. Public Land Survey	T <u>6N</u> R <u>15W</u>	<u>I-4</u>
	T _____ R _____	(W 1/4 cor., Sec. 11
	T _____ R _____	Olive Twp.)
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

Ray [Signature]
REGISTER OF DEEDS
OTTAWA COUNTY, MI

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L
2	6	5	4	3	2	1						
3												
4	7	8	9	10	11	12						
5												
6	18	17	16	15	14	13						
7												
8	19	20	21	22	23	24						
9												
10	30	29	28	27	26	25						
11												
12	31	32	33	34	35	36						
13												

I, Douglas J. Koning, in a field survey on November 26, 1997, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

I-1 Government Notes Set Post May 1832 By Calvin Britain D.S. Cherry 10" S52°E 5 Links W. Ash 10" N52°W 8 Links	L.C.R.C. Liber 3, Page 153, January 1977 I-4 Cast Iron Monument 24" Maple SW 36.79' 16" Maple W 76.95' Power Pole NW 71.47'
---	---

L.C.R.C. Liber 3, Page 204, November 1977

I-4 Set Cast Iron Monument 6" Pine WNW 29.15' 28" Maple SW 37.69' Power Pole SSE 91.05'
--

P.A. 345 OTTAWA COUNTY
PEER APPROVED 12-1-97

[Signature]

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner.


I-4 Found Cast Iron Monument
5.5'± East of the Centerline Bit. Road
Found Nail & Tag in Sw Side Power Pole S35°E 91.12'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner.

I-4 3/4" Iron in Monument Box
5.5'± East of the Centerline Bit. Road
Set Tag & Nail in South Side 24" Maple West 77.55'
Set Tag & Nail in SW Side Power Pole N30°W 74.72'
Set Tag & Nail in SE Side Power Pole N26°E 111.27'

THIS MARKER IS BEING WITNESSED AS PART OF A ROAD RECONSTRUCTION PROJECT AND HAS NOT BEEN APPROVED BY THE OTTAWA COUNTY REMONUMENTATION PEER GROUP AT THIS TIME.

Signed by Douglas J. Koning
Surveyor's Michigan License No. 35995



12-1-97

REMON LIBER 3 PAGE 608

\$ 9.00 CORNER
\$ 1.00 PHOTO