

## APR 0 5 1996

## COMMISSION

Signed by

Surveyor's Michigan Vicense No

## OTTAWA COUNTY REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE

RECORDED

For corners in	Filing Require	ement of Act 74	Mich. P.A	<sup>(. 1970</sup> 95 NOV 15	PM 2: 08
Ottawa (County)	Located in:	Corner Code #	<u>.</u>		(Edlonan)
1. Public Land Survey	T_6N_R15W_ TR TR	I-7 (SE cor., Sec. 15 Olive Twp.)		REGIST	ER OF DEEDS A COUNTY. MI
Property Controlling S in Section S      Miscellaneous S Property in Sec. S	TR _TR _TR _TR		Pag	sister of Deeds Stam	M # File Number
4. Lot No, Record			<u> </u>	pater of beeds stain	
5. Private Claims	In a field survey	on October 23	19 95	2 -6 -54	G H ! J K L
do hereby certify that under requiremer in lines 1 and 2 above were in confocurrent manual of survey instructions Management or by a decree of a Court above were in conformance with the recourt of Law; established, re—esta expressed below:  NOTE: Not more than 4 corners,	nts of P.A. /4, Michigon ormance with regulation of the United States D of Law and/or that the ules of the Michigan Boo blished, monumented,	P.A. of 1970, the comer as and rules therefore as epartment of the Interior, corner points mentioned i and of Land Surveyors or lemonumented, recorner	required in the Bureau of Lanc I lines 3,4 and 5 by a Decree of c vered, found as	7	1 - 22 - 23 - 24
on this certificate.	di ili die salio tom	and range, may be to		13	
A. Description of original mor I—7 Cast Iron Monument in Nail and O.C. Remon Tag Wo Nail and O.C. Remon Tag NE Nail and O.C. Remon Tag SE Nail and O.C. Remon Tag Se	Box (Centerline of est side Triple Syco E side Power Pole E side 12" Pine	Crossroads N, S, E, imore N14°W	W)  10.65' 75.10'	P.A. 345 OTTA ER APPROVED_  Suday D.  Suday D.	10/02/06
				DOY	
B. Description of corner evidence of the second of the sec	Box (Centerline of E side Power Pole E side 12" Pine		estoring or re W) 75.10' 57.22' 36.58'	eestablishing corner.	
This marker is accepted					
C. Description of monument	for corner and acc	cessories established	to perpetuat	e locating the position	on of the corner.
I—7 Cast Iron Monument in Nail and O.C. Remon Tag N Nail and O.C. Remon Tag S Nail and O.C. Remon Tag S Set O.C. Remon Tag and P	E side Power Pole E side 12" Pine iw side 54" Maple	Crossroads N, S, E, N56°W S41°W S52°E S55°E	W) 75.10' 57.22' 36.58' 54.45'		

DOUGLAS J. \* Dote /0-20-9 CORN APPROVED BY MICHOAN STATE BOARD OF LAND SURFERON LIBER 2 PAGE 496