

OTTAWA COUNTY REMONUMENTATION  
LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

RECORDED  
93 NOV 11 AM 11:55

*D. J. Koning*  
REGISTER OF DEEDS  
OTTAWA COUNTY, MI

For corners in

Ottawa (County)	Located In:	Corner Code #
1. Public Land Survey	T <u>6N</u> R <u>15W</u>	<u>I-8</u>
	T _____ R _____	<u>(E 1/4 cor. Sec.</u>
	T _____ R _____	<u>22, Olive Twp.</u>
	T _____ R _____	_____
2. Property Controlling in Section	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____
3. Miscellaneous Property in Sec.	S _____ T _____ R _____	_____
	S _____ T _____ R _____	_____

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

I, Douglas J. Koning in a field survey on September 8, 19 93, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

L.C.R.C. L. 1 P. 71 1971	L.C.R.C. L. 3 P. 209 1976
I-8 Centerline St. Sign SE 30.30'	I-8 Set Cast Iron Monument over Stone
Tele. Pole NW 44.14'	Power Pole WNW 64.60'
Power Pole SW 75.85'	Tel. Pole NW 44.45'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I-8 Found C.I. Mon. in Mon. Box  
Nail and Tag in Power Pole WNW 64.60'

This marker is accepted as a careful and faithful perpetuation of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-8 C.I. Mon. in Box (Centerline crossing of Roads)  
Cut "X" S. end Conc. Culvert S45°W 28.22'  
Cut "X" S. end conc. culvert S50°E 26.75'  
Nail & O.C. Remon Tag N. side P. Pole N65°W 64.52'  
Nail & O.C. Remon Tag S. Side P. Pole N87°E 297.02'  
NW Cor. Conc. Blk. Fnd. of Bld. S83°E 275.88'

Signed by *Douglas J. Koning* Date: 10-17-93  
Surveyor's Michigan License No. 35995

