## & Yavnue FENONUMENTATION

Ottawa County Remonumentation

RECORDED

	APR 0 5 1996	wa County Renom	unteritation	0555	The same too
	APR 0 5 1996 LANG	Requirement of A	DATION CERTIFICA	ME AD DEC 15	PM 4: 52
For corners in	COMMISSIOR I	, riequirement of A	ot 14, mion. F.A. 13	Defendas	B. Breeze
Ottawa (County)	Located In:	Corner	Code ##	REGISTER OTTAWA	OF DEEDS COUNTY, MI
Public Land Survey	T <u>T7N</u> F T F T F	? ?			
2. Property Controlling					
in Section 3. Miscellaneous	S F F F			Decister of basels (	Stamu & File Munches
Property in Sec.	S T F			negister of Deeds :	Stamp & File Number
	, Recorded Plat			A B C · D	EFGHIJKLI
5. Private Claims				2 6 5	3 - 2 - 1 -
do hereby certify that unde in lines 1 and 2 above we	na , in a field survey on . r requirements of P.A. 74, Mir re in conformance with reg nstructions of the United St	chiganP.A. of 1970, the co ulations and rules theref	orner points mentioned fore as required in the	3 4 7 8 5 6 18 17 7	16 15 14 13
Management or by a decree above were in conformance	e of a Court of Law and/or that e with the rules of the Michig d, re-established, monume	at the corner points menti gan Board of Land Survey	oned in lines 3, 4 and 5 ors or by a Decree of a	8 19 20	23 23 24 24 25 25
NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.				12 31 32	33 34 35 36
A. Description of origin	nal monument and acces	sories and/or subsequ	uent restoration:	13	<del>*************************************</del>
	in D.S. E 36 lks.	L.C.R.C. records 6, Page 158 - Od (over) L.C.R.C. records 4, Page 329 - Ja (over)	ct. 11, 1991 ed in Liber	(over) L.C.R.C. record 1, Page 441 - (over) L.C.R.C. record	June 20, 1972  rded in Liber  June 9, 1972  rded in Liber
				5, Page 149 - (over)	Aug. 1, 1984
J-7 Found C.I. mon. Found PK nail ir	in mon. box n W side 24" Maple side 6" Thornappl	. N	storing or reestablish NE 78.32' W 59.52'	(OVET) ning corner:	
			F	2A. 345 ÖTTAW.	A COUNTY
				PPRQVED_/_	2/11/95 "
	this corner as a the position of t		urate	Ledoy D. T.	ledeweld 1
C. Description of mont	ument for corner and acc	essories established t	to perpetuate locatin	g the position of the	corner:
Set nail and 0.0 Set nail and 0.0 Set nail and 0.0	n. box C. tag in W side 2 C. tag in N side 1 C. tag in top of w C. tag in N side 6 -S bit.conc. road	4" Ash ood post at T b	N35°E 78.30 N77°W 48.99 OX N84°W 34.69 N41°W 59.55 E 1' S 3'	5' * License st	OF MICHIGAN  AAURICE J.  ROSEMA LAND URVEYOR NO. 27459  FESSIONA  FESSIONA
Sinh.	Inical E. P	NE Omo.	Date	ctober 21, 199	(stittings.
Signed by					BOARD OF LAND SURVEYORS, JAN. 28, 19 REVISED MAY 14, 19 REVISED JAN., 11

## J-7, T7N, R14W

L.C.R.C. recorded in Liber 1, Page 463
- June 20, 1972
Bt Spike on Centerline of B.T.
Spike in 30" Oak
Spike in 18" Hickory
Spike in 16" Maple
On Line ± with fences to E and W

L.C.R.C. recorded in Liber 1, Page 441
- June 9, 1972
3/4" Steel Bar
Cor. Fence Post E 30.25'
Fence Post W 29.50'
Buried cable post W 34.30'

L.C.R.C. recorded in Liber 4, Page 329
- July 19, 1982
Re-Rod in Monument Box
PK in face buried cable post
PK in bent fence post50.80'
Sq. spike in W'ly side 18" Maple
Nail in SE side 20" Hickory
Centerline Blacktop road

Liber 4, Page 329
W 34.30'
W 29.42'
Sq. spike in W'ly side 18" Maple
NNE 78.42'
Centerline Blacktop road

E 1.6'

L.C.R.C. recorded in Liber 5, Page 149

- August 1, 1984

Re-rod in Monument Box

Sq. spike in W'ly side 18" Maple

Nail and B.C. in SE side 20" Hickory

Nail in N side 6" Elm

Centerline blacktop road

NAME 78.35'

W 34.51'

E 1.6'

L.C.R.C. recorded in Liber 6, Page 158

- October 11, 1991

C.I. Monument in Monument Box
5" Tree ESE 35.57'
24" Maple NE 78.34'
14" Ash WNW 48.74'
6" Thornapple NW 59.54'